

PRODUCT CATALOG







Husky®

GENERAL FUELING PRODUCTS

Table of Content

NOZZLES

Conventional 1-0

Husky 1A

Metal Hand Guard	1-1
Rebuilt Metal Hand Guard	1-17
Polymer Hand Guard.....	1-2
Rebuilt Polymer Hand Guard.....	1-18

Husky X

Standard	1-4
BSPP	1-5
Cold Weather	1-6
Double Poppet	1-7
Rebuilt	1-8
Sightglass	1-9
Rebuilt Cold Weather	1-19
EZ Lever PGH.....	1-27
WPHG PGH.....	1-44

Husky XS®

Standard	1-10
BSPP	1-11
Cold Weather	1-12
Double Poppet	1-13
MFM	1-14
Rebuilt	1-15
Sightglass	1-16
Rebuilt Cold Weather	1-20
PHG	1-28
XS EZ Lever PGH.....	1-32
XS MFM	1-40
XS EZ Lever Cold Weather PGH	1-42
XS Cold Weather PGH.....	1-43
XS Bellows Splash Guard	1-45
XS EZ Lever BSP PGH Sightglass	1-46

Husky Eco

Enhanced Conventional	1-33
-----------------------------	------

Husky 1AS

Polymer Hand Guard.....	1-36
Metal Hand Guard	1-37
Cold Weather Metal Hand Guard.....	1-38
Cold Weather Polymer Hand Guard	1-39

Farm and Commercial 2-0

Husky 1GS

Aluminum Hand Guard.....	2-1
Polymer Hand Guard.....	2-2
Rebuilt	2-3
Rebuilt Metal Hand Guard	2-7
Cold Weather	2-5

Husky XFS

Standard	2-4
Rebuilt	2-6

Husky 1GSS

Polymer Hand Guard.....	2-8
Metal Hand Guard	2-9
Cold Weather Polymer	2-10
Cold Weather Metal.....	2-11

Diesel Exhaust Fluid..... 3-0

DEF Stainless Steel.....	3-1
DEF Polymer	3-2
DEF X Nozzles	3-3

Truck and High Volume..... 4-0

1690/1691	4-1
1690 Cold Weather.....	4-2

Husky 1HS

Aluminum Hand Guard.....	4-3
Polymer Hand Guard.....	4-4

Husky VIII

Standard.....	4-5
BSPP	4-6
Cold Weather.....	4-7
Rebuilt	4-11
VIII Nozzles.....	4-14
VIII Cold Weather.....	4-16
Rebuilt	4-18
BSPP	4-20

Husky VIIIS

Standard	4-8
BSPP	4-9
Cold Weather	4-10
Rebuilt	4-12
Rebuilt BSPP.....	4-13
Standard	4-15
Cold Weather	4-17
Rebuilt	4-19

Husky 1HSS

Polymer Hand Guard.....	4-23
Metal Hand Guard	4-24
Cold Weather Polymer	4-25
Cold Weather Metal Hand Guard.....	4-26

Vapor Recovery 5-0

Husky V34

Standard	5-4
Coax Nozzle	5-5
Double Poppet	5-6
ORVR Vacuum Assist	5-7



Husky®

GENERAL FUELING PRODUCTS

Husky V34i	
Standard	5-8
Double Poppet	5-9
Double Poppet / Cold Weather	5-10

Husky V34iA	
Double Poppet	5-11

Husky 34iS	
Standard	5-12
Double Poppet	5-13

Husky V34iSA	
Double Poppet	5-1

Husky V34iSK	
Double Poppet Sightglass	5-2

Ethanol Fueling	6-0
X E25	6-5
X E25 Cold Weather	6-7
X E85	6-1
X E85 Cold Weather	6-2
XS E25	6-6
XS E25 Cold Weather	6-8
XS E85	6-3
XS E85 Cold Weather	6-4

Whiskey Nozzles	8-0
WN	8-1
X WN	8-2
1A WN	8-3
VIII WN	8-4
1690 WN	8-5

ACCESSORIES

Swivels	9-0
Standard	9-1
Inline	9-2

Farm & Commercial	
Standard	9-3
Truck & High Volume	9-4

Vapor Recovery	9-5
-----------------------------	------------

Truck & High Volume	
Diesel	9-6
High Volume	9-7

Diesel Exhaust Fluid	
Stainless Steel – Model 007214, 007285, 007356, 008413, 010579 and 010675	9-8
Polymer – Model 010227, 010549, 010551 and 010553	9-8

Ethanol Fueling	
E85 Swivel	9-9

Safe-T-Breaks	10-0
----------------------------	-------------

Conventional	
Standard	10-1
MagBreak®	10-2
Vac Assist MagBreak®	10-10
E25/E85 MagBreak®	10-14

Farm & Commercial	
Standard	10-3
Truck & High Volume	10-4

Diesel Exhaust Fluid	
Husky DEF	10-5

Truck and High Volume	
Truck & High Volume	10-6

Vapor Recovery	
Balance Vapor	10-7
Vacuum Assist	10-8

Ethanol Fueling	
E85 STB	10-9
E25 STB	10-11

Inline Safe-T-Break	
Inline STB	10-12

Swivel / Safe-T-Break Combos ...	11-0
---	-------------

Conventional	11-1
Truck & High Volume	11-2
Inline Combo	11-3

Guards	12-0
---------------------	-------------

Nozzle and STB Guards	12-1
Nozzle POPD™ Guards	12-2

Spouts	13-0
---------------------	-------------

X and XS Spout Assembly	13-1
1GS Spout Assembly	13-3
DEF Spout Assembly	13-4
VIII and VIIS Spout Assembly	13-5
V, V3 and V34 Spout Assembly	13-6
E85 Spout Assembly	13-7

Pressure/Vacuum Vents	14-0
------------------------------------	-------------

Model 8060	14-1
Model 4620	14-2
Model 4885	14-2
Model 5885	14-2

Test & Maintenance	15-0
-------------------------------------	-------------

Nozzle Service Kit	15-1
HCA Hose Conversion Adaptor	15-2



Husky®

GENERAL FUELING PRODUCTS

Flo-Equalizer™ 16-0

Conventional Systems

Husky 004490, 007490 16-1

Recovery Systems

Husky 005827 16-1

Husky 005837 16-1

DEF Adaptors 17-0

Stainless Steel Adaptors (007214, 007285, 007356, 008413, 010579 and 010675, 011477 and 012872) 17-1

Polymer Adaptors (010227, 010549, 010551 and 010553) 17-1

HOSES

Curb Hoses 18-0

Curb Hoses

EagleFlex® Hardwall 18-1

EagleFlex® Softwall 18-2

EagleFlex® Wirebraid 18-3

Low Perm Hardwall Hose 18-7

Farm Fueling Hoses

Premier 18-4

Farm Fueling Hoses

Whip Hoses 18-5

Low Perm Whip Hose 18-8

DEF Dispensing Hoses 18-6

Fuel Oil Hose 18-9

EZ-Connect 19-0

EZ-Connect 19-1

OIL BARON 20-0

Oil Baron 20-1

Oil Baron Plus 20-2




Table of Contents

OIL FILTER CRUSHERS.....1-0

C-4	1-1
C-6	1-2
TT-12	1-3
TT-25	1-4
Crusher Stands.....	1-5

Gauges.....2-0

Black Knight.....	2-1
Metric Black Knight.....	2-2
Red Fox.....	2-3
Metric Red Fox.....	2-4
Jarhead	2-5
Adjustable Jarhead	2-6
Overfill.....	2-7
Leak Guard	2-8
Seasee Drum Gauge.....	2-9
DEF Black Knight.....	2-10
Clearly Gauge LLG.....	2-11

Tank Gauges and Alarms3-0

Gauges and Alarms

007	3-1
Sentry Tank Alarm	3-2
Sentry Wall Mount.....	3-3

Tank Gauges and Alarms3-0

DEF Tank Gauges

with Jarhead.....	3-4
with Overfill	3-5
007 with Jarhead	3-6
007 with Overfill.....	3-7
Sentry with Jarhead	3-8
Sentry with Overfill.....	3-9
55 Drum Alert	3-10
55 Drum Alarm	3-11
FNTM 55 Drum Alert	3-12
Kalkey Commander Tank Controller	3-13
Kalkey Commander Wall Mount.....	3-14
MK6 Tank Gauge	3-15

Gauge Accessories.....4-0

AD110.....	4-1
Remote Solenoid Valve System	4-2
Solenoid Valves.....	4-3
Siren/Sensor/Strobes	4-4
TM3.....	4-5

Oil Baron5-0

Oil Baron	5-1
Oil Baron Plus	5-2



Table of Contents

Aviation Fueling Hoses	1-0	Aviation Fueling Nozzles	7-0
4113 Permanent Fitting	1-1	Osprey	7-1
4113 Reusable Coupling	1-2	Osprey S	7-2
4113CT Permanent Cold Weather Fitting	1-3	Falcon Nozzle	9-0
JacRiser Fueling Hoses	2-0	Falcon Manual	9-1
5500 JacRiser	2-1	Falcon Quick Disconnect	9-2
Coupling	3-0	Swivels	10-0
Aviation Qualified Couplings	3-1	Aviation Swivel	10-1
Protective Coils	4-0	Aviation Spouts	11-0
Spiral Casings	4-1	Falcon Spout Assembly	11-1
Deadman Hoses	5-0	Aviation Strainer	12-0
Twin 1/4" Hose	5-1	Aviation NPT Strainer	12-1
Sensing Hoses	6-0		
Twin 3/8" Hoses	6-1		



Table of Contents

Loading Arms.	1-0
Hose Loading Arm	1-1



Table of Contents

Sensors.....	1-0
WE-008L.....	1-1





Conventional Nozzles



1A Nozzles



1-1

CONVENTIONAL FUELING

Automatic shut-off nozzle with metal handguard for full-service and self-service stations.

- 1A nozzle shuts off when the gas tank is full.
- Aluminum reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696104N^	with Three Notch Hold Open Clip	3.3 (1.4)
696108	without Hold Open Clip	3.3 (1.4)
696159N^	with Three Notch Hold Open Clip, and Waffle Splash Guard	3.3 (1.4)
696172N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Reducer Bushing	3.3 (1.4)
691209N^	with Three Notch Hold Open Clip and Reducer Bushing	3.3 (1.4)

^ NOT LISTED

New Unleaded Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696116N^	with Three Notch Hold Open Clip	3.4 (1.5)
696120	without Hold Open Clip	3.4 (1.5)

^ NOT LISTED

New Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696103N^	with Three Notch Hold Open Clip	3.4 (1.5)
696107	without Hold Open Clip	3.4 (1.5)
696161N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.4 (1.5)
696173N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Reducer Bushing	3.4 (1.5)
1411303N^	with Two Notch Hold Open Clip, EZ Lever and Full Grip Guard	3.4 (1.5)
6961208N^	with Three Notch Hold Open Clip and Reducer Bushing	3.4 (1.5)

New Light Duty Diesel Nozzles with BSPP


NOT LISTED

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696115N^	with Three Notch Hold Open Clip	3.4 (1.5)
696119	without Hold Open Clip	3.4 (1.5)

Construction

^ NOT LISTED

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x ¾" F Reducer Bushing



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
003376	Mate Handle Guard
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Nozzle Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1A Nozzles




1-2

CONVENTIONAL FUELING

Automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

- 1A nozzle shuts off when the gas tank is full.
- Aluminum reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
209804N [^]	with Three Notch Hold Open Clip	3.3 (1.4)
209808	without Hold Open Clip	3.3 (1.4)
209859N [^]	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
209872N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Reducer Bushing	3.3 (1.4)
2098114N [^]	with Three Notch Hold Open Clip and Spout Plug	3.3 (1.4)
1426404N [^]	with Two Notch Hold Open Clip, EZ Lever and Full Grip Guard	3.4 (1.5)
2098209N [^]	with Three Notch Hold Open Clip and Reducer Bearing	3.3 (1.4)
209843N [^]	with Single Notch Hold Open Clip	3.3 (1.4)
		[^] NOT LISTED

New Unleaded Nozzles with BSPP

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
209816N [^]	with Three Notch Hold Open Clip	3.4 (1.5)
209820	without Hold Open Clip	3.4 (1.5)

New Light Duty Diesel Nozzles with NPT


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
209803N [^]	with Three Notch Hold Open Clip	3.4 (1.5)
209807	without Hold Open Clip	3.4 (1.5)
209861N [^]	with Three Notch Hold Open Clip and Waffle Splash Guard	3.4 (1.5)
209873N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Reducer Bushing	3.4 (1.5)
1426403N [^]	with Two Notch Hold Open Clip, EZ Lever and Full Grip Guard	3.4 (1.5)
2098208N [^]	with Three Notch Hold Open Clip and Reducer Bushing	3.4 (1.5)
2098238 [^]	with Single Notch Hold Open Clip	3.4 (1.5)

New Light Duty Diesel Nozzles with BSPP

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
209815N [^]	with Three Notch Hold Open Clip	3.4 (1.5)

Construction

Body	Die cast aluminum body with black hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x 3/4" F Reducer Bushing



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
007295	Mate Handle Guard
000226	Mate Nozzle Guard
006628	POPD® Clear Cover
006655	POPD® Full Grip Nozzle Guard
007210	POPD® Full Grip Nozzle Reguard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Nozzle Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when the gas tank is full.
- Comes standard with smooth full grip guard.
- Aluminum reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Optional EZ lever:
 - two piece design cuts opening force in half
 - easier "to-the-penny" dispensing
 - ADA Compliant
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.



New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159404N^	with Three Notch Hold Open Clip	3.0 (1.4)
E159404N^	with Three Notch Hold Open Clip	3.1 (1.4)
159408	without Hold Open Clip	3.0 (1.4)
E159408	without Hold Open Clip	3.0 (1.4)
159424N^	with Three Notch Hold Open Clip and Sightglass	2.9 (1.3)
159454N^	with Three Notch Hold Open Clip and Flo-Equalizer®	3.0 (1.4)
159458	without Hold Open Clip, with Flo-Equalizer®	3.0 (1.4)
159459N^	with Three Notch Hold Open Clip and Waffle Splash Guard	2.7 (1.2)
E159459N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	2.7 (1.2)
159468	without Hold Open Clip, with Waffle Splash Guard	2.7 (1.2)
159494N^	with Three Notch Hold Open Clip and POPD® S	2.7 (1.2)
1120404N^	with Two Notch Hold Open Clip and EZ Lever	3.0 (1.4)
159443N^	with Single Notch Hold Open Clip	3.0 (1.4)

^ NOT LISTED


New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159403N^	with Three Notch Hold Open Clip	3.1 (1.4)
E159403N^	with Three Notch Hold Open Clip	3.1 (1.4)
159407	without Hold Open Clip	3.0 (1.4)
E159407	without Hold Open Clip	3.0 (1.4)
159453N^	with Three Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
159457	without Hold Open Clip, with Flo-Equalizer®	3.1 (1.4)
159463N^	with Three Notch Hold Open Clip and Waffle Splash Guard	2.8 (1.3)
159467	without Hold Open Clip, with Waffle Splash Guard	2.8 (1.3)
159496N^	with Three Notch Hold Open Clip, POPD® S and Waffle Splash Guard	2.8 (1.3)
1594122N^	with Three Notch Hold Open Clip and POPD® H	2.8 (1.3)
1594134	without Hold Open Clip	2.8 (1.3)
1594137N^	with Three Notch Hold Open Clip and Waffle Splash Guard	2.8 (1.3)
1120403N^	with Two Notch Hold Open Clip and EZ Lever	3.0 (1.4)
1594238N^	with Single Notch Hold Open Clip	3.0 (1.4)

^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece polymer
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-On Package
003795	Mate Guard
008175	POPD® EZS Nozzle Guard
008176	POPD® EZH Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X BSPP Nozzles



1-5

CONVENTIONAL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when the gas tank is full.
- Aluminum reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159416N^	with Three Notch Hold Open Clip	3.0 (1.3)
159416A*	with Three Notch Hold Open Clip - Atex	3.0 (1.3)
E159416N^	with Three Notch Hold Open Clip	3.0 (1.3)
E159416A*	with Three Notch Hold Open Clip - Atex	3.0 (1.3)
159487A*	with Three Notch Hold Open Clip and Flo-Equalizer® - Atex	3.0 (1.3)
E538498N^	with Three Notch Hold Open Clip, Double Poppet, Waffle Splash Guard and POPD® Mate Guard	3.0 (1.3)
159420	without Hold Open Clip	3.0 (1.3)
E159420	without Hold Open Clip	3.0 (1.3)

^ NOT LISTED


New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159415N^	with Three Notch Hold Open Clip	3.1 (1.4)
159415A*	with Three Notch Hold Open Clip - Atex	3.1 (1.4)
E159415N^	with Three Notch Hold Open Clip	3.1 (1.4)
159486A*	with Three Notch Hold Open Clip and Flo-Equalizer® - Atex	3.1 (1.4)
E538499N^	with Three Notch Hold Open Clip, Double Poppet, Waffle Splash Guard and POPD® Mate Guard	3.1 (1.4)
159419	without Hold Open Clip	3.1 (1.4)
E159419	without Hold Open Clip	3.1 (1.4)

^ NOT LISTED

CONSTRUCTION

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	3/4" / 19 mm NPT



II 1 G
EN 13012
TYPE 1



P-TU7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003385	¾" F x ¾" F BSPP Reconnectable Safe-T-Break®
003385A	¾" F x ¾" F BSPP Reconnectable Safe-T-Break® - Atex
002774	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break®
002774A	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break® - Atex

Swivels

MODEL NO.	DESCRIPTION
003590	¾" M x ¾" F BSPP Multi-Plane Swivel
003590A	¾" M x ¾" F BSPP Multi-Plane Swivel - Atex
002771	¾" M x ¾" F BSPP 90° Pump Swivel
002771A	¾" M x ¾" F BSPP 90° Pump Swivel - Atex

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
007085	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break®
007085A	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with internal screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X CW Nozzles



1-6

CONVENTIONAL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- Aluminum reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
498404N^	with Three Notch Hold Open Clip	3.0 (1.3)
498408	without Hold Open Clip	3.0 (1.3)
498462N^	with Three Notch Hold Open Clip and Waffle Splash Guard	2.7 (1.2)
498466	without Hold Open Clip, with Waffle Splash Guard	2.7 (1.2)

^ NOT LISTED


New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
498403N^	with Three Notch Hold Open Clip	3.1 (1.4)
498407	without Hold Open Clip	3.1 (1.4)
498461N^	with Three Notch Hold Open Clip and Waffle Splash Guard	2.8 (1.2)
498467	without Hold Open Clip, with Waffle Splash Guard	2.8 (1.2)
4984134	without Hold Open Clip, with Waffle Splash Guard, and StreamShaper®	2.8 (1.2)

^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-plane Swivel
000355	¾" M x ¾" F NPT Multi-plane Black Swivel
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Double Poppet allows “to the penny” dispensing.
- Double Poppet is a two (2) step closure reducing the amount of pressure spiking, or “hydraulic hammer” and the adverse effects this has on the hose and dispenser meter.
- Aluminum reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
538404N^	with Three Notch Hold Open Clip	3.1 (1.4)
538424N^	with Three Notch Hold Open Clip and Sightglass	3.1 (1.4)
538476N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
		^ NOT LISTED

New Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
538403N^	with Three Notch Hold Open Clip	3.1 (1.4)
5384135N^	with Three Notch Hold Open Clip and StreamShaper®	3.1 (1.4)
		^ NOT LISTED

New Unleaded Nozzles with BSPP


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
538416N^	with Three Notch Hold Open Clip	3.1 (1.4)
E538416N^	with Three Notch Hold Open Clip	3.1 (1.4)
E538416A*	with Three Notch Hold Open Clip - Atex	3.1 (1.4)
E538420	without Hold Open Clip	3.1 (1.4)
		^ NOT LISTED

New Light Duty Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
538415N^	with Three Notch Hold Open Clip	3.1 (1.4)
E538415N^	with Three Notch Hold Open Clip	3.1 (1.4)
E538419	without Hold Open Clip	3.1 (1.4)
		^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19 mm NPT



II 1 G
EN 13012
TYPE 1



P-TU7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®
003385	¾" F x ¾" F BSPP Reconnectable Safe-T-Break®
003385A	¾" F x ¾" F BSPP Reconnectable Safe-T-Break® - Atex
002774	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break®
002774A*	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break® - Atex

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel
003590	¾" M x ¾" F BSPP Multi-Plane Swivel
003590A	¾" M x ¾" F BSPP Multi-Plane Swivel - Atex
002771	¾" M x ¾" F BSPP 90° Pump Swivel
002771A	¾" M x ¾" F BSPP 90° Pump Swivel - Atex

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®
007085	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break®
007085A	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break® - Atex

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT

005885 2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT **Guards**

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X Rebuilt Nozzles



1-8

CONVENTIONAL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when the gas tank is full.
- Aluminum reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



Rebuilt Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
265704N^	with Three Notch Hold Open Clip	3.1 (1.4)
E265704N^	with Three Notch Hold Open Clip	3.1 (1.4)
265708	without Hold Open Clip	3.1 (1.4)
E265708	without Hold Open Clip	3.1 (1.4)
265724N^	with Three Notch Hold Open Clip and Sightglass	3.1 (1.4)
265744N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.1 (1.4)
265754N^	with Three Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
265758	without Hold Open Clip with Flo-Equalizer®	3.1 (1.4)
265764N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)

^ NOT LISTED


Rebuilt Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
265703N^	with Three Notch Hold Open Clip	3.1 (1.4)
E265703N^	with Three Notch Hold Open Clip	3.1 (1.4)
265707	without Hold Open Clip	3.1 (1.4)
E265707	without Hold Open Clip	3.1 (1.4)
265745N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.1 (1.4)
265753N^	with Three Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
265757	without Hold Open Clip with Flo-Equalizer®	3.1 (1.4)
265763N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)

^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X Sightglass Nozzles



Husky

GENERAL FUELING PRODUCTS

1-9

CONVENTIONAL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when the gas tank is full.
- Stainless steel reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Sightglass on nozzle allows customer to see fuel flow through nozzle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159424N^	with Three Notch Hold Open Clip	3.0 (1.3)
E159424N^	with Three Notch Hold Open Clip	3.1 (1.4)
538424N^	with Hold Open Clip and Double Poppet	3.1 (1.4)
159428	without Hold Open Clip	3.0 (1.3)
E159428	without Hold Open Clip	3.0 (1.3)
1594184N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)

^ NOT LISTED


New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159423N^	with Three Notch Hold Open Clip	3.1 (1.4)
E159423N^	with Three Notch Hold Open Clip	3.1 (1.4)
538423N^	with Three Notch Hold Open Clip and Double Poppet	3.1 (1.4)
159427	without Hold Open Clip	3.0 (1.3)
E159427	without Hold Open Clip	3.0 (1.3)

^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	3/4" / 19.1 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS



Sightglass Nozzles

Automatic shut off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.




Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS[®] nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop[®] device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper[®]* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- Optional EZ Lever:
 - two piece design cuts opening force in half
 - easier "to-the-penny" dispensing
 - ADA compliant



Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon [®]
Lever	Single-piece polymer lever or two-piece polymer EZ lever
Inlet	3/4" / 19.1 mm NPT



New Unleaded Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159504	with Three Notch Hold Open Clip	3.1 (1.4)
E159504	with Three Notch Hold Open Clip	3.1 (1.4)
159508	w/o Hold Open Clip	3.1 (1.4)
E159508	with Hold Open Clip	3.1 (1.4)
159543	with Single Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer [®]	3.1 (1.4)
159544	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer [®]	3.2 (1.4)
159554	with Three Notch Hold Open Clip and Flo-Equalizer [®]	3.1 (1.4)
159558	w/o Hold Open Clip with Flo-Equalizer [®]	3.1 (1.4)
159559	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
159566	w/o Hold Open Clip with Waffle Splash Guard	3.0 (1.3)
159575	w/o Hold Open Clip with 1807 Waffle Splash Guard	3.0 (1.3)
159576	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
159579	w/o Hold Open Clip with 1807 Waffle Splash Guard	3.0 (1.3)
159582	with Three Notch Hold Open Clip and Drip Less Spout	3.0 (1.3)
159589	with Single Notch Hold Open Clip, POPD [®] S and Waffle Splash Guard	3.0 (1.3)
159595	with Three Notch Hold Open Clip, POPD [®] S and Waffle Splash Guard	3.1 (1.4)
1302704	with Three Notch Hold Open Clip with GPR	3.1 (1.4)
1302708	w/o Hold Open Clip with GPR	3.1 (1.4)
1595106	with Two Notch Hold Open Clip	3.0 (1.3)
1595108	w/o Hold Open Clip, with POPD [®] S and Waffle Splash Guard	3.0 (1.3)
1595128	w/o Hold Open Clip and Spout Spring, with Waffle Splash Guard	3.0 (1.3)
1595131	w/o Hold Open Clip and Spout Spring, w/POPD [®] H and Waffle Splash Guard	3.1 (1.4)
1595146	with Three Notch Hold Open Clip, POPD [®] H and Waffle Splash Guard	3.1 (1.4)
1595179	with One Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1595224	with Two Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer [®]	3.1 (1.4)
1595232	with Single Notch Hold Open Clip, POPD [®] H and Waffle Splash Guard	3.1 (1.4)
1595239	with Single Notch Hold Open Clip	3.1 (1.4)
1120504	with Two Notch Hold Open Clip and EZ Lever	3.1 (1.4)
1120559	with Two Notch Hold Open Clip, EZ Lever and Waffle Splash Guard	3.1 (1.4)
13027186	w/o Hold Open Clip and Spout Spring, with Waffle Splash Guard with GPR	3.0 (1.3)

New Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159503	with Three Notch Hold Open Clip	3.1 (1.4)
E159503	with Three Notch Hold Open Clip	3.1 (1.4)
159507	w/o Hold Open Clip	3.1 (1.4)
E159507	w/o Hold Open Clip	3.1 (1.4)
159545	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer [®]	3.2 (1.4)
159553	with Three Notch Hold Open Clip and Flo-Equalizer [®]	3.1 (1.4)
159557	w/o Hold Open Clip with Flo-Equalizer [®]	3.1 (1.4)
159561	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
159567	w/o Hold Open Clip with Waffle Splash Guard	3.1 (1.4)
159577	with Single Notch Clip, POPD [®] and Waffle Splash Guard	3.3 (1.4)
159578	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
159580	w/o Hold Open Clip with 1807 Waffle Splash Guard	3.1 (1.4)
159585	with Single Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer [®]	3.1 (1.4)
159596	with Three Notch Hold Open Clip, POPD [®] and Waffle Splash Guard	3.3 (1.4)
159597	with Single Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1120561	with Two Notch Hold Open Clip, EZ Lever and Waffle Splash Guard	3.1 (1.4)
1595109	w/o Hold Open Clip, with POPD [®] S and Waffle Splash Guard	3.1 (1.4)
1595122	with Three Notch Hold Open Clip, POPD [®] H and Waffle Splash Guard	3.1 (1.4)
1595127	w/o Hold Open Clip and Spout Spring, w/POPD [®] H and Waffle Splash Guard	3.1 (1.4)
1595130	w/o Hold Open Clip and Spout Spring, with Waffle Splash Guard	3.1 (1.4)
1595135	with Three Notch Hold Open Clip	3.1 (1.4)
1595211	with Three Notch Hold Open Clip, Waffle Splash Guard and Drip Less Spout	3.1 (1.4)
1595225	with Two Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1595233	with Single Notch Hold Open Clip, POPD [®] H and Waffle Splash Guard	3.1 (1.4)
1595238	with Single Notch Hold Open Clip	3.1 (1.4)
1120503N [^]	with Two Notch Hold Open Clip and EZ Lever	3.1 (1.4)
11205109	w/o Hold Open Clip, with EZ Lever, POPD [®] S and Waffle Splash Guard	3.1 (1.4)

[^]Not Listed

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks[®]

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break [®]
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break [®]
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break [®]
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break [®]

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break[®] Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break [®]

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop [®]
010434	Unleaded Long Spout without Flo-Stop [®]
001471	Light Duty Diesel Spout without Flo-Stop [®] with StreamShaper [®]
010353	Light Duty Diesel Long Spout without Flo-Stop [®]

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer [®] - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer [®] - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD [®] EZH Nozzle Guard
008175	POPD [®] EZS Nozzle Guard
007999	POPD [®] H Clear Cover
008185	POPD [®] H Full Grip Guard
008192	POPD [®] H Full Grip Reguard
008166	POPD [®] H Mate Guard
006628	POPD [®] S Clear Cover
006665	POPD [®] S Full Grip Guard
007205	POPD [®] S Full Grip Reguard
008165	POPD [®] S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard

XS® BSPP Nozzles



1-11

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159516	with Three Notch Hold Open Clip	3.0 (1.3)
159516A*	with Three Notch Hold Open Clip - Atex	3.0 (1.3)
E159516N^	with Three Notch Hold Open Clip	3.0 (1.3)
E159516	with Three Notch Hold Open Clip	3.1 (1.4)
159520	without Hold Open Clip	3.0 (1.3)
E159520	without Hold Open Clip	3.1 (1.4)

^ NOT LISTED


New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159515	with Three Notch Hold Open Clip	3.0 (1.3)
E159515A*	with Three Notch Hold Open Clip - Atex	3.0 (1.3)
E159516N^	with Three Notch Hold Open Clip	3.0 (1.3)
E159515	with Three Notch Hold Open Clip	3.1 (1.4)
159519	without Hold Open Clip	3.0 (1.3)
E159519	without Hold Open Clip	3.1 (1.4)

^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece polymere
Inlet	¾" / 19.1 mm BSPP



II 1 G
EN 13012
TYPE 1

* U
P-TU7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



XS®

BSPP Nozzles

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003385	¾" F x ¾" F BSPP Reconnectable Safe-T-Break®
003385A	¾" F x ¾" F BSPP Reconnectable Safe-T-Break® - Atex
002774	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break®
002774A	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break® - Atex

Swivels

MODEL NO.	DESCRIPTION
003590	¾" M x ¾" F BSPP Multi-Plane Swivel
003590A	¾" M x ¾" F BSPP Multi-Plane Swivel - Atex
002771	¾" M x ¾" F BSPP 90° Pump Swivel
002771A	¾" M x ¾" F BSPP 90° Pump Swivel - Atex

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
007085	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break®
007085A	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003795	Mate Guard
003440	Mate Easy-on Package
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® CW Nozzles



1-12

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
498104	with Three Notch Hold Open Clip	3.1 (1.4)
498108	without Hold Open Clip	3.1 (1.4)
498162	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
498166	without Hold Open Clip, with Waffle Splash Guard	3.0 (1.3)
498195	with Three Notch Hold Open Clip, POPD® S and Waffle Splash Guard	3.0 (1.3)
1302604	with Three Notch Hold Open Clip with GPR	3.1 (1.4)
1302608	without Hold Open Clip with GPR	3.1 (1.4)
1302659	with Three Notch Hold Open Clip and Waffle Splash Guard with GPR	3.0 (1.3)
1302695	with Three Notch Hold Open Clip, POPD® S and Waffle Splash Guard with GPR	3.0 (1.3)

New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
498103	with Three Notch Hold Open Clip	3.1 (1.4)
498107	without Hold Open Clip	3.1 (1.4)
498161	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
498167	without Hold Open Clip, with Waffle Splash Guard	3.1 (1.4)
498196	with Three Notch Hold Open Clip, POPD® S and Waffle Splash Guard	3.1 (1.4)
4981135	with Three Notch Hold Open Clip	3.1 (1.4)

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



XS®

CW Nozzles

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Black Swivel
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® DP Nozzles



1-13

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Double Poppet allows “to the penny” dispensing.
- Double Poppet is a two (2) step closure reducing the amount of pressure spiking, or “hydraulic hammer” and the adverse effects this has on the hose and dispenser meter.
- A reinforced stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
539604	with Three Notch Hold Open Clip	3.1 (1.4)
539676	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)

New Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
539603	with Three Notch Hold Open Clip	3.1 (1.4)
5396135	with Three Notch Hold Open Clip and Mate Guard with StreamShaper®	3.1 (1.4)

New Unleaded Nozzles with BSPP


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
539616A*	with Three Notch Hold Open Clip - Atex	3.1 (1.4)
539632A*	with Three Notch Hold Open Clip and Sightglass - Atex	3.1 (1.4)
E539616	with Three Notch Hold Open Clip	3.1 (1.4)
E539687	with Three Notch Hold Open Clip Flo-Equalizer® and Mate Guard	3.1 (1.4)
E539620	without Hold Open Clip	3.1 (1.4)

New Light Duty Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E539615	with Three Notch Hold Open Clip	3.1 (1.4)
E539686	with Three Notch Hold Open Clip, Flo-Equalizer®	3.1 (1.4)

CONSTRUCTION

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19 mm NPT or BSPP



II 1 G
EN 13012
TYPE 1



P-TU7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



XS®

DP Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®
003385	¾" F x ¾" F BSPP Reconnectable Safe-T-Break®
003385A	¾" F x ¾" F BSPP Reconnectable Safe-T-Break® - Atex
002774	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break®
002774A	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break® - Atex

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel
003590	¾" M x ¾" F BSPP Multi-Plane Swivel
003590A	¾" M x ¾" F BSPP Multi-Plane Swivel - Atex
002771	¾" M x ¾" F BSPP 90° Pump Swivel
002771A	¾" M x ¾" F BSPP 90° Pump Swivel - Atex

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®
007085	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break®
007085A	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break® - Atex

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® MFM Nozzles



1-14

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- A reinforced stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.



New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159562	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
159568	without Hold Open Clip, with Red VSG, Sightglass and Lenticular Lens	3.0 (1.3)

New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159560	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
539660	with Three Notch Hold Open Clip, Double Poppet and Waffle Splash Guard	3.3 (1.4)
1595267	with Three Notch Hold Open Clip, and Drip Less Spout	3.3 (1.4)

CONSTRUCTION

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky
 GENERAL FUELING PRODUCTS

XS® MFM Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x ¾" F Reducer Bushing



Guards

MODEL NO.	DESCRIPTION
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® Rebuilt Nozzles



1-15

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



Rebuilt Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
265804	with Three Notch Hold Open Clip	3.1 (1.4)
265808	without Hold Open Clip	3.1 (1.4)
265824	with Three Notch Hold Open Clip and Sightglass	3.1 (1.4)
265844	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.1 (1.4)
265854	with Three Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
265858	without Hold Open Clip, with Flo-Equalizer®	3.1 (1.4)
265864	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)

Rebuilt Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
265803	with Three Notch Hold Open Clip	3.1 (1.4)
265807	without Hold Open Clip	3.1 (1.4)
265845	with Three Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
265853	without Hold Open Clip, with Flo-Equalizer®	3.1 (1.4)
265857	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
265863	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS®
Rebuilt Nozzles

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Black Swivel
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® Sightglass Nozzles



1-16

CONVENTIONAL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- A reinforced stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Sightglass on nozzle allows customer to see fuel flow through nozzle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159524	with Three Notch Hold Open Clip	3.1 (1.4)
E159524	with Three Notch Hold Open Clip	3.1 (1.4)
159528	without Hold Open Clip	3.1 (1.4)
E159528	without Hold Open Clip	3.1 (1.4)
1302724	with Three Notch Hold Open Clip with GPR	3.1 (1.4)
E11635236	with Two Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	3.1 (1.4)

New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159523	with Three Notch Hold Open Clip	3.1 (1.4)
E159523	with Three Notch Hold Open Clip	3.1 (1.4)
159527	without Hold Open Clip	3.1 (1.4)
E159527	without Hold Open Clip	3.1 (1.4)

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19.1 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS®
Sightglass Nozzles
Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1A Rebuilt Nozzles



1-17

CONVENTIONAL FUELING

Automatic shut-off nozzle with metal handguard for full-service and self-service stations.

- 1A nozzle shuts off when the gas tank is full.
- Aluminum reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



Rebuilt Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696404N^	with Three Notch Hold Open Clip	3.3 (1.4)
696408	without Hold Open Clip	3.3 (1.4)
696459N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
696472N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Reducer Bushing	3.3 (1.4)

^ NOT LISTED


Rebuilt Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696403N^	with Three Notch Hold Open Clip	3.4 (1.5)
696407	without Hold Open Clip	3.4 (1.5)
696461N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
696473N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Reducer Bushing	3.4 (1.5)

^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

Model No.	Description
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge
000385	1" M x ¾" F Reducer Bushing



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
003376	Mate Handle Guard
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Nozzle Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard

1A Rebuilt Nozzles



1-18

CONVENTIONAL FUELING

Automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

- 1A nozzle shuts off when the gas tank is full.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Aluminum reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



Rebuilt Unleaded Nozzles


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
074704N^	with Three Notch Hold Open Clip	3.5 (1.6)
074708	without Hold Open Clip	3.5 (1.6)
074759N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.5 (1.6)
074772N^	with Three Notch Hold Open Clip, Waffle Splash Guard with Reducer Bushing	3.3 (1.4)
		^ NOT LISTED

Rebuilt Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
074703N^	with Three Notch Hold Open Clip	3.6 (1.7)
074707	without Hold Open Clip	3.6 (1.7)
074761N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.6 (1.7)
074773N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Reducer Bushing	3.0 (1.3)
Reducer Bushing		3.3 (1.4)
		^ NOT LISTED

Construction

Body	Die cast aluminum body with black hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
000385	1" M x ¾" F Reducer Bushing
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
007295	Mate Handle Guard
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Nozzle Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X CW Rebuilt Nozzles



1-19

CONVENTIONAL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- Aluminum reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



Rebuilt Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
503704N^	with Three Notch Hold Open Clip	3.1 (1.4)
		^ NOT LISTED

Rebuilt Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
503703N^	with Three Notch Hold Open Clip	3.1 (1.4)
		^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

X CW Rebuilt Nozzles

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Black Swivel
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



Rebuilt Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
503904	with Three Notch Hold Open Clip	3.1 (1.4)

Rebuilt Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
503903	with Three Notch Hold Open Clip	3.1 (1.4)

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS®
Rebuilt CW Nozzles

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Black Swivel
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008176	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X EZ Lever PHG Nozzles



Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when:
 - the gas tank is full.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- 2-piece lever is easier to use:
 - requires ½ the force to open nozzle.
 - ADA compliant.



New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1163404N	with Two Notch Hold Open Clip	3.0 (1.4)
116342535	without Hold Open Clip, with POPD® S and Waffle Splash Guard	3.0 (1.4)
13458119N^	with Two Notch Hold Open Clip and POPD® H	3.0 (1.4)
13458214N^	with Two Notch Hold Open Clip, Long Spout and Excessive Heat Resistance	3.0 (1.4)
1163466	without Hold Open Clip, with Waffle Splash Guard	3.0 (1.4)
11634124	without Hold Open Clip, with POPD® H and Waffle Splash Guard	3.0 (1.4)

^ NOT LISTED


New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1163403N	with Two Notch Hold Open Clip	3.1 (1.4)
13458205N^	with Two Notch Hold Open Clip and POPD® H	3.1 (1.4)
13458215N^	with Two Notch Hold Open Clip, Long Spout and Excessive Heat Resistance	3.1 (1.4)
1163467	without Hold Open Clip, with Waffle Splash Guard	3.1 (1.4)
11634120	without Hold Open Clip, with POPD® H and Waffle Splash Guard	3.1 (1.4)

^ NOT LISTED

Construction

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Two-piece polymer
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

X EZ Lever PHG Nozzles

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-On Package
003795	Mate Guard
008175	POPD® EZS Nozzle Guard
008176	POPD® EZH Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.



New Unleaded Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1219304	with Three Notch Hold Open Clip	3.0 (1.3)
1219304N^	with Three Notch Hold Open Clip	3.0 (1.3)
1219359	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
1219395	with Three Notch Hold Open Clip, POPD® S and Waffle Splash Guard	3.0 (1.3)
12193146	with Three Notch Hold Open Clip, POPD® H and Waffle Splash Guard	3.0 (1.3)
12193179	with Single Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.0 (1.3)
E1219359	with Three Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	3.0 (1.3)


^NOT LISTED

New Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1219303	with Three Notch Hold Open Clip	3.1 (1.4)
1219361	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1219396	with Three Notch Hold Open Clip, POPD® S and Waffle Splash Guard	3.0 (1.3)
1219397	with Single Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
12193122	with Three Notch Hold Open Clip, POPD® H and Waffle Splash Guard	3.1 (1.4)
E1219361	with Three Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	3.0 (1.3)

Construction

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Polymer lever, one piece
Inlet	3/4" / 19.1 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS[®]
PHG Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks[®]

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break [®]
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break [®]
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break [®]
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break [®]

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break[®] Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break [®]

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop [®]
010434	Unleaded Long Spout without Flo-Stop [®]
001471	Light Duty Diesel Spout without Flo-Stop [®] with StreamShaper [®]
010353	Light Duty Diesel Long Spout without Flo-Stop [®]

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer [®] - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer [®] - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD [®] EZH Nozzle Guard
008175	POPD [®] EZS Nozzle Guard
007999	POPD [®] H Clear Cover
008185	POPD [®] H Full Grip Guard
008192	POPD [®] H Full Grip Reguard
008166	POPD [®] H Mate Guard
006628	POPD [®] S Clear Cover
006665	POPD [®] S Full Grip Guard
007205	POPD [®] S Full Grip Reguard
008165	POPD [®] S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- 2-piece lever is easier to use:
 - requires ½ the force to open nozzle.
 - ADA compliant.



New Unleaded Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1163504	with Two Notch Hold Open Clip	3.1 (1.4)
1163508	without Hold Open Clip	3.1 (1.4)
1163504N^	with Two Notch Hold Open Clip	3.1 (1.4)
1163544	with Two Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.1 (1.4)
1163544N^	with Two Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
1163559	with Two Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1163566	without Hold Open Clip, with Waffle Splash Guard	3.1 (1.4)
1163582	with Two Notch Hold Open Clip, Waffle Splash Guard and Drip Less Spout	3.1 (1.4)
1163595	with Two Notch Hold Open Clip, POPD® S and Waffle Splash Guard	3.1 (1.4)
11635108	without Hold Open Clip, with POPD® S and Waffle Splash Guard	3.1 (1.4)
11635126	without Hold Open Clip, with POPD® S Full Grip Guard	3.1 (1.4)
11635146	with Two Notch Hold Open Clip, POPD® H and Waffle Splash Guard	3.1 (1.4)
11635214N^	with Two Notch Hold Open Clip and Long Spout	3.1 (1.4)
E1163504	with Two Notch Hold Open Clip and Mate Guard	3.1 (1.4)
E1163504N^	with Two Notch Hold Open Clip and Mate Guard	3.1 (1.4)
E1163508	without Hold Open Clip, with Mate Guard	3.1 (1.4)
E1163543	with Single Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	3.1 (1.4)
E1163559	with Two Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	3.1 (1.4)
E1163566	without Hold Open Clip, with Waffle Splash Guard and Mate Guard	3.1 (1.4)
E1163582	with Two Notch Hold Open Clip, Waffle Splash Guard, Drip Less Spout and Mate Guard	3.1 (1.4)
E11635246	without Hold Open Clip, Waffle Splash Guard, Drip Less Spout and Mate Guard	3.1 (1.4)

^NOT LISTED


New Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1163503	with Two Notch Hold Open Clip	3.1 (1.4)
1163503N^	with Two Notch Hold Open Clip	3.1 (1.4)
1163507	without Hold Open Clip	3.1 (1.4)
1163553N^	with Two Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
1163561	with Two Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1163567	without Hold Open Clip, with Waffle Splash Guard	3.1 (1.4)
1163596	with Two Notch Hold Open Clip, POPD® S and Waffle Splash Guard	3.1 (1.4)
11635109	without Hold Open Clip, with POPD® S and Waffle Splash Guard	3.1 (1.4)
11635211	with Two Notch Hold Open Clip, Waffle Splash Guard and Drip Less Spout	3.1 (1.4)
11635270	without Hold Open Clip, with POPD® S Full Grip Guard	3.1 (1.4)
11635215N^	with Two Notch Hold Open Clip and Long Spout	3.1 (1.4)
E1163503	with Two Notch Hold Open Clip and Mate Guard	3.1 (1.4)
E1163507	without Hold Open Clip, with Mate Guard	3.1 (1.4)
E1163597	with Single Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	3.1 (1.4)
E1163561	with Two Notch Hold Open Clip, Waffle Splash Guard and Mate Guard	3.1 (1.4)
E1163567	without Hold Open Clip, with Waffle Splash Guard and Mate Guard	3.1 (1.4)
E11635211	with Two Notch Hold Open Clip, Waffle Splash Guard, Drip Less Spout and Mate Guard	3.1 (1.4)
E11635247	with Hold Open Clip, Waffle Splash Guard, Drip Less Spout and Mate Guard	3.1 (1.4)

^NOT LISTED

CONSTRUCTION

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Polymer lever
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS®
EZ Lever PHG Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Enhanced Conventional (ECO) Nozzles



1-33

CONVENTIONAL FUELING

Automatic shut-off conventional nozzle equipped with a mechanical interlock that shuts off the nozzle if it falls from the fill tank.

- Unique internal interlock device that shuts off the fuel flow before the spout is out of the tank.
- Aluminum casting with high impact polymer hand guard provides a lightweight, easier to handle conventional nozzle.
- 2-piece lever is easier to use:
 - requires ½ the force to open nozzle.
 - ADA compliant.
- A reinforced stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Drip Less spout reduces/eliminates drips from spout.
- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Lightest insertion “force” of any safety interlock operated nozzle.
- Comes standard with smooth full grip guard.
- CARB compliant for drips, spills, spitting and liquid retention.
- Unique tilt poppet maximizes “to-the-penny” dispensing.
- Cold weather version contains a poppet disc seal rated to -40° F/C to prevent fuel leakage from the main seal in extreme cold



New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1190404	with Two Notch Hold Open Clip, EZ Lever and Drip Less Spout	2.8 (1.3)
1190408	without Hold Open Clip, with EZ Lever and Drip Less Spout	2.8 (1.3)
11904180	with Two Notch Hold Open Clip, EZ Lever, Drip Less Spout and Flo-Equalizer®	2.8 (1.3)

New Cold Weather Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1474504	with Two Notch Hold Open Clip, EZ Lever and Drip Less Spout	2.8 (1.3)

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Two piece high impact polymer
Inlet	¾" / 19.1 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Enhanced Conventional (ECO) Nozzles

Automatic shut-off conventional nozzle equipped with a mechanical interlock that shuts off the nozzle if it falls from the fill tank.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
008330	¾" F x ¾" F NPT Reconnectable MagBreak®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
013664	Unleaded ECO Spout Assembly Kit

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT
005041	3" Thread to 2" Adaptor - NPT

Guards

MODEL NO.	DESCRIPTION
014034	Full Grip Nozzle Guard



Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
000397	Unleaded Spout Gauge

Low Perm Hoses

MODEL NO.	DESCRIPTION
CP12LP8.5	¾" Low Perm Hardwall 8.5' Assembly Hose
CP12LP8.5SV	¾" Low Perm Hardwall 8.5' Assembly Hose Swivel
CP12LP9	¾" Low Perm Hardwall 9' Assembly Hose
CP12LP9SV	¾" Low Perm Hardwall 9' Assembly Hose Swivel
CP12LP.75	¾" Low Perm Hardwall 9" Assembly Hose
CP12LP.75SV	¾" Low Perm Hardwall 9" Swivel Assembly Hose



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1AS Nozzles



1-36

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

- 1AS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- Stainless steel reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.



New Unleaded Nozzles with NPT


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1215904	with Three Notch Hold Open Clip	3.3 (1.4)
12159209	with Three Notch Hold Open Clip and Reducer Bushing	3.3 (1.4)

New Light Duty Diesel Nozzles with NPT

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1215903	with Three Notch Hold Open Clip	3.4 (1.5)
1215961	with Three Notch Hold Open Clip and Waffle Splash Guard	3.4 (1.5)
12159208	with Three Notch Hold Open Clip and Reducer Bushing	3.4 (1.5)
12159208	with Three Notch Hold Open Clip, Waffle Splash Guard and Drip Less Spout	3.4 (1.5)
E1215903	with Three Notch Hold Open Clip and Mate Guard	3.4 (1.5)

Construction

Body	Die cast aluminum body with high impact polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x ¾" F Reducer Bushing



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
007295	Mate Handle Guard
000226	Mate Nozzle Guard
006628	POPD® Clear Cover
006655	POPD® Full Grip Nozzle Guard
007210	POPD® Full Grip Nozzle Reguard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Nozzle Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1AS Nozzles



1-37

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for full-service and self-service stations.

- 1AS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Stainless steel reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216204	with Three Notch Hold Open Clip	3.3 (1.4)
12162239	with Single Notch Hold Open Clip	3.3 (1.4)

New Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216203	with Three Notch Hold Open Clip	3.4 (1.5)
12162238	with Single Notch Hold Open Clip	3.4 (1.5)

Construction

Body	Die cast aluminum body with metal hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with metal handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x ¾" F Reducer Bushing



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
003376	Mate Handle Guard
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Nozzle Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1AS CW Nozzles



1-38

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for full-service and self-service stations.

- 1AS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Stainless steel reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399204	with Three Notch Hold Open Clip	3.3 (1.4)

New Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399203	with Three Notch Hold Open Clip	3.4 (1.5)

Construction

Body	Die cast aluminum body with metal hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with metal handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x ¾" F Reducer Bushing



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
003376	Mate Handle Guard
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Nozzle Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1AS CW Nozzles



1-39

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

- 1AS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Stainless steel reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1398904	with Three Notch Hold Open Clip	3.3 (1.4)

New Light Duty Diesel Nozzles with NPT

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1398903	with Three Notch Hold Open Clip	3.4 (1.5)

Construction

Body	Die cast aluminum body with high impact polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

1AS CW Nozzles

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x 3/4" F Reducer Bushing



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
007295	Mate Handle Guard
000226	Mate Nozzle Guard
006628	POPD® Clear Cover
006655	POPD® Full Grip Nozzle Guard
007210	POPD® Full Grip Nozzle Reguard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Nozzle Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008169	POPD® S Mate Nozzle Guard
000099	Protection Package
001811	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® MFM PHG Nozzles



1-40

CONVENTIONAL FUELING

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- A reinforced stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.




New Light Duty Diesel Nozzles

MODEL NO	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1219360	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
1163560	with Two Notch Hold Open Clip, Waffle Splash Guard and EZ Lever	3.3 (1.4)

CONSTRUCTION

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Polymer lever
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



XS[®] MFM PHG Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks[®]

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break [®]
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break [®]
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break [®]
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break [®]

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black

Swivel/Safe-T-Break[®] Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break [®]

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop [®]
010434	Unleaded Long Spout without Flo-Stop [®]
001471	Light Duty Diesel Spout without Flo-Stop [®] with StreamShaper [®]
010353	Light Duty Diesel Long Spout without Flo-Stop [®]

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x 3/4" F Reducer Bushing



Guards

MODEL NO.	DESCRIPTION
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
008176	POPD [®] EZH Nozzle Guard
008175	POPD [®] EZS Nozzle Guard
007999	POPD [®] H Clear Cover
008185	POPD [®] H Full Grip Guard
008192	POPD [®] H Full Grip Reguard
008166	POPD [®] H Mate Guard
006628	POPD [®] S Clear Cover
006665	POPD [®] S Full Grip Guard
007205	POPD [®] S Full Grip Reguard
008165	POPD [®] S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- 2-piece lever is easier to use:
 - requires ½ the force to open nozzle.
 - ADA compliant.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.



New Unleaded Nozzles


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1396804	with Two Notch Hold Open Clip	3.1 (1.4)
1396866	without Hold Open Clip, with Waffle Splash Guard	3.1 (1.4)
E1396804	with Two Notch Hold Open Clip and Mate Guard	3.1 (1.4)

New Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1396803	with Two Notch Hold Open Clip	3.1 (1.4)
1396867	without Hold Open Clip, with Waffle Splash Guard	3.1 (1.4)
E1396803	with Two Notch Hold Open Clip and Mate Guard	3.1 (1.4)

CONSTRUCTION

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Two piece polymer lever
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS®
EZ Lever CW PHG Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.



New Unleaded Nozzles


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1456959	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1456966	without Hold Open Clip, With Waffle Splash Guard	3.1 (1.4)

New Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1456961	with Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1456967	without Hold Open Clip, With Waffle Splash Guard	3.1 (1.4)

Construction

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Polymer lever, one piece
Inlet	3/4" / 19.1 mm NPT



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS®
CW PHG Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X WPHG PHG Nozzles



1-44

CONVENTIONAL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when:
 - the gas tank is full.
- Comes standard with mate guard.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Wayne Polymer Handguard:
 - high-strength polymer handguard designed to specifically fit Wayne dispensers.
 - optional magnet can be fitted into the handguard to trigger the dispenser's proximity switch.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.



New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E1503004N	with Three Notch Hold Open Clip and Magnetic Hand Guard	3.0 (1.4)
		^ NOT LISTED

New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E1503003N	with Three Notch Hold Open Clip and Magnetic Hand Guard	3.0 (1.4)
		^ NOT LISTED

Construction

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Single-piece polymer
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®
008330	¾" F x ¾" F NPT Reconnectable MAGBREAK®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit



Guards

MODEL NO.	DESCRIPTION
007361	Black Handle Guard
014524	Mate Easy-On Package
014530	Mate Guard
007999	POPD® H Clear Cover
015253	POPD® H Mate Guard With Clear Cover
001808	Waffle Splash Guard
015247	POPD® H Mate Guard Without Clear Cover



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- 2-piece lever is easier to use:
 - requires ½ the force to open nozzle.
 - ADA compliant.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.



New Unleaded Nozzles


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
11635248	with Two Notch Hold Open Clip, Veg. Splash Guard, Drip Less Spout and Mate Guard	3.1 (1.4)
		^NOT LISTED

New Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
11635249	with Two Notch Hold Open Clip, Veg. Splash Guard, Drip Less Spout and Mate Guard	3.1 (1.4)
		^NOT LISTED

CONSTRUCTION

Body	Die cast aluminum with polymer handguard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Polymer lever
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS® Bellows Splash Guard Nozzles

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Sightglass on nozzle allows customer to see fuel flow through nozzle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- 2-piece lever is easier to use:
 - requires ½ the force to open nozzle.
 - ADA compliant.
- A reinforced stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.



New Unleaded Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E11635273	with Two Notch Hold Open Clip	3.1 (1.4)
		^NOT LISTED

New Light Duty Diesel Nozzles

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E11635272	with Two Notch Hold Open Clip	3.1 (1.4)
		^NOT LISTED

CONSTRUCTION


Body Die cast aluminum with polymer handguard

Seals Fluorocarbon

Packing Double o-ring seal protected by fiber reinforced Teflon®

Lever Polymer lever

Inlet 3/4" / 19 mm BSP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XS® EZ Lever BSP PHG Sightglass

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003385	¾" F x ¾" F BSPP Reconnectable Safe-T-Break®
003385A	¾" F x ¾" F BSPP Reconnectable Safe-T-Break® - Atex
002774	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break®
002774A	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break® - Atex

Swivels

MODEL NO.	DESCRIPTION
003590	¾" M x ¾" F BSPP Multi-Plane Swivel
003590A	¾" M x ¾" F BSPP Multi-Plane Swivel - Atex
003590W	¾" M x ¾" F BSPP Multi-Plane Swivel with Warm Weather Seals
002771	¾" M x ¾" F BSPP 90° Pump Swivel
002771A	¾" M x ¾" F BSPP 90° Pump Swivel - Atex

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
007085	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Farm & Commercial Nozzles



1GS Nozzles



2-1

FARM AND COMMERCIAL FUELING

Automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GS nozzle shuts off when the gas tank is full.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Heavy duty, long lasting metal handguard.
- Not legal for retail dispensing applications.



Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696204N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
696208	without Hold Open Clip with Hook	3.6 (1.6)
6962209N^	with Three Notch Hold Open Clip, Hook, and Reducer Bushing	3.6 (1.6)

^ NOT LISTED

Unleaded Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696216N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

^ NOT LISTED

Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696203N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
696207	without Hold Open Clip with Hook	3.6 (1.6)
6962208N^	with Three Notch Hold Open Clip, Hook and Reducer Bushing	3.6 (1.6)

^ NOT LISTED

Light Duty Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696215N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

^ NOT LISTED

Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696210N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

^ NOT LISTED

Heavy Duty Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696238N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPTF Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000385	1" M x 3/4" F Reducer Bushing - NPT Threads
001717	1" M x 3/4" F Reducer Bushing - BSPP Threads
000397	Unleaded Spout Gauge
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1GS Nozzles



2-2

FARM AND COMMERCIAL FUELING

Automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GS nozzle shuts off when the gas tank is full.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045704N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
045708	without Hold Open Clip and Hook	3.6 (1.6)
0457209N^	with Three Notch Hold Open Clip, Hook and Reducer Bushing	3.6 (1.6)

^ NOT LISTED

New Unleaded Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045716N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
045720	without Hold Open Clip with Hook	3.6 (1.6)

^ NOT LISTED

New Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045703N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
045707	without Hold Open Clip with Hook	3.6 (1.6)
0457208N^	with Three Notch Hold Open Clip, Hook and Reducer Bushing	3.6 (1.6)

^ NOT LISTED

New Light Duty Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045715N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
045719	without Hold Open Clip with Hook	3.6 (1.6)

^ NOT LISTED

New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045709N^	with Three Notch Hold Open Clip and Hook without Flo-Stop®	3.6 (1.6)
045710N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
045712	without Hold Open Clip, with Hook	3.6 (1.6)

^ NOT LISTED


New Heavy Duty Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045738N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
000385	1" M x ¾" F Reducer Bushing - NPT threads
001717	1" M x ¾" F Reducer Bushing - BSPP threads
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1GS Rebuilt Nozzles



2-3

FARM AND COMMERCIAL FUELING

Automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GS nozzle shuts off when the gas tank is full.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.



Rebuilt Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
078604N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
0786209N^	with Three Notch Hold Open Clip, Hook and Reducer Bushing	3.6 (1.6)

^ NOT LISTED

Rebuilt Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
078603N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
0786208N^	with Three Notch Hold Open Clip, Hook and Reducer Bushing	3.6 (1.6)

^ NOT LISTED


Rebuilt Heavy Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
078610N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

^ NOT LISTED

CONSTRUCTION

Body	Die cast aluminum body with black hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1GS Rebuilt Nozzles

Automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
000385	1" M x 3/4" F Reducer Bushing - NPT threads
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XFS Nozzles



2-4

FARM AND COMMERCIAL FUELING

Automatic shut-off nozzle for farm, 12V skid tanks and consumer pump applications.

- Strong, improved flow - up to 18 gpm / 68.1 Lpm.
- Dispenses 10 gpm / 37.8 Lpm at only 5.6 psi / 0.38 bar (unleaded nozzle).
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or is raised above horizontal.
- Unleaded nozzle includes StreamShaper® to reduce turbulence for straighter fuel flow and less splash back spillage.
- Has built-in hook and fits "holster lock" of skid tank pumps.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337004N^	with Hold Open Clip and Hook	3.0 (1.3)
337008	without Hold Open Clip and Hook	3.0 (1.3)
503404N^	with Hold Open Clip without Hook	3.0 (1.3)

^ NOT LISTED

New Unleaded Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337016N^	with Hold Open Clip and Hook	3.0 (1.3)
503416N^	with Hold Open Clip, without Hook	2.9 (1.3)

^ NOT LISTED

New Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337003N^	with Hold Open Clip and Hook	3.2 (1.4)
337007	without Hold Open Clip and Hook	3.2 (1.4)
503403N^	with Hold Open Clip without Hook	3.6 (1.6)

^ NOT LISTED


New Light Duty Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337015N^	with Hold Open Clip and Hook	2.9 (1.3)
503415N^	with Hold Open Clip without Hook	2.9 (1.3)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for farm, 12V skid tanks and consumer pump applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®
003385	¾" F x ¾" F BSPP Reconnectable Safe-T-Break®
003385A	¾" F x ¾" F BSPP Reconnectable Safe-T-Break® - Atex
002774	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break®
002774A	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break® - Atex

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003895	¾" M x ¾" F NPT Inline Swivel
002272	¾" M x ¾" F NPT 90° Pump Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel
003590	¾" M x ¾" F BSPP Multi-Plane Swivel
003590A	¾" M x ¾" F BSPP Multi-Plane Swivel - Atex
002771	¾" M x ¾" F BSPP 90° Pump Swivel

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®
007085	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break®
007085A	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
003356	Unleaded Spout with Hanging Hook without Flo-Stop®
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
003358	Light Duty Diesel with Hanging Hook without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008166	POPD® H Mate Guard
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard

1GS CW Nozzles



2-5

FARM AND COMMERCIAL FUELING

Automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GS nozzle shuts off when the gas tank is full.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1096203N [^]	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
		[^] NOT LISTED

New Light Duty Diesel Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1096204N [^]	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
		[^] NOT LISTED

New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1096210N [^]	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
		[^] NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
001717	1" M x 3/4" F Reducer Bushing - BSPP Threads
000385	1" M x 3/4" F Reducer Bushing - NPT Threads
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XFS Rebuilt Nozzles



2-6

FARM AND COMMERCIAL FUELING

Automatic shut-off nozzle for farm, 12V skid tanks and consumer pump applications.

- Strong, improved flow - up to 18 gpm / 68.1 Lpm.
- Dispenses 10 gpm / 37.8 Lpm at only 5.6 psi / 0.38 bar (unleaded nozzle).
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or is raised above horizontal.
- Unleaded nozzle includes StreamShaper® to reduce turbulence for straighter fuel flow and less splash back spillage.
- Has built-in hook and fits "holster lock" of skid tank pumps.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.



Rebuilt Unleaded Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
504304N^	with Hold Open Clip and Hook	3.1 (1.4)
503604N^	with Hold Open Clip without Hook	3.1 (1.4)
^ NOT LISTED		

Rebuilt Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
504303N^	with Hold Open Clip and Hook	3.2 (1.4)
503603N^	with Hold Open Clip without Hook	3.2 (1.4)
^ NOT LISTED		

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

XFS Rebuilt Nozzles

Automatic shut-off nozzle for farm, 12V skid tanks and consumer pump applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®
003385	¾" F x ¾" F BSPP Reconnectable Safe-T-Break®
003385A	¾" F x ¾" F BSPP Reconnectable Safe-T-Break® - Atex
002774	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break®
002774A	¾" F x ¾" F BSPP Non-Reconnectable Safe-T-Break® - Atex

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
003895	¾" M x ¾" F NPT Inline Swivel
002272	¾" M x ¾" F NPT 90° Pump Swivel
002950	¾" M x ¾" F NPT Multi-Plane Restricted Swivel
003590	¾" M x ¾" F BSPP Multi-Plane Swivel
003590A	¾" M x ¾" F BSPP Multi-Plane Swivel - Atex
002771	¾" M x ¾" F BSPP 90° Pump Swivel
002771A	¾" M x ¾" F BSPP 90° Pump Swivel - Atex

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	¾" M NPT Multi-Plane Swivel connected to ¾" F NPT Reconnectable Safe-T-Break®
007085	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break®
007085A	¾" M BSPP Multi-Plane Swivel connected to ¾" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
003356	Unleaded Spout with Hanging Hook without Flo-Stop®
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
003358	Light Duty Diesel with Hanging Hook without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Cover
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008166	POPD® H Mate Guard
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1GS Rebuilt Nozzles



2-7

FARM AND COMMERCIAL FUELING

Automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GS nozzle shuts off when the gas tank is full.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Heavy duty, long lasting metal handguard.
- Not legal for retail dispensing applications.



Rebuilt Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696504N^	with Three Notch Hold Open Clip, and Hook	3.6 (1.6)
696508	without Hold Open Clip, with Hook	3.6 (1.6)
696559N^	with Three Notch Hold Open Clip, Hook and Reducer Bushing	3.6 (1.6)

^ NOT LISTED

Rebuilt Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696503N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)
696507	without Hold Open Clip with Hook	3.6 (1.6)
6965208N^	with Three Notch Hold Open Clip, Hook and Reducer Bushing	3.6 (1.6)

^ NOT LISTED


Rebuilt Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696510N^	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1GS Rebuilt Nozzles

Automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
000385	1" M x 3/4" F Reducer Bushing - NPT threads
001717	1" M x 3/4" F Reducer Bushing - BSPP threads
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1GSS Nozzles



2-8

FARM AND COMMERCIAL FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Not legal for retail dispensing applications.
- Stainless steel reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216504	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

New Light Duty Diesel Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216503	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216510	with Three Notch Hold Open Clip and Hook without Flo-Stop®	3.6 (1.6)

Construction

Body	Die cast aluminum body with high impact polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
000385	1" M x 3/4" F Reducer Bushing - NPT threads
001717	1" M x 3/4" F Reducer Bushing - BSPP threads
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1GSS Nozzles



2-9

FARM AND COMMERCIAL FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Not legal for retail dispensing applications.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.



Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216804	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

Light Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216803	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1216810	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

Construction

Body	Die cast aluminum body with metal hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPTF Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000385	1" M x 3/4" F Reducer Bushing - NPT Threads
001717	1" M x 3/4" F Reducer Bushing - BSPP Threads
000397	Unleaded Spout Gauge
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1GSS CW Nozzles



2-10

FARM AND COMMERCIAL FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.
- Stainless steel reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399504	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

New Light Duty Diesel Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399503	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399510	with Three Notch Hold Open Clip and Hook without Flo-Stop®	3.6 (1.6)

Construction

Body	Die cast aluminum body with high impact polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1GSS CW Nozzles

Pressure activated, automatic shut-off nozzle with polymer handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
000385	1" M x 3/4" F Reducer Bushing - NPT threads
001717	1" M x 3/4" F Reducer Bushing - BSPP threads
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1GSS CW Nozzles



2-11

FARM AND COMMERCIAL FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

- 1GSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.
- Nozzle is equipped with unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



Unleaded Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399704	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

Light Duty Diesel Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399703	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399710	with Three Notch Hold Open Clip and Hook	3.6 (1.6)

Construction

Body	Die cast aluminum body with metal hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1GSS CW Nozzles

Pressure activated, automatic shut-off nozzle with metal handguard for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x 3/4" F NPT Multi-Plane Swivel
000356	1" M x 3/4" F NPT Multi-Plane Swivel Anodized Black
003306	1" M x 1" F BSPP Multi-Plane Swivel
003306A	1" M x 1" F BSPP Multi-Plane Swivel - Atex

Swivel•Safe-T-Break® Combos


MODEL NO.	DESCRIPTION
005969	1" M NPTF Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®
005215	Heavy Duty Diesel Spout with Flo-Stop®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000385	1" M x 3/4" F Reducer Bushing - NPT Threads
001717	1" M x 3/4" F Reducer Bushing - BSPP Threads
000397	Unleaded Spout Gauge
000548	Hanging Hook for Unleaded and Light Duty Diesel Nozzles



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
001804	Full Grip Reguard
005494	Lever Guard
000226	Mate Guard
007376	Mate Handle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008170	POPD® H Mate Guard
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





GENERAL FUELING PRODUCTS

Diesel Exhaust Fluid Nozzles



DEF Nozzles



3-1

DIESEL EXHAUST FLUID

Automatic shut-off Diesel Exhaust Fluid (DEF) nozzle for full-service and self-service stations.

- Modular design for easy cleaning.
- Constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- Nozzle shuts off when the DEF tank is full.
- Available with magnetic Accufuel® safety feature.
- Equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Comes standard with mate nozzle guard and handle cover.
- Stainless Steel construction.



DEF Nozzles with 1" BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
731004N^	with Two Notch Hold Open Clip; without Spout Ring and magnetic Accufuel® Spout	4.6 (2.1)
731088N^	with Two Notch Hold Open Clip and Spout Ring; without magnetic Accufuel® Spout	4.6 (2.1)
731091N^	with Two Notch Hold Open Clip, Spout Ring and magnetic Accufuel® Spout	4.6 (2.1)
1043691N^	with Two Notch Hold Open Clip, Spout Ring, magnetic Accufuel® Spout, and Waffle Guard - M34 Threads	4.6 (2.1)
7310192N^	with Two Notch Hold Open Clip, Spout Ring, Grounding Cable and Spout Cap, without magnetic Accufuel® Spout	4.6 (2.1)
		^ NOT LISTED


DEF Nozzles with M34

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1043691N^	with Two Notch Hold Open Clip, Spout Ring, magnetic Accufuel® Spout, and Waffle Guard	4.6 (2.1)

Construction

^ NOT LISTED

Body	Investment Cast Stainless Steel
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm BSPP M34 1.5 Face Seal threads



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off Diesel Exhaust Fluid (DEF) nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
007219	1" M x 1" M BSPP Non-Reconnectable Stainless Steel Safe-T-Break®
008216	1" M x 1" M BSPP Reconnectable Stainless Steel Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
007269	1" M x 1" M BSPP Inline Swivel
007275	1" M BSPP x M34 M Inline Swivel
007282	3/4" M BSPP x 3/4" Hose Barb Roller Bearing Inline Swivel
007467	1" F x 1" M BSPP Inline Swivel
008510	1" M BSPP 1" F NPT Inline Swivel
010936	3/4" M BSPP X 3/4" Hose Barb Inline Swivel

Spouts

MODEL NO.	DESCRIPTION
007360	with Spout Ring and Flo-Stop®
007364	with Spout Ring and Magnetic Accufuel® Safety Feature
007362	with Flo-Stop®

Guards

MODEL NO.	DESCRIPTION
008429	DEF Handguard Repair Kit
007376	Handle Cover (Black)
000226	Mate Nozzle Guard
001808	Waffle Splash Guard

Adaptors

MODEL NO.	DESCRIPTION
007285	1" M x 1" M BSPP Straight Adaptor
007356	1" M BSPP x M M34 Straight Adaptor
008413	1" M BSPP x 3/4" Hose Barb Adaptor with Seal Kit

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007523	1" BSPP Seal Kit Assembly
007163	Loss Motion Diaphragm Cartridge Assembly
007160	Plunger Cartridge Assembly
007150	Poppet Valve / Venturi Cartridge Assembly

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
013185	M34 M NPT Multi-Plane Swivel connected to 1" BSP M Reconnectable Safe-T-Break®
014438	1" BSP M Multi-Plane Swivel connected to 1" BSP M Reconnectable Safe-T-Break®



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Polymer DEF Nozzle



3-2

DIESEL EXHAUST FLUID

Polymer shut-off Diesel Exhaust Fluid (DEF) nozzle for full-service and self-service stations.

- Lighter than stainless steel nozzles.
- *Streamshaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Less expensive than comparable nozzles.
- Nozzle shuts off when the DEF tank is full.
- Stainless steel spout for durability.
- Replaceable stainless steel spout.
- Available with magnetic Accufuel® safety feature.
- Lower lever force.
- Flow characteristics of nozzle reduces crystallization of DEF.
- Complies with ISO Standard 22241-2:2006.




New Polymer DEF Nozzle with 1" BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
873504N^	with Two Notch Hold Open Clip without Spout Ring and magnetic Accufuel® Spout	1.53 (0.7)
873508	without Two Notch Hold Open Clip, Spout Ring and magnetic Accufuel® Spout	1.53 (0.7)
873588N^	with Two Notch Hold Open Clip and Spout Ring, without magnetic Accufuel® Spout	1.53 (0.7)
873591N^	with Two Notch Hold Open Clip, Spout Ring and magnetic Accufuel® Spout	1.53 (0.7)
8735153	without Two Notch Hold Open Clip and magnetic Accufuel® Spout, with Spout Ring	1.53 (0.7)
8735158	without Two Notch Hold Open Clip with Spout Ring and magnetic Accufuel® Spout	1.53 (0.7)
1202991N	with Two Notch Hold Open Clip, Spout Ring, magnetic Accufuel® Spout, and Gilbarco Magnetic Hand Guard	1.53 (0.7)
1307791N^	with Two Notch Hold Open Clip, Spout Ring and magnetic Accufuel® Spout, without Spout Groove	1.53 (0.7)
13077154N^	with Two Notch Hold Open Clip and Spout Ring, without Spout Groove and magnetic Accufuel® Spout	1.53 (0.7)

^ NOT LISTED

Construction

Body	Acetal
Seals	Fluorocarbon o-rings and diaphragm
Spout	19 mm diameter
Lever	One-piece contoured steel with hard plastic cover
Inlet	1" BSPP Male/Female seal



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Polymer shut-off Diesel Exhaust Fluid (DEF) nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
007219	1" M x 1" M BSPP Non-Reconnectable Stainless Steel Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
007275	1" M BSPP x M34 M Inline Swivel
007282	3/4" M BSPP x 3/4" Hose Barb Inline Swivel
007467	1" F x 1" M BSPP Inline Swivel
008510	1" M BSPP x 1" F NPT Inline Swivel
008822	1" F x 1" M BSPP Inline Swivel Face Seal

Spouts

MODEL NO.	DESCRIPTION
013591	with StreamShaper®
013592	with Spout Ring and StreamShaper®
013593	with Spout Ring and Magnetic Accufuel® Safety Feature

Adaptors

MODEL NO.	DESCRIPTION
010227	DEF 1" Female BSPP Adaptor
010549	DEF 1" Female BSPP/1" Female NPT Adaptor
010551	DEF 1" Female BSPP x 3/4" Female NPT Adaptor
010553	DEF 1" Female BSPP X 3/4" Female BSPP Adaptor
010579	1" Female BSPP x 3/4" Male DEF HB Adaptor
010675	1" Female BSPP x 1" Female BSPP Adaptor, Straight

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007523	1" BSPP Seal Kit Assembly




2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Automatic shut-off Diesel Exhaust Fluid (DEF) nozzle for full-service and self-service stations.

- Lighter than stainless steel nozzles.
- *Streamshaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Less expensive than comparable nozzles.
- Nozzle shuts off when the DEF tank is full.
- Stainless steel spout for durability.
- Flow characteristics of nozzle reduces crystallization of DEF.
- Complies with ISO Standard 22241-2:2006.



New X DEF Nozzle with 3/4" NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
11676155N	with Three Notch Hold Open Clip	3.0 (1.3)
11676188N	with Three Notch Hold Open Clip, Spout Ring and Magnetic Accufuel® Spout	3.0 (1.3)
11676189N	with Three Notch Hold Open Clip and Long Spout	3.0 (1.3)
12150155N	with Three Notch Hold Open Clip and Gilbarco Magnetic Hand Guard	3.0 (1.3)
12970155N	with Three Notch Hold Open Clip and Wayne Magnetic Hand Guard	3.0 (1.3)

New X DEF Nozzle with 3/4" BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1167691N	with Three Notch Hold Open Clip, Spout Ring and Magnetic Accufuel® Spout	3.0 (1.3)
11676154N	with Three Notch Hold Open Clip	3.0 (1.3)
11676180N	with Three Notch Hold Open Clip without Waffle Guard	3.0 (1.3)
11676190N	with Three Notch Hold Open Clip and Long Spout	3.0 (1.3)
12150154N	with Three Notch Hold Open Clip and Gilbarco Magnetic Hand Guard	3.0 (1.3)
1215091N	with Three Notch Hold Open Clip, Spout Ring, Magnetic Accufuel® Spout and Gilbarco Magnetic Hand Guard	3.0 (1.3)
12964154N	with Two Notch Hold Open Clip, EZ Lever and Wayne Magnetic Hand Guard without Spout Groove	3.0 (1.3)
12970154N	with Three Notch Hold Open Clip and Wayne Magnetic Hand Guard	3.0 (1.3)
13410203N	with Two Notch Hold Open Clip, EZ Lever and Magnetic Accufuel® Spout, without Spout Groove	3.0 (1.3)
13410204N	with Two Notch Hold Open Clip, EZ Lever, without Spout Groove	3.0 (1.3)

New X DEF Nozzle with M34

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
11676274N	with Three Notch Hold Open Clip and Long Spout	3.0 (1.3)
12150185N	with Three Notch Hold Open Clip, Spout Ring, Magnetic Accufuel® Spout and Gilbarco Magnetic Hand Guard	3.0 (1.3)
12150187N	with Three Notch Hold Open Clip and Gilbarco Magnetic Hand Guard	3.0 (1.3)
12150259N	without Three Notch Hold Open Clip, with Gilbarco Magnetic Hand Guard	3.0 (1.3)
12644155N	with Three Notch Hold Open Clip and Wayne Magnetic Hand Guard	3.0 (1.3)
12970185N	with Three Notch Hold Open Clip, Spout Ring, Magnetic Accufuel® Spout and Wayne Magnetic Hand Guard	3.0 (1.3)
12970259N	without Three Notch Hold Open Clip, with Wayne Magnetic Hand Guard	3.0 (1.3)

Construction

Body	Anodized Aluminum
Seals	Fluorocarbon o-rings and diaphragm
Spout	19 mm diameter
Lever	One-piece contoured steel with hard plastic cover
Inlet	3/4" / 19 mm NPT Female threads or 3/4" / 19 mm BSPP Face Seal threads M34 1.5 Face Seal threads



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off Diesel Exhaust Fluid (DEF) nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
012070	3/4" F x 3/4" F NPT Reconnectable Safe-T-Break®
012659	3/4" F x 3/4" F BSPP Reconnectable Safe-T-Break®

Swivel


MODEL NO.	DESCRIPTION
007282	3/4" M BSPP x 3/4" Hose Barb Roller Bearing Inline Swivel
010936	3/4" M BSPP x 3/4" Hose Barb Inline Swivel
012656	3/4" M x 3/4" F BSPP Roller Bearing Inline Swivel
012604	3/4" M x 3/4" F NPT Roller Bearing Inline Swivel

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007522	3/4" BSPP Seal Kit Assembly
013285	with StreamShaper®
013286	with Spout Ring and Magnetic Accufuel® Safety Feature
015319	with Long Spout and StreamShaper®

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
012828	3/4" BSP M Multi-Plane Swivel connected to 3/4" BSP F Reconnectable Safe-T-Break®
012831	3/4" NPT M Multi-Plane Swivel connected to 3/4" NPT F Reconnectable Safe-T-Break®
012887	3/4" BSP M Multi-Plane Swivel connected to 1" BSP F Reconnectable Safe-T-Break®
012890	3/4" BSP M Multi-Plane Swivel connected to 1" BSP M Reconnectable Safe-T-Break®



Gilbarco Magnetic Hand Guard



Wayne Magnetic Hand Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Truck & High Volume Nozzles



1690/1691 Nozzles



4-1

HIGH VOLUME FUELING

Husky® 1690/1691 nozzle is 30% lighter than similar nozzles.

- Nozzle designed with extra large hand opening to accommodate gloves or mittens.
- Check valve is in nozzle body, not the spout, for inexpensive and fast spout replacement.
- Includes a self-adjusting stem packing.
- Automatic shut-off with dual poppets for easy opening.
- 1690 is equipped with two position hold open latch.
- 1691 is not equipped with hold open latch.
- Right angle design allows nozzle to "fit" close to walls and corners.
- Cast-in protective standoffs provide durability with rough usage.



New Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
169010N^	without shear groove in spout	4.6 (2.0)
169112	with shear groove in spout	4.6 (2.0)
^ NOT LISTED		

Rebuilt Nozzles with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
169410N^	without shear groove in spout	4.6 (2.0)
^ NOT LISTED		

New Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
169038N^	without shear groove in spout	4.6 (2.0)
^ NOT LISTED		

Construction

Body	Die cast aluminum body
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1½" NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

1690/1691 Nozzles

Husky® 1690/1691 nozzle is 30% lighter than similar nozzles.

Dimensions and System Options

Swivels

MODEL NO.	DESCRIPTION
005240	1¼" F x 1½" M NPT Single Plane Swivel
005266	1½" F x 1½" M NPT Single Plane Swivel
005754	1¼" F x 1½" M BSPP Single Plane Swivel
005755	1½" F x 1½" M BSPP Single Plane Swivel

Spouts


MODEL NO.	DESCRIPTION
004889	Spout Assembly without shear groove
005042	Spout Assembly with shear groove (1691 CUL version)

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1690 CW Nozzles



4-2

HIGH VOLUME FUELING

High volume automatic shut-off nozzle provides 100 gpm and is 30% lighter than similar nozzles.

- Contains a poppet disc seal, rated at -40°F/C (exceeding the UL standard of -20°F / -29°C) to prevent fuel leakage from the main seal in extreme cold weather.
- Self-adjusting stem packing - no field adjustment is required.
- Nozzle is designed with extra large hand opening to accommodate gloves or mittens.
- Automatic shut-off with dual poppets for easy opening.
- Check valve is in the nozzle body, not the spout, for inexpensive, fast spout replacement.
- Right angle design allows nozzle to "fit" close to walls and corners.
- Two position hold open latch.
- Cast-in protective standoffs provide durability with rough usage.



New Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
652310N^	with two position hold-open latch	3.96 (1.79)
		^ NOT LISTED

Rebuilt Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
879810N^	with two position hold-open latch	3.96 (1.79)
		^ NOT LISTED

Construction

Body	Die Cast Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1-1/2 in / 38 mm NPT
Spout	1-3/8 in / 34.9 mm O.D



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1690 CW Nozzles

High volume automatic shut-off nozzle provides 100 gpm and is 30% lighter than similar nozzles.

Dimensions and System Options

Swivels

MODEL NO.	DESCRIPTION
005235	1¼ in / 32 mm F x 1¼ in / 32 mm M Inline Swivel
005240	1¼ in / 32 mm F x 1½ in / 38 mm M Inline Swivel
005265	1½ in / 38 mm F x 1¼ in / 32 mm M Inline Swivel
005266	1½ in / 38 mm F x 1½ in / 38 mm M Inline Swivel

Spouts


MODEL NO.	DESCRIPTION
004889	Spout without shear groove

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing, and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

1HS Nozzles



4-3

HIGH VOLUME FUELING

Automatic shut-off nozzle with metal handguard for dispensing up to 25 gpm / 94.6 Lpm.

- 1HS nozzle shuts off when the gas tank is full.
- Accu-Flo® poppet allows "to-the-penny" fuel dispensing.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Comes standard with full grip guard and waffle splash guard.
- Heavy-duty, long-lasting metal hand guard.



New Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696310N^	with Three Notch Hold Open Clip	3.4 (1.5)
696365N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.6 (1.6)
696312	without Hold Open Clip	3.4 (1.5)

^ NOT LISTED

Rebuilt Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696610N^	with Three Notch Hold Open Clip	3.4 (1.5)
696665N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
696612	without Hold Open Clip	3.4 (1.5)

^ NOT LISTED


New Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
696338N^	with Three Notch Hold Open Clip	3.4 (1.5)
696340	without Hold Open Clip	3.4 (1.5)

^ NOT LISTED

Construction

Body	Die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for dispensing up to 25 gpm / 94.6 Lpm.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
005215	Heavy Duty Diesel Spout with Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Nozzle Guard
001804	Full Grip Nozzle Reguard
005494	Lever Guard
007295	Mate Handle Cover
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard
000099	Protection Package
001811	Reguard Package
001808	Waffle Splash Guard

1HS Nozzles



4-4

HIGH VOLUME FUELING

Automatic shut-off nozzle with polymer handguard for dispensing up to 25 gpm / 94.6 Lpm.

- 1HS nozzle shuts off when the gas tank is full.
- Accu-Flo® poppet allows “to-the-penny” fuel dispensing.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Comes standard with full grip guard and waffle splash guard.



New Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
026810N^	with Three Notch Hold Open Clip	3.4 (1.5)
026865N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.4 (1.5)
026890N^	with Three Notch Hold Open Clip, POPD® Full Grip Guard and Waffle Splash Guard	3.4 (1.5)
026812	without Hold Open Clip	3.4 (1.5)

^ NOT LISTED

Rebuilt Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
052410N^	with Three Notch Hold Open Clip	3.4 (1.5)
052465N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
052412	without Hold Open Clip	3.4 (1.5)

^ NOT LISTED

New Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
026838N^	with Three Notch Hold Open Clip	3.4 (1.5)
026840	without Hold Open Clip	3.4 (1.5)

^ NOT LISTED


Rebuilt Diesel Nozzles with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
052438N^	with Three Notch Hold Open Clip	3.4 (1.5)

^ NOT LISTED

Construction

Body	Die cast aluminum body with high impact polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for dispensing up to 25 gpm / 94.6 Lpm.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPTF Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
005215	Heavy Duty Diesel Spout with Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Nozzle Guard
001804	Full Grip Nozzle Reguard
005494	Lever Guard
007376	Mate Handle Cover
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard
000099	Protection Package
001811	Reguard Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



VIII Nozzles



4-5

HIGH VOLUME FUELING

Automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIII nozzle shuts off when the gas tank is full.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.




New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
173310N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	3.9 (1.7)
17331001N^	with Three Notch Hold Open Clip, Waffle Splash Guard, Long Spout and Spout Bushing	4.0 (1.8)
173312	without Hold Open Clip, with Waffle Splash Guard and Spout Bushing	3.9 (1.7)
173381N^	with Three Notch Hold Open Clip and Spout Bushing without Waffle Splash Guard	3.9 (1.7)
503010N^	with Three Notch Hold Open Clip and Waffle Splash Guard without Spout Bushing	3.9 (1.7)
503012	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard	3.9 (1.7)
503081N^	with Three Notch Hold Open Clip, without Spout Bushing and Waffle Splash Guard	3.9 (1.7)
50301001N^	with Three Notch Hold Open Clip, Long Spout, Waffle Splash Guard, without Spout Bushing	3.9 (1.7)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



VIII BSPP Nozzles



4-6

HIGH VOLUME FUELING

Automatic shut off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIII nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.


New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
173338N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)
503038N^	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.5 (2.0)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

BSPP Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003076	1" F x 1" F Reconnectable Safe-T-Break®
003076A	1" F x 1" F Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F Non-Reconnectable Safe-T-Break®

BSPP Swivels

MODEL NO.	DESCRIPTION
003306	1" M x 1" F Multi-Plane Swivel
006949	1" M x 1" F Multi-Plane High Flow Swivel

BSPP Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly Kit with Bushing
005017	Complete Spout Assembly Kit without Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with internal screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIII CW Nozzles



4-7

HIGH VOLUME FUELING

Automatic shut-off nozzle with polymer handguard for truck stops and other high volume applications.

- Nozzle shuts off when the gas tank is full.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Contains a poppet disc seal designed to prevent fuel leakage from the main seal in extreme cold weather.
- Nozzle can get flow rates up to 75 GPM / 284 LPM.
- Standard nozzle spout is reinforced with a thick aluminum bushing that holds the spout spring in place and keeps the spout from rounding in.


New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
651510N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)
651512	without Hold Open Clip with Waffle Splash Guard and Spout Bushing	4.6 (2.1)
651710N^	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.5 (2.0)
651712	without Hold Open Clip with Waffle Splash Guard, without Spout Bushing	4.6 (2.1)
828110N^	with Three Notch Hold Open Clip, Waffle Splash Guard, without Spout Bushing	4.6 (2.1)
835110N^	with Three Notch Hold Open Clip, Waffle Splash Guard, and Spout Bushing	4.6 (2.1)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for truck stops and other high volume applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly Kit with Bushing
005017	Complete Spout Assembly Kit without Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008168	POPD® H Mate Guard
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIIIS Nozzles



4-8

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIIIS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.




New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
177610	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.6 (2.0)
17761001	with Three Notch Hold Open Clip, Waffle Splash Guard, Long Spout and Spout Bushing	4.6 (2.0)
177690	with Three Notch Hold Open Clip, POPD® S Full Grip Guard, Waffle Splash Guard and Spout Bushing	4.6 (2.0)
177612	without Hold Open Clip, with Waffle Splash Guard and Spout Bushing	4.6 (2.0)
1776147	with Three Notch Hold Open Clip, POPD® H Full Grip Guard, Waffle Splash Guard and Spout Bushing	4.6 (2.0)
504010	with Three Notch Hold Open Clip and Waffle Splash Guard without Spout Bushing	4.6 (2.0)
504012	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard	4.6 (2.0)
5040132	with Three Notch Hold Open Clip, without Waffle Splash Guard or Spout Bushing	4.6 (2.0)
11043132	with Three Notch Hold Open Clip, and Short Spout Spring, without Spout Bushing or Waffle Splash Guard	4.6 (2.0)
1776240	with Single Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.6 (2.0)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assy Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIIIS BSPP Nozzles



4-9

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIIIS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.




New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
177638	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	3.9 (1.7)
177640	without Hold Open Clip, with Waffle Splash Guard and Spout Bushing	3.9 (1.7)
504038	without Spout Bushing, with Three Notch Hold Open Clip and Waffle Splash Guard	3.9 (1.7)
504040	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard	3.9 (1.7)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

VIII BSPP Nozzles

Pressure activated, automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

BSPP Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003076	1" F x 1" F Reconnectable Safe-T-Break®
003076A	1" F x 1" F Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F Non-Reconnectable Safe-T-Break®

BSPP Swivels

MODEL NO.	DESCRIPTION
003306	1" M x 1" F Multi-Plane Swivel
006949	1" M x 1" F Multi-Plane High Flow Swivel

BSPP Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly Kit with Bushing
005017	Complete Spout Assembly Kit without Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



VIIIS CW Nozzles



4-10

HIGH VOLUME FUELING

Pressure activated nozzle with polymer handguard for self-service and unattended stations.


- VIIIS Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Contains a poppet disc seal designed to prevent fuel leakage from the main seal in extreme cold weather.
- Spout is reinforced with a thick aluminum bushing that holds the spout spring in place and keeps the spout from rounding in - the two leading causes of clicking-off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Contains a poppet disc seal, rated at -40° F/C, to prevent fuel leakage from the main seal in extreme cold weather.

New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
651910	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.6 (2.0)
652110	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.5 (2.0)
6519159	without Hold Open Clip, with Waffle Splash Guard and Spout Bushing	4.5 (2.0)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	LPM 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated nozzle with polymer handguard for self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly Kit with Bushing
005017	Complete Spout Assembly Kit without Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



VIII Rebuilt Nozzles



4-11

HIGH VOLUME FUELING

Automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIII nozzle shuts off when the gas tank is full.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.




Rebuilt Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
265910N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	3.9 (1.7)
265912	without Hold Open Clip, with Waffle Splash Guard and Spout Bushing	3.9 (1.7)
502510N [^]	with Three Notch Hold Open Clip and Waffle Splash Guard without Spout Bushing	3.9 (1.7)

[^] NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIIIS Rebuilt Nozzles



4-12

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.


- VIIIS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.

Rebuilt Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
266010	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.6 (2.0)
503510	with Three Notch Hold Open Clip and Waffle Splash Guard without Spout Bushing	4.6 (2.0)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



VIIIIS Rebuilt Nozzles

Pressure activated, automatic shut-off nozzle with polymer handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assy Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



VIII Nozzles



4-13

HIGH VOLUME FUELING

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIII nozzle shuts off when the gas tank is full.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.


New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
749310N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard, and Spout Bushing	4.5 (2.0)
74931001N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard, Long Spout, and Spout Bushing	4.7 (2.1)
750610N [^]	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.4 (2.0)
75061001N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Long Spout, without Spout Bushing	4.6 (2.1)
750612	without Hold Open Clip or Spout Bushing, with Waffle Splash Guard	4.4 (2.0)
7506230N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard, and Short Spout Spring, without Spout Bushing	4.4 (2.0)
750681N [^]	with Three Notch Hold Open Clip, without Waffle Splash Guard or Spout Bushing	4.3 (2.0)
1108710N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing, Nickel Plated Body	4.5 (2.0)

Construction

[^] NOT LISTED

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIII Nozzles



4-14

HIGH VOLUME FUELING

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIII nozzle shuts off when the gas tank is full.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.


New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
749310N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard, and Spout Bushing	4.5 (2.0)
74931001N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard, Long Spout, and Spout Bushing	4.7 (2.1)
750610N [^]	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.4 (2.0)
75061001N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Long Spout, without Spout Bushing	4.6 (2.1)
750612	without Hold Open Clip or Spout Bushing, with Waffle Splash Guard	4.4 (2.0)
7506230N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard, and Short Spout Spring, without Spout Bushing	4.4 (2.0)
750681N [^]	with Three Notch Hold Open Clip, without Waffle Splash Guard or Spout Bushing	4.3 (2.0)
1108710N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing, Nickel Plated Body	4.5 (2.0)
750623001N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard, Long Spout, and Short Spout Spring, without Spout Bushing	4.5 (2.0)

[^] NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIIIS Nozzles



4-15

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIIIS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.




New Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
749610	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)
74961001	with Three Notch Hold Open Clip, Waffle Splash Guard, Long Spout and Spout Bushing	4.7 (2.1)
749612	without Hold Open Clip, with Waffle Splash Guard and Spout Bushing	4.5 (2.0)
751010	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.4 (2.0)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assy Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIII CW Nozzles



4-16

HIGH VOLUME FUELING

Automatic shut-off nozzle with metal handguard for truck stops and other high volume applications.

- Nozzle shuts off when the gas tank is full.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Contains a poppet disc seal designed to prevent fuel leakage from the main seal in extreme cold weather.
- Standard nozzle spout is reinforced with a thick aluminum bushing that holds the spout spring in place and keeps the spout from rounding in.


New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
751510N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)
751710N^	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.4 (2.0)

Construction

^ NOT LISTED

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for truck stops and other high volume applications.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly Kit with Bushing
005017	Complete Spout Assembly Kit without Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIIIS CW Nozzles



4-17

HIGH VOLUME FUELING

Pressure activated nozzle with metal handguard for self-service and unattended stations.

- VIIIS Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Contains a poppet disc seal, rated at -40° F/C, to prevent fuel leakage from the main seal in extreme cold weather.
- Contains a poppet disc seal designed to prevent fuel leakage from the main seal in extreme cold weather.
- Spout is reinforced with a thick aluminum bushing that holds the spout spring in place and keeps the spout from rounding in - the two leading causes of clicking-off and splash-back spillage.




New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
751910	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated nozzle with metal handguard for self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel•Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly Kit with Bushing
005017	Complete Spout Assembly Kit without Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIII Rebuilt Nozzles



4-18

HIGH VOLUME FUELING

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

- VIII nozzle shuts off when the gas tank is full.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.


Rebuilt Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
749910N [^]	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)
750410N [^]	with Three Notch Hold Open Clip and Waffle Splash Guard, without Spout Bushing	4.5 (2.0)

Construction

[^] NOT LISTED

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

VIIIS Rebuilt Nozzles



4-19

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations

- VIIIS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.




Rebuilt Heavy Duty Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
750210	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



VIIIIS Rebuilt Nozzles

Pressure activated, automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F Reconnectable Safe-T-Break®
005812	1" F x 1" F Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F Multi-Plane Swivel
004860	1" M x 1" F Multi-Plane High Volume Swivel
000095	1" M x 1" F Multi-Plane 70° Pump Swivel
003395	1" M x 1" F Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M Multi-Plane Swivel connected to 1" F Reconnectable Safe-T-Break®

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly with Spout Bushing
005017	Complete Spout Assembly without Spout Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Spout Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assy Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



VIII BSPP Nozzles



4-20

HIGH VOLUME FUELING

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.


- VIII nozzle shuts off when the gas tank is full.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.

New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
749338N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	4.5 (2.0)
1108738N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing, Nickel Plated Body	4.5 (2.0)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle with metal handguard for truck stop and other high volume full-service, self-service and unattended stations.

Dimensions and System Options

BSPP Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003076	1" F x 1" F Reconnectable Safe-T-Break®
003076A	1" F x 1" F Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F Non-Reconnectable Safe-T-Break®

BSPP Swivels

MODEL NO.	DESCRIPTION
003306	1" M x 1" F Multi-Plane Swivel
006949	1" M x 1" F Multi-Plane High Flow Swivel

BSPP Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
002279	Complete Spout Assembly Kit with Bushing
005017	Complete Spout Assembly Kit without Bushing
003589	Complete Long Spout Assembly with Spout Bushing
011043	Complete Spout Assembly without Bushing and Small Spout Spring

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
006645	Plunger Assembly Lift Tool



Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005516	Full Grip Reguard
005494	Lever Guard
008178	POPD® EZH Nozzle Guard
008177	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008186	POPD® H Full Grip Guard
008193	POPD® H Full Grip Reguard
008168	POPD® H Mate Guard
006628	POPD® S Clear Cover
007352	POPD® S Full Grip Guard
008194	POPD® S Full Grip Reguard
008167	POPD® S Mate Guard
001808	Waffle Splash Guard

1HSS Nozzles



4-23

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for dispensing up to 25 gpm / 94.6 Lpm.

- 1HSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Comes standard with smooth full grip guard.
- Optional EZ Lever and tilt poppet:
 - two piece lever design cuts opening force in half.
 - maximizes “to-the-penny” dispensing.
 - ADA compliant.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.




New Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1217110	with Three Notch Hold Open Clip	3.4 (1.5)
1217165	with Three Notch Hold Open Clip and Waffle Splash Guard	3.4 (1.5)
1437710N^	with Two Notch Hold Open Clip, EZ Lever and Tilt Poppet	3.4 (1.5)

^ NOT LISTED

Construction

Body	Die cast aluminum body with high impact polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1HSS Nozzles

Pressure activated, automatic shut-off nozzle with polymer handguard for dispensing up to 25 gpm / 94.6 Lpm.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPTF Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
005215	Heavy Duty Diesel Spout with Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Nozzle Guard
001804	Full Grip Nozzle Reguard
005494	Lever Guard
007376	Mate Handle Cover
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard
000099	Protection Package
001811	Reguard Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1HSS Nozzles



4-24

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for dispensing up to 25 gpm / 94.6 Lpm.

- 1HSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Comes standard with smooth full grip guard.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.




New Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1217410	with Three Notch Hold Open Clip	3.4 (1.5)
12174240	with Single Notch Hold Open Clip	3.4 (1.5)

Construction

Body	Die cast aluminum with metal hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle with metal handguard for dispensing up to 25 gpm / 94.6 Lpm.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
005215	Heavy Duty Diesel Spout with Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Nozzle Guard
001804	Full Grip Nozzle Reguard
005494	Lever Guard
007295	Mate Handle Cover
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard
000099	Protection Package
001811	Reguard Package
001808	Waffle Splash Guard

1HSS CW Nozzles



4-25

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with polymer handguard for dispensing up to 25 gpm / 94.6 Lpm.

- 1HSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Comes standard with smooth full grip guard.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.




New Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1399910	with Three Notch Hold Open Clip	3.4 (1.5)

Construction

Body	Die cast aluminum body with high impact polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1HSS CW Nozzles

Pressure activated, automatic shut-off nozzle with polymer handguard for dispensing up to 25 gpm / 94.6 Lpm.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPTF Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
005215	Heavy Duty Diesel Spout with Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Nozzle Guard
001804	Full Grip Nozzle Reguard
005494	Lever Guard
007376	Mate Handle Cover
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard
000099	Protection Package
001811	Reguard Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1HSS CW Nozzles



4-26

HIGH VOLUME FUELING

Pressure activated, automatic shut-off nozzle with metal handguard for dispensing up to 25 gpm / 94.6 Lpm.

- 1HSS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Comes standard with smooth full grip guard.
- Contains a poppet disc seal, rated at -40° F/C to prevent fuel leakage from the main seal in extreme cold weather.




New Diesel Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1400110	with Three Notch Hold Open Clip	3.4 (1.5)

Construction

Body	Die cast aluminum with metal hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT & BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1HSS CW Nozzles

Pressure activated, automatic shut-off nozzle with metal handguard for dispensing up to 25 gpm / 94.6 Lpm.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®
003076	1" F x 1" F BSPP Reconnectable Safe-T-Break®
003076A	1" F x 1" F BSPP Reconnectable Safe-T-Break® - Atex
006914	1" F x 1" F BSPP Non-Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®
008015	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break®
008015A	1" M BSPP Multi-Plane Swivel connected to 1" F BSPP Reconnectable Safe-T-Break® - Atex

Spouts


MODEL NO.	DESCRIPTION
005215	Heavy Duty Diesel Spout with Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit



Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Nozzle Guard
001804	Full Grip Nozzle Reguard
005494	Lever Guard
007295	Mate Handle Cover
000226	Mate Nozzle Guard
008180	POPD® EZH Nozzle Guard
008179	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008183	POPD® H Full Grip Guard
008190	POPD® H Full Grip Reguard
008170	POPD® H Mate Guard
006628	POPD® S Clear Cover
006655	POPD® S Full Grip Guard
007210	POPD® S Full Grip Reguard
008169	POPD® S Mate Guard
000099	Protection Package
001811	Reguard Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Vapor Recovery Nozzles



V34iSA DP Nozzles



5-1

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34iSA Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Nozzle Models 7345041N and 7345041A are equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter flow and less splash back spillage.
- Nozzle is equipped with a double poppet for precise, slow-flow, to-the-penny dispensing.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Uses conventional spout without spout ring and aluminum vapor escape guard.
- Vapor assist is achieved at the body end of the spout where a vapor ring captures emissions.




New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
7345021N^	with High Flow Double Poppet and Two Notch Hold Open Clip, without Attitude Device	4.0 (1.8)
7345041N^	with High Flow Double Poppet and Two Notch Hold Open Clip	4.0 (1.8)
7345041A^	with High Flow Double Poppet and Two Notch Hold Open Clip - Atex	4.0 (1.8)
11560021N^	with High Flow Double Poppet, Two Notch Hold Open Clip and Cold Weather Seals	4.0 (1.8)


^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



VAPOR BACK PRESSURE (INCHES H₂O)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
004034A	Reconnectable Safe-T-Break® - Atex
006210	Non-Reconnectable Safe-T-Break®
005134A	Non-Reconnectable Safe-T-Break® - Atex
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Replacement Kit
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34SK DP SG Nozzles



5-2

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34SK Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Nozzles are equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Sightglass on nozzle allows customer to see fuel flow through nozzle.
- *StreamShaper®* reduces turbulence for straighter flow and less splash back spillage.
- Nozzle is equipped with a double poppet for precise, slow-flow, to-the-penny dispensing.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Uses conventional spout with spout ring and soft vapor escape guard.
- Vapor assist is achieved at the body end of the spout where a vapor ring captures emissions.





New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E12111170N [^]	with High Flow Double Poppet and Two Notch Hold Open Clip	4.0 (1.8)
		[^] NOT LISTED

Construction

Body	Aluminum w/reinforced polymer handguard
Seals	Fluorocarbon
Packing	Fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1-1/4" - 18



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

V34SK DP SG Nozzles

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006560	Reconnectable ORVR Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
012115	Complete V34SK Spout Assembly Kit - Unleaded

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Replacement Kit
000397	Unleaded Spout Gauge
012113	Vapor Splash Guard Clamp
012118	V34SK A/L Spout Adaptor
012114	V34SK Vapor Splash Guard (VSG) with Clamp

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34 Nozzles




5-4

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34 Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- *Streamshaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Nozzle spout is covered by a one year warranty.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Uses conventional spout with spout ring and soft vapor escape guard.
- Vapor assist achieved at the body end of the spout where a vapor ring catches emissions.
- Optional EZ Lever:
 - two piece design cuts opening force in half
 - easier "to-the-penny" dispensing
 - ADA compliant



New Unleaded Nozzles



MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6250041	with Three Notch Hold Open Clip	4.0 (1.8)
6250041A*	with Three Notch Hold Open Clip - Atex	4.0 (1.8)
6250241	with Three Notch Hold Open Clip and Sightglass	4.0 (1.8)
6250941	with Three Notch Hold Open Clip and POPD® Full Grip Guard	4.0 (1.8)
6250431	with Single Notch Hold Open Clip	4.0 (1.8)
6250891	with Single Notch Hold Open Clip and POPD® Full Grip Guard	4.0 (1.8)
6250081	without Hold Open Clip	4.0 (1.8)
11996041	with Two Notch Hold Open Clip and EZ Lever	4.0 (1.8)

Rebuilt Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6254041	with Three Notch Hold Open Clip	3.7 (1.6)
6254241	with Three Notch Hold Open Clip and Sightglass	3.7 (1.6)
6254081	without Hold Open Clip	3.7 (1.6)

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



AIR RESOURCES BOARD



II 1 G
EN 13012
Type 1



P-TÜ7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
004034A	Reconnectable Safe-T-Break® - Atex
006210	Non-Reconnectable Safe-T-Break®
005134A	Non-Reconnectable Safe-T-Break® - Atex
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel - Atex

Spouts


MODEL NO.	DESCRIPTION
006291	Complete Spout Assembly Kit - Unleaded
006391	Unleaded Spout

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
006941	Adaptor, Conventional Fueling to 3/4"
004360	Air/Liquid Spout Adaptor
003593	Hold Open Clip Kit
004335	O-ring, Air/Liquid Test Spout Adaptor
005233	O-ring Kit
007089	Nozzle Service Kit
005260	Tool for dry Air/Liquid Test
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®
004000	Vapor Splash Guard (VSG) with Clamp
004039	Vapor Splash Guard Clamp
006497	VSG Clamp Tool
010073	Waffle VSG with Clamp (single notch V34)
010076	Waffle VSG without Clamp (single notch V34)



Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34 Coax Nozzles



5-5

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34 Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Uses a coaxial spout with spout ring and has large vapor-capturing holes at the end of the spout.
- Nozzle spout is covered by a one year warranty.


New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6200041	with Coaxial Spout and Three Notch Hold Open Clip	4.0 (1.8)
14229041N^	with Coaxial Spout, Two Notch Hold Open Clip, EZ Lever and Tokheim Polymer Handguard	4.0 (1.8)


^Not Listed

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



VAPOR BACK PRESSURE (INCHES H₂O)



AIR RESOURCES BOARD



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

V34 Coax Nozzles

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
006210	Non-Reconnectable Safe-T-Break®
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel

Spouts

MODEL NO.	DESCRIPTION
008642	Complete Spout Assembly Kit - Unleaded

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004360	Air/Liquid Spout Adaptor
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Kit
005260	Tool for dry Air/Liquid Test
000397	Unlead Spout Gauge
005837	Vapor Assist Flo-Equalizer®
004000	Vapor Splash Guard (VSG) with Clamp
004039	Vapor Splash Guard Clamp
006497	VSG Clamp Tool

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34 DP Nozzles



5-6

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34 nozzle shuts off when the gas tank is full.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- *Streamshaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Uses conventional spout with spout ring and soft vapor escape guard.
- Vapor assist achieved at the body end of the spout where a vapor ring catches emissions.
- Nozzle spout is covered by a one year warranty.



New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6252041	with Double Poppet and Two Notch Hold Open Clip	4.0 (1.8)
6252041A*	with Double Poppet and Two Notch Hold Open Clip - Atex	4.0 (1.8)
6252931A*	with High Flow Double Poppet and Two Notch Hold Open Clip - Atex	4.0 (1.8)

Rebuilt Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6254041	with Three Notch Hold Open Clip	3.7 (1.6)
6254241	with Three Notch Hold Open Clip and Sightglass	3.7 (1.6)
6254081	without Hold Open Clip	3.7 (1.6)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



VAPOR BACK PRESSURE (INCHES H₂O)



AIR RESOURCES BOARD



II 1 G
EN 13012
Type 1



P-TÜ7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
006210	Non-Reconnectable Safe-T-Break®
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel - Atex

Spouts


MODEL NO.	DESCRIPTION
006291	Complete Spout Assembly Kit - Unleaded
006391	Unleaded Spout

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004360	Air/Liquid Spout Adaptor
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Kit
005260	Tool for dry Air/Liquid Test
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®
004000	Vapor Splash Guard (VSG) with Clamp
004039	VSG Clamp
006497	VSG Clamp Tool



Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard

V34 ORVR Nozzles



5-7

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34 Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Nozzle designed for the Veeder-Root® 900301 and VST Enviro-Loc® primary hose with ORVR valve.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper®* reduces turbulence for straighter flow and less splash back spillage.
- Uses conventional spout with spout ring and soft vapor escape guard.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Vapor assist achieved at the body end of the spout where a vapor ring catches emissions.




New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6536041	with Three Notch Hold Open Clip	4.0 (1.8)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Fiber Reinforced Teflon®
Lever	One Piece Contoured Steel with hard plastic cover
Inlet	1 1/4" - 18



VAPOR BACK PRESSURE (INCHES H₂O)



California Environmental Protection Agency
AIR RESOURCES BOARD



Texas Commission on
Environmental Quality

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



V34 ORVR Nozzles

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006560	Reconnectable ORVR Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
006663	Complete Spout Assembly Kit - Unleaded
006391	Unleaded Spout

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004360	A/L Spout Adaptor
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Replacement Kit
006656	ORVR Vapor Splash Guard (VSG) with Clamp
005260	Tool For Dry A/L Test
005837	Vapor Assist Flo-Equalizer®
004039	Vapor Splash Guard Clamp
006497	VSG Clamp Tool

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34i Nozzle shuts off when the gas tank is full.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper*® reduces turbulence for straighter flow and less splash back spillage.
- Uses conventional spout with spout ring and soft vapor escape guard.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Vapor assist achieved at the body end of the spout where a vapor ring catches emissions.
- Nozzle spout is covered by a one year warranty.





New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6670041N^	with Two Notch Hold Open Clip	4.0 (1.8)
6670041A*	with Two Notch Hold Open Clip - Atex	4.0 (1.8)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
004034A	Reconnectable Safe-T-Break® - Atex
006210	Non-Reconnectable Safe-T-Break®
005134A	Non-Reconnectable Safe-T-Break® - Atex
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel - Atex

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Kit
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34i DP Nozzles



5-9

VAPOR RECOVERY

Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34i nozzle shuts off when the gas tank is full.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- *StreamShaper*® reduces turbulence for straighter flow and less splash back spillage.
- Nozzle is equipped with a double poppet for precise, slow-flow, to-the-penny dispensing.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Uses conventional spout without spout ring and aluminum vapor escape guard.
- Vapor assist is achieved at the body end of the spout where a vapor ring captures emissions.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.




New Unleaded Nozzles


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
7321041A*	with Double Poppet, and Three Notch Hold Open Clip - Atex	4.0 (1.8)
7320041A*	with High Flow Double Poppet, and Three Notch Hold Open Clip - Atex	4.0 (1.8)
7320101A*	with High Flow Double Poppet, without Three Notch Hold Open Clip - Atex	4.0 (1.8)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



VAPOR BACK PRESSURE (INCHES H₂O)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
006210	Non-Reconnectable Safe-T-Break®
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel - Atex

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Replacement Kit
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34i nozzle shuts off when the gas tank is full.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- *StreamShaper*® reduces turbulence for straighter flow and less splash back spillage.
- Nozzle is equipped with a double poppet for precise, slow-flow, to-the-penny dispensing.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Uses conventional spout without spout ring and aluminum vapor escape guard.
- Vapor assist is achieved at the body end of the spout where a vapor ring captures emissions.

Model 8686041N

- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.





New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
8686021N^	with Double Poppet, Cold Weather Seals and Two Notch Hold Open Clip	4.0 (1.8)
8686041N^	with Double Poppet, Cold Weather Seals, Flo-Stop® and Two Notch Hold Open Clip	4.0 (1.8)

^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

V34i DP & CW Nozzles

Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
006210	Non-Reconnectable Safe-T-Break®
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Replacement Kit
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34iA DP Nozzles



5-11

VAPOR RECOVERY

Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34iA nozzle shuts off when the gas tank is full.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- *StreamShaper*® reduces turbulence for straighter flow and less splash back spillage.
- Nozzle is equipped with a double poppet for precise, slow-flow, to-the-penny dispensing.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Uses conventional spout without spout ring and aluminum vapor escape guard.
- Vapor assist is achieved at the body end of the spout where a vapor ring captures emissions.
- Nozzle spout is covered by a one year warranty.





New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
7320041N^	with High Flow Double Poppet and Two Notch Hold Open Clip	4.0 (1.8)
7320081N^	with High Flow Double Poppet, without Hold Open Clip	4.0 (1.8)
		^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



V34iA DP Nozzles

Automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
004034A	Reconnectable Safe-T-Break® - Atex
006210	Non-Reconnectable Safe-T-Break®
005134A	Non-Reconnectable Safe-T-Break® - Atex
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Replacement Kit
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34iS Nozzles



5-12

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34iS Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter flow and less splash back spillage.
- Uses conventional spout with spout ring and soft vapor escape guard.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Vapor assist achieved at the body end of the spout where a vapor ring catches emissions.





New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6675041	with Two Notch Hold Open Clip	4.0 (1.8)
6675041A*	with Two Notch Hold Open Clip - Atex	4.0 (1.8)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



II 1 G
EN 13012
TYPE 1



P-TÜ7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
004034A	Reconnectable Safe-T-Break® - Atex
006210	Non-Reconnectable Safe-T-Break®
005134A	Non-Reconnectable Safe-T-Break® - Atex
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel - Atex

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Kit
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V34iS DP Nozzles



5-13

VAPOR RECOVERY

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34iS Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- StreamShaper® reduces turbulence for straighter flow and less splash back spillage.
- Nozzle is equipped with a double poppet for precise, slow-flow, to-the-penny dispensing.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Uses conventional spout without spout ring and aluminum vapor escape guard.
- Vapor assist is achieved at the body end of the spout where a vapor ring captures emissions.




New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
7345041N^	with High Flow Double Poppet and Two Notch Hold Open Clip	4.0 (1.8)
7345041A*	with High Flow Double Poppet and Two Notch Hold Open Clip - Atex	4.0 (1.8)


^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



VAPOR BACK PRESSURE (INCHES H₂O)



INLET PRESSURE (SpG = .78)



II 1 G
EN 13012
TYPE 1



P-TÜ7-8113626964



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



V34iS DP Nozzles

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
004034A	Reconnectable Safe-T-Break® - Atex
006210	Non-Reconnectable Safe-T-Break®
005134A	Non-Reconnectable Safe-T-Break® - Atex
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel - Atex

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Replacement Kit
000397	Unleaded Spout Gauge
005837	Vapor Assist Flo-Equalizer®

Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Ethanol Fueling Nozzles



X E85 Nozzles



6-1

ETHANOL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- Aluminum body, spout, and internal parts are nickel plated to prevent contamination and corrosion from Ethanol blends.
- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-85.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Husky® X nozzle shuts off when the gas tank is full.
- Nozzle comes with smooth full grip guard.
- All seals are UL approved fluorocarbon compounds to prevent deterioration from Ethanol blends.
- New poppet seal design improves flow control and provides enhanced endurance over time.




New Unleaded Nozzles - MHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
659404N^	with Three Notch Hold Open Clip	2.8 (1.2)
659459N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.2)
659444N^	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.0 (1.2)
659495N^	with Three Notch Hold Open Clip, POPD® S Full Grip Guard, Waffle Splash Guard	3.0 (1.2)

^ NOT LISTED

Construction

Body	Die cast aluminum with Electroless Nickel Plating
Seals	Fluorocarbon
Handguard	Metal or Polymer
Packing	Double O-ring seal protected by fiber reinforced Teflon®
Lever	Polymer
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006360 [^]	¾" F x ¾" F Reconnectable E85 Safe-T-Break®
006273	¾" F x ¾" F Non-Reconnectable E25/E85 Safe-T-Break®

[^] NOT UL LISTED

Swivels

MODEL NO.	DESCRIPTION
006350 [^]	¾" M x ¾" F Multi-plane E85 Swivel

[^] NOT UL LISTED

Spouts

MODEL NO.	DESCRIPTION
006207	Unleaded E85 Spout Assembly

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
006628	POPD® Clear Cover
006665	POPD® Full Grip Guard
007205	POPD® Full Grip Reguard
007815	POPD® Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X E85 CW Nozzles



6-2

ETHANOL FUELING

Automatic shut-off nozzle for full-service and self-service stations.


- Aluminum body, spout, and internal parts are nickel plated to prevent contamination and corrosion from Ethanol blends.
- Contains a poppet seal rated at -40°F/C to prevent fuel leakage from the main seal in extreme cold weather.
- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-85.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Nozzle comes with smooth full grip guard
- New poppet seal improves flow control and provides enhanced endurance over time.

New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
665904N^	with Three Notch Hold Open Clip	2.5 (1.3)
665964N^	with Three Notch Hold Open Clip and Flo-Splash Guard	2.5 (1.3)
665954N^	with Three Notch Hold Open Clip and Flo-Equalizer®	2.5 (1.3)
665944N^	with Three Notch Hold Open Clip and Flo-Equalizer®	2.5 (1.3)

Construction

Body	One piece die cast aluminum
Seals	Fluoropolymer
Packing	Doughnut seal protected by reinforced Teflon®
Lever	Stainless steel
Inlet	3/4"



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



X E85 CW Nozzles

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006360 [^]	¾" F x ¾" F Reconnectable E85 Safe-T-Break®
006273	¾" F x ¾" F Non-Reconnectable E85 Safe-T-Break®

[^] NOT LISTED

Swivels

MODEL NO.	DESCRIPTION
006350 [^]	¾" M x ¾" F Multi-plane E85 Swivel

[^] NOT LISTED

Spouts

MODEL NO.	DESCRIPTION
006207	X, XS® E85 Spout Assy with StreamShaper®

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Interlock - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm
007089	Nozzle Service Kit
000397	Unleaded Spout

Guards

MODEL NO.	DESCRIPTION
003376	POP® Full Grip Guard
004145	POP® Full Grip Guard
001806	POP® Full Grip Guard
005494	POP® Full Grip Guard
003440	POP® Full Grip Guard
003795	POP® Full Grip Guard
006628	POP® Full Grip Guard
006665	POP® Full Grip Guard
007205	POP® Full Grip Guard
007815	POP® Full Grip Guard
001506	POP® Full Grip Guard
001809	POP® Full Grip Guard
001808	POP® Full Grip Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® E85 Nozzles



6-3

ETHANOL FUELING

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® E85 Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Aluminum body, spout, and internal parts are nickel plated to prevent contamination and corrosion from Ethanol blends.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-85.
- Nozzle comes with smooth full grip guard.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- All seals are UL approved fluorocarbon compounds to prevent deterioration from Ethanol blends.
- New poppet seal design improves flow control and provides enhanced endurance over time.



New Unleaded Nozzles - MHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
659504	with Three Notch Hold Open Clip	3.0 (1.3)
659508	without Three Notch Hold Open Clip	3.0 (1.3)
659559	with Three Notch Hold Open Clip and Waffle Splash Guard	2.9 (1.3)
659589	with Single Notch Hold Open Clip, POPD® S Full Grip Guard and Waffle Splash Guard	3.0 (1.3)
6595100N^	with Three Notch Hold Open Clip, POPD® S Full Grip Guard, Waffle Splash Guard and Sightglass	3.0 (1.3)
6595119	with Three Notch Hold Open Clip and POPD® H Full Grip Guard	3.0 (1.3)
6595146	with Three Notch Hold Open Clip, POPD® H Full Grip Guard and Waffle Splash Guard	3.0 (1.3)
6595179	with Single Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
6595181	with Three Notch Hold Open Clip, POPD® H Full Grip Guard and 1807 Waffle Splash Guard	3.0 (1.3)

^ NOT LISTED


New Unleaded Nozzles - PHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E1488404	with Two Notch Hold Open Clip, EZ Lever, Polymer Handguard and Mate Guard	3.0 (1.2)
E1488459	with Two Notch Hold Open Clip, EZ Lever, Polymer Handguard, Mate Guard and Waffle Splash Guard	3.0 (1.2)
E1488495	with Two Notch Hold Open Clip, EZ Lever, Polymer Handguard, POPD®S Full Grip Guard and Waffle Splash Guard	3.0 (1.2)
1488404	with Two Notch Hold Open Clip, EZ Lever, Polymer Handguard and Full Grip Guard	3.0 (1.2)
1421304N^	with Two Notch Hold Open Clip, EZ Lever, Tilt Poppet and Full Grip Guard	3.0 (1.2)
1581759	with Two Notch Hold Open Clip, Polymer Handguard and Full Grip Guard	3.0 (1.2)

^ NOT LISTED

Construction

Body	Die cast aluminum with Electroless Nickel Plating
Seals	Fluorocarbon
Handguard	Metal or Polymer
Packing	Double O-ring seal protected by fiber reinforced Teflon®
Lever	Polymer
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



XS[®] E85 Nozzles

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks[®]

MODEL NO.	DESCRIPTION
006360 [^]	¾" F x ¾" F Reconnectable E85 Safe-T-Break [®]
006273	¾" F x ¾" F Non-Reconnectable E85 Safe-T-Break [®]

[^] NOT UL LISTED

Swivels

MODEL NO.	DESCRIPTION
006350 [^]	¾" M x ¾" F Multi-plane E85 Swivel

[^] NOT UL LISTED

Spouts

MODEL NO.	DESCRIPTION
006207	Unleaded E85 Spout Assembly

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer [®] - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
004951	Spout Nut
000397	Unleaded Spout Gauge

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
006628	POPD [®] Clear Cover
006665	POPD [®] Full Grip Guard
007205	POPD [®] Full Grip Reguard
007815	POPD [®] Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® E85 nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Aluminum body, spout, and internal parts are nickel plated to prevent contamination and corrosion from Ethanol blends.
- Contains a poppet seal rated at -40°F/C to prevent fuel leakage from the main seal in extreme cold weather.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-85.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Nozzle comes with smooth full grip guard.
- New poppet seal improves flow control and provides enhanced endurance over time.



New Unleaded Nozzles - MHG


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
666164	with Three Notch Hold Open Clip and Waffle Splash Guard	2.9 (1.3)
^ NOT LISTED		

New Unleaded Nozzles - PHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
666154N^	with Hold Open Clip, Polymer Hand Guard, Spout Bushing, Full Grip Guard and #1808 Waffle Splash Guard and Cold Weather Seals and Flo Equalizer	3.0 (1.2)
^ NOT LISTED		

Construction

Body	Die cast aluminum with Electroless Nickel Plating
Seals	Fluorocarbon
Handguard	Metal or Polymer
Packing	Double O-ring seal protected by fiber reinforced Teflon®
Lever	Polymer
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006360^	¾" F x ¾" F Reconnectable E85 Safe-T-Break®
006273	¾" F x ¾" F Non-Reconnectable E85 Safe-T-Break®

^ NOT UL LISTED

Swivels

MODEL NO.	DESCRIPTION
006350^	¾" M x ¾" F Multi-plane E85 Swivel

^ NOT UL LISTED

Spouts

MODEL NO.	DESCRIPTION
006207	Unleaded E85 Spout without Flo-Stop®

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing, and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
006628	POPD® Clear Cover
006665	POPD® Full Grip Guard
007205	POPD® Full Grip Reguard
007815	POPD® Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X E25 Nozzle



6-5

ETHANOL FUELING

Automatic shut-off nozzle for full-service and self-service stations.

- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-25.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Husky® X nozzle shut off when the gas tank is full.
- Nozzle comes with smooth full grip guard.
- All seals are UL approved fluorocarbon compounds to prevent deterioration from Ethanol blends.
- New poppet seal design improves flow control and provides enhanced endurance over time.



New Unleaded Nozzle - MHG


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1108059N^	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.2)
		^ NOT LISTED

New Unleaded Nozzles - PHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1175504N^	with Three Notch hold Open Clip, Polymer Hand Guard, Spout Bushing and Full Grip Guard with EZ Lever	3.0 (1.2)
		^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Handguard	Metal or Polymer
Packing	Double O-ring seal protected by fiber reinforced Teflon®
Lever	Polymer
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006360^	¾" F x ¾" F Reconnectable E25 Safe-T-Break®
006273	¾" F x ¾" F Non-Reconnectable E25/E85 Safe-T-Break®

^ NOT LISTED

Spouts

MODEL NO.	DESCRIPTION
011100	Unleaded E25 Spout Assembly

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
006628	POPD® Clear Cover
006665	POPD® Full Grip Guard
007205	POPD® Full Grip Reguard
007815	POPD® Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® E25 Nozzle



6-6

ETHANOL FUELING

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® E25 Nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-25.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Nozzle comes with smooth full grip guard.
- All seals are UL approved fluorocarbon compounds to prevent deterioration from Ethanol blends.
- New poppet seal design improves flow control and provides enhanced endurance over time.



New Unleaded Nozzle - MHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1108689	with One Notch Hold Open Clip, POPD®s Full Grip Guard and Waffle Splash Guard	3.0 (1.3)
11086179	with One Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
11084181	with Three Notch Hold Open Clip, POPD® H Full Grip Guard, 001807 Waffle Splash Guard	3.0 (1.2)

^ NOT LISTED


New Unleaded Nozzles - PHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1503204N^	with Two Notch Hold Open Clip, EZ Lever, Polymer Handguard and Full Grip Guard	3.0 (1.2)
E1503204	with Two Notch Hold Open Clip, EZ Lever, Polymer Handguard and Mate Guard	3.0 (1.2)
E1503259	with Two Notch Hold Open Clip, EZ Lever, Polymer Handguard, Mate Guard and Waffle Splash Guard	3.0 (1.2)

^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Handguard	Metal or Polymer
Packing	Double O-ring seal protected by fiber reinforced Teflon®
Lever	Polymer
Inlet	3/4" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks[®]

MODEL NO.	DESCRIPTION
006360 [^]	¾" F x ¾" F Reconnectable E25 Safe-T-Break [®]
006273	¾" F x ¾" F Non-Reconnectable E25/E85 Safe-T-Break [®]

[^] NOT LISTED

Spouts

MODEL NO.	DESCRIPTION
011100	Unleaded E25 Spout Assembly

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
004951	Spout Nut
000397	Unleaded Spout Gauge

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
006628	POPD [®] Clear Cover
006665	POPD [®] Full Grip Guard
007205	POPD [®] Full Grip Reguard
007815	POPD [®] Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



X E25 CW Nozzle



6-7

ETHANOL FUELING

Automatic shut-off nozzle for full-service and self-service stations.


- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-25.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Husky® X nozzle shut off when the gas tank is full.
- Nozzle comes with smooth full grip guard.
- All seals are UL approved fluorocarbon compounds to prevent deterioration from Ethanol blends.
- New poppet seal design improves flow control and provides enhanced endurance over time.

New Unleaded Nozzle

MODEL NO.	DESCRIPTION	WEIGHT LBS (KG)
1108259^	with Three Notched Open Guard	3.0 (1.2)
		^ NOT LISTED

Construction

Body	Stainless steel die cast
Seals	Fluorocarbon
Packing	Seal protected by fiber reinforced Teflon®
Lever	Contoured polymer
Spout	Stainless steel



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



X E25 CW Nozzle

Automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006360 [^]	¾" F x ¾" F Reconnectable E25 Safe-T-Break®
006273	¾" F x ¾" F Non-Reconnectable E25/E85 Safe-T-Break®

[^] NOT LISTED

Spouts

MODEL NO.	DESCRIPTION
011100	Unleaded E25 Spout Assembly

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reel Guard
005494	Lever Guard
003440	Mechanical Protection Package
003795	Regard®
006628	Regard®
006665	Full Grip Guard
007205	Full Grip Guard
007815	Full Grip Guard
001506	Protection Package
001809	Regard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



XS® E25 CW Nozzle



6-8

ETHANOL FUELING

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

- XS® E25 nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- *StreamShaper®* reduces turbulence for straighter fuel flow and less splash back spillage.
- Compatible with unleaded and all Ethanol blends through E-25.
- A reinforced stainless steel spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Nozzle comes with smooth full grip guard.
- All seals are UL approved fluorocarbon compounds to prevent deterioration from Ethanol blends.
- New poppet seal design improves flow control and provides enhanced endurance over time.




New Unleaded Nozzle - MHG

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1108459	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
		^ NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Handguard	Metal or Polymer
Packing	Double O-ring seal protected by fiber reinforced Teflon®
Lever	Polymer
Inlet	¾" / 19 mm NPT



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



XS® E25 CW Nozzle

Pressure activated, automatic shut-off nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
006360^	¾" F x ¾" F Reconnectable E25 Safe-T-Break®
006273	¾" F x ¾" F Non-Reconnectable E25/E85 Safe-T-Break®

^ NOT LISTED

Spouts

MODEL NO.	DESCRIPTION
011100	Unleaded E25 Spout Assembly

Pressure/Vacuum Vents


MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
004951	Spout Nut
000397	Unleaded Spout Gauge

Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
006628	POPD® Clear Cover
006665	POPD® Full Grip Guard
007205	POPD® Full Grip Reguard
007815	POPD® Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Whiskey Nozzles



Automatic shut-off nozzle for wine and distilled spirits dispensing.

- Modular design for easy cleaning.
- Nozzle shuts off when the container is full.
- Comes standard with mate nozzle guard and handle cover.
- Seals provide maximum durability and chemical resistance to high concentrations of ethanol.
- Stainless Steel construction.
- Constructed with food grade materials.




New WN Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E8528104N [^]	Stainless steel, 1" Inlet BSPP, 3/4" OD spout, mate nozzle guard and two notch hold open clip	3.0 (1.3)
		[^] NOT LISTED

Construction

Body	Investment Cast Stainless Steel
Disc	Ethylene Propylene
Packing	Double o-ring seal protected by fiber reinforced Teflon [®]
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm BSPP




Automatic shut-off nozzle for wine and distilled spirits dispensing.

Dimensions and System Options

Guards

MODEL NO.	DESCRIPTION
008429	Handguard Repair
007376	Handle Cover (Black)
000226	Mate Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Automatic shut-off nozzle for distilled spirits dispensing.

- Aluminum body, spout, and internal parts are nickel-plated to prevent contamination and corrosion.
- *StreamShaper*® reduces turbulence for straighter flow and less splash back spillage.
- Nozzle comes standard with Mate Nozzle Guard and Black Handle Cover.
- Seals provide maximum durability and chemical resistance to high concentrations of ethanol.
- Stainless steel reinforced spout bushing keeps the spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle shuts off when the container is full.

New XWN Nozzles with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E840004N [^]	Nickel-Plated, with 3/4" NPT Inlet, 13/16" O.D. Spout, Mate Nozzle Guard, and Three Notch Hold Open Clip; without Flo-Stop®	2.8 (1.2)

[^] NOT LISTED


New XWN Nozzles with BSP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E840016N [^]	Nickel-Plated, with 3/4" BSP Inlet, 13/16" O.D. Spout, Mate Nozzle Guard, and Three Notch Hold Open Clip; without Flo-Stop®	2.8 (1.2)

[^] NOT LISTED

Construction

Body	Die cast aluminum with Electroless Nickel Plating
Disc	Fluorocarbon
Packing	Double O-ring seal protected by fiber reinforced Teflon®
Lever	One piece high-impact polymer
Inlet	3/4" / 19 mm NPT or 3/4" / 19 mm BSP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for distilled spirits dispensing.

Dimensions and System Options

Guards

MODEL NO.	DESCRIPTION
012117	Black Handle Guard
003440	Mate Easy-on Package
003795	Mate Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1AWN Nozzles



8-3

DISTILLED SPIRITS DISPENSING

Automatic shut-off nozzle with polymer handguard for distilled spirits dispensing.

- Nozzle shuts off when the container is full.
- Aluminum reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle comes standard with mate guard and black handle cover.
- *StreamShaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Aluminum body, spout, and internal parts are nickel plated to prevent contamination and corrosion.
- Seals provide maximum durability and chemical resistance to high concentrations of ethanol.



New 1AWN Nozzles with NPT


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E874203N [^]	Nickel-Plated, with 1" NPT inlet, ¹⁵ / ₁₆ " O.D. Spout, Mate Guard and Three Notch Hold Open Clip; without Flo-Stop®	3.3 (1.4)
		[^] NOT LISTED

New 1AWN Nozzles with BSP

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E874215N [^]	Nickel-Plated, with 1" BSP inlet, ¹⁵ / ₁₆ " O.D. Spout, Mate Guard and Three Notch Hold Open Clip; without Flo-Stop®	3.3 (1.4)
		[^] NOT LISTED

Construction

Body	Die cast aluminum body with electroless nickel plating and black polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT or 1" / 25.4 mm BSP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


1AWN Nozzles

Automatic shut-off nozzle with polymer handguard for distilled spirits dispensing.

Dimensions and System Options

Guards

MODEL NO.	DESCRIPTION
000554	Full Grip Guard
005494	Lever Guard
007295	Mate Handle Guard
000226	Mate Nozzle Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

VIII WN Nozzles



8-4

DISTILLED SPIRITS DISPENSING

High-Flow automatic nozzle for distilled spirits dispensing.

- Nozzle shuts off when the container is full.
- Automatic shut-off with dual poppets for easy opening.
- Nozzle comes standard with full grip guard.
- Aluminum body, spout, and internal parts are nickel plated to prevent contamination and corrosion.
- Seals provide maximum durability and chemical resistance to high concentrations of ethanol.

New VIII WN Nozzles with NPT


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
874110N [^]	Nickel-Plated, with 1" NPT inlet, 1 3/16" O.D. Spout and Three Notch Hold Open Clip; without Flo-Stop [®]	3.9 (1.7)
		[^] NOT LISTED

New VIII WN Nozzles with BSP

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
874138N [^]	Nickel-Plated, with 1" BSP inlet, 1 3/16" O.D. Spout and Three Notch Hold Open Clip; without Flo-Stop [®]	3.9 (1.7)
		[^] NOT LISTED

Construction

Body	Sand cast aluminum body with electroless nickel plating and black polymer hand guard
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon [®]
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT or 1" / 25.4 mm BSP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS


VIII WN Nozzles

High-Flow automatic nozzle for distilled spirits dispensing.

Dimensions and System Options

Guards

MODEL NO.	DESCRIPTION
004740	Full Grip Guard
005494	Lever Guard
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



1690WN Nozzles



8-5

DISTILLED SPIRITS DISPENSING

Extreme High-Flow automatic nozzle for distilled spirits dispensing.

- Nozzle designed with extra large hand opening to accomodate gloves or mittens.
- Automatic shut-off with dual poppets for easy opening.
- Aluminum body, spout, and internal parts are nickel plated to prevent contamination and corrosion.
- Seals provide maximum durability and chemical resistance to high concentrations of ethanol.
- Cast-in protective standoffs provide durability with rough usage
- Right angle design allows nozzle to "fit" close to walls and corners.



New 1690WN Nozzles with NPT


MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
875010N [^]	Nickel-Plated, with 1 1/2" NPT inlet, 1 3/8" O.D. Spout and Two position Hold latch	4.6 (2.0)
		[^] NOT LISTED

New 1690WN Nozzles with BSP

MODEL	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
875038N [^]	Nickel-Plated, with 1 1/2" BSP inlet, 1 3/8" O.D. Spout and Two position Hold latch	4.6 (2.0)
		[^] NOT LISTED

Construction

Body	Sand cast aluminum body with electroless nickel plating
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon [®]
Lever	One piece contoured steel
Inlet	1 1/2" NPT or 1 1/2" BSP




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



1690WN Nozzles

Extreme High-Flow automatic nozzle for distilled spirits edispensing.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





GENERAL FUELING PRODUCTS

Swivels



Standard Swivels



9-1

SWIVELS

For standard fueling applications.



Model 000352



Model 000350



Model 002272

Features

All Husky® Multi-Plane Swivels

- Compatible with unleaded, diesel, and Ethanol blends through E10.
- Compact and light weight for easy handling.
- High flow rates due to laminar flow design.
- High strength step shoulder bearing diameters and impact absorbing stops.

Model 002950 Restricted Swivel

- Multi-Plane, 210° spherical rotation at the swivel nut.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

All Weather Swivels

- Multi-Plane, full 360° spherical rotation for easy movement of nozzle.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

Construction

Body: High Aluminum Zinc Alloy

Inner O-ring: Fluorsilicone

Outer O-ring: Fluorocarbon

Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
000350	3/4" M x 3/4" F	NPT	Multi-Plane Swivel	.50/.22
000352	1" M x 3/4" F	NPT	Multi-Plane Swivel	.66/.29
000355	3/4" M x 3/4" F	NPT	Multi-Plane Swivel, Anodized Black	.49/.22
000356	1" M x 3/4" F	NPT	Multi-Plane Swivel, Anodized Black	.66/.29
002272	3/4" M x 3/4" F	NPT	90° Swivel	.38/.17
002950	3/4" M x 3/4" F	NPT	Multi-Plane Swivel Restricted	.50/.22
001491	3/4" M x 3/4" F	BSPT	Multi-Plane Swivel	.50/.22
003590	3/4" M x 3/4" F	BSPP	Multi-Plane Swivel	.60/.27
003590A*	3/4" M x 3/4" F	BSPP	Multi-Plane Swivel - Atex	.60/.27
002771	3/4" M x 3/4" F	BSPP	90° Swivel	.38/.17
002771A*	3/4" M x 3/4" F	BSPP	90° Swivel - Atex	.38/.17




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Standard Swivels


For standard fueling applications.

Dimensions


Model 000352




Model 000350



Model 002272



Flow Charts



Inline Swivels



9-2

SWIVELS

For standard fueling applications.

Model 003895



Features

All Husky® Multi-Plane Swivels

- Compatible with unleaded, diesel, and Ethanol blends through E10.
- Compact and light weight for easy handling.
- High flow rates due to laminar flow design.
- High strength step shoulder bearing diameters and impact absorbing stops.

All Weather Swivels

- Multi-Plane, full 360° spherical rotation for easy movement of nozzle.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

Construction

Body: Aluminum

Inner O-ring: Fluorsilicone

Outer O-ring: Fluorsilicone


Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
003895	3/4" M x 3/4" F	NPT	Single Plane Swivel	1.4/.65
003898	3/4" M x 1" F	NPT	Single Plane Swivel	1.4/.65
008517	1" M x 1" F	NPT	Single Plane Swivel	1.4/.65
003760	3/4" M x 1" F	BSPT	Single Plane Swivel	1.4/.65
003830	1" M x 1" F	BSPP	Single Plane Swivel	1.4/.65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

For standard fueling applications.

Dimensions



For standard farming applications.



Model 000352



Model 000350



Model 002272

Features

All Husky® Multi-Plane Swivels

- Compatible with unleaded, diesel, and Ethanol blends through E10.
- Compact and light weight for easy handling.
- High flow rates due to laminar flow design.
- High strength step shoulder bearing diameters and impact absorbing stops.

Model 002950 Restricted Swivel

- Multi-Plane, 210° spherical rotation at the swivel nut.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

All Weather Swivels

- Multi-Plane, full 360° spherical rotation for easy movement of nozzle.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

Construction

Body: High Aluminum Zinc Alloy

Inner O-ring: Fluorsilicone

Outer O-ring: Fluorocarbon

Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
000350	3/4" M x 3/4" F	NPT	Multi-Plane Swivel	.50/.22
000352	1" M x 3/4" F	NPT	Multi-Plane Swivel	.66/.29
000355	3/4" M x 3/4" F	NPT	Multi-Plane Swivel, Anodized Black	.49/.22
000356	1" M x 3/4" F	NPT	Multi-Plane Swivel, Anodized Black	.66/.29
002272	3/4" M x 3/4" F	NPT	90° Swivel	.38/.17
002950	3/4" M x 3/4" F	NPT	Multi-Plane Swivel Restricted	.50/.22
001491	3/4" M x 3/4" F	BSPT	Multi-Plane Swivel	.50/.22
003590	3/4" M x 3/4" F	BSPP	Multi-Plane Swivel	.60/.27
003590A*	3/4" M x 3/4" F	BSPP	Multi-Plane Swivel - Atex	.60/.27
002771A*	3/4" M x 3/4" F	BSPP	90° Swivel - Atex	.38/.17




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


For standard farming applications.

Dimensions


Model 000352




Model 000350



Model 002272



Flow Charts



For truck and high volume fueling.



Model 004860



Model 000087



Model 000095

Features

All Husky® Multi-Plane Swivels

- Compatible with diesel fuels and Ethanol blends through E10.
- Compact and light weight for easy handling.
- High flow rates due to laminar flow design.
- High strength step shoulder bearing diameters and impact absorbing stops.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

Husky® High Volume Multi-Plane Swivels

- Multi-Plane, full 360° spherical rotation for easy movement of nozzle.
- For use with high flow nozzles with flow rates up to 100 gpm/ 378 Lpm.
- Raised stainless steel ball bearings provide easy joint movement, greatly improving ease of swivel when used on higher pressure systems.
- 75% less back pressure.

Husky® Multi-Plane Restricted Swivels

- Multi-Plane, 210° spherical rotation at the swivel nut.

Construction

STANDARD

Body: High Aluminum Zinc Alloy

Inner O-ring: Fluorsilicone

Outer O-ring: Fluorocarbon

HIGH VOLUME

Body: Aluminum, Zinc and Zinc Plated Steel

Inner O-ring: Fluorsilicone

Outer O-ring: Fluorocarbon

Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
000087	1" M x 1" F	NPT	Multi-Plane Swivel	.96/.43
004860	1" M x 1" F	NPT	High Flow Multi-Plane Swivel	1.4/.63
000095	1" M x 1" F	NPT	70° Pump Multi-Plane Swivel	.76/.34
003395	1" M x 1" F	NPT	90° Swivel	.93/.42
003306	1" M x 1" F	BSPP	Multi-Plane Swivel	1.1/.49
003306A*	1" M x 1" F	BSPP	Multi-Plane Swivel- Atex	1.1/.49
006949	1" M x 1" F	BSPP	High Flow Multi-Plane Swivel	1.1/.49
006949A*	1" M x 1" F	BSPP	High Flow Multi-Plane Swivel- Atex	1.1/.49
007254	1" M x 1" F	BSPP	90° Swivel	1.1/.49
001670	1" M x 1" F	BSPT	Multi-Plane Swivel	.93/.42




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


For truck and high volume fueling.

Dimensions


Model 000087, 003306, 003395 and 007254




Model 004860 and 006949



Model 000095



Flow Charts



Model 004860
 Models 000087, 000095



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



004605 Vapor Recovery Swivel is compatible with most vacuum assist vapor recovery systems.



Model 004605

Features

- 360° rotation at each swivel joint.
- Double o-rings at each swivel joint.
- Can be installed at the nozzle or at the dispenser.
- Stainless steel ball bearings and races allow for easy joint movement and reduces friction, thus extending the life of the swivel.
- Has 2 (two) plane rotation.
- Exceptional flow rate and reduced back pressure.
- Lightweight and compact.

Construction

Body: Zinc

Inlet Body: Aluminum

Swivel Nut: Electroless, Nickel Plated Aluminum

Seals: Fluorocarbon

Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
004605	M34 x 1.5"	M34	Multi-Plane Swivel	1.0 (.45)
004605A*	M34 x 1.5"	M34	Multi-Plane Swivel - Atex	1.0 (.45)




AIR RESOURCES BOARD





WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

004605 Vapor Recovery Swivel is compatible with most vacuum assist vapor recovery systems.

Dimensions



Flow Charts



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Diesel Swivels



9-6

SWIVELS

Husky® high volume delivery swivels make it easier to manipulate the long, heavy hoses used on bulk delivery systems.



Model 005265

Features

- Prevents kinking and twisting of hose.
- Unique stainless steel ball bearing design provides easier joint movement during high pressure applications.
- Easier to angle the nozzle into fill openings.

Construction

Body: Aluminum

Seals: Fluorocarbon

Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
005235	1¼" F x 1¼" M	NPT	Single Plane Swivel	1.4/.65
005240	1¼" F x 1½" M	NPT	Single Plane Swivel	1.4/.65
005265	1½" F x 1¼" M	NPT	Single Plane Swivel	1.4/.65
005266	1½" F x 1½" M	NPT	Single Plane Swivel	1.4/.65
005754	1¼" F x 1½" M	BSPP	Single Plane Swivel	1.4/.65
005755	1½" F x 1½" M	BSPP	Single Plane Swivel	1.4/.65




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Husky high volume delivery swivels make it easier to manipulate the long, heavy hoses used on bulk delivery systems.

Dimensions

Model 005235, 005240, 005265 and 005266



High Volume Swivels



9-7

SWIVELS

For truck and high volume fueling.



Model 004860



Model 000087



Model 000095

Features

All Husky® Multi-Plane Swivels

- Compatible with diesel fuels and Ethanol blends through E10.
- Compact and light weight for easy handling.
- High flow rates due to laminar flow design.
- High strength step shoulder bearing diameters and impact absorbing stops.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

Husky® High Volume Multi-Plane Swivels

- Multi-Plane, full 360° spherical rotation for easy movement of nozzle.
- For use with high flow nozzles with flow rates up to 100 gpm/ 378 Lpm.
- Raised stainless steel ball bearings provide easy joint movement, greatly improving ease of swivel when used on higher pressure systems.
- 75% less back pressure.

Husky® Multi-Plane Restricted Swivels

- Multi-Plane, 210° spherical rotation at the swivel nut.

Construction

STANDARD

Body: High Aluminum Zinc Alloy

Inner O-ring: Fluorsilicone

Outer O-ring: Fluorocarbon

HIGH VOLUME

Body: Aluminum, Zinc and Zinc Plated Steel

Inner O-ring: Fluorsilicone

Outer O-ring: Fluorocarbon

Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
000087	1" M x 1" F	NPT	Multi-Plane Swivel	.96/.43
004860	1" M x 1" F	NPT	High Flow Multi-Plane Swivel	1.4/.63
000095	1" M x 1" F	NPT	70° Pump Multi-Plane Swivel	.76/.34
003395	1" M x 1" F	NPT	90° Swivel	.93/.42
003306	1" M x 1" F	BSPP	Multi-Plane Swivel	1.1/.49
003306A*	1" M x 1" F	BSPP	Multi-Plane Swivel- Atex	1.1/.49
006949	1" M x 1" F	BSPP	High Flow Multi-Plane Swivel	1.1/.49
006949A*	1" M x 1" F	BSPP	High Flow Multi-Plane Swivel- Atex	1.1/.49
001670	1" M x 1" F	BSPT	Multi-Plane Swivel	.93/.42



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky


GENERAL FUELING PRODUCTS

High Volume Swivels


For truck and high volume fueling.

Dimensions


Model 000087, 003306, 003395 and 007254




Model 004860 and 006949



Model 000095



Flow Charts



Model 004860
Models 000087, 000095



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



DEF Swivels



9-8

SWIVELS

Diesel Exhaust Fluid Inline Swivels.

Model 007269



Model 007275



Model
007467/008510/008822



Model 012604/012656



Model 007282/010936



Features

- Full 360° rotation for easy movement of nozzle.
- Relieves kinking and twisting of the hose.
- High flow rate featuring laminar flow design.
- Compact for easy handling.
- Unique to Husky® products, the steel ball bearing design provides easier joint movement during high pressure applications.
- DEF compatible thread sealant required for NPT threads only

Construction

Body: Stainless Steel, 012604/012656 - Anodized Aluminum

Seals: Fluorocarbon

Nut: 012604 - Stainless Steel

Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
007269	1" M x 1" M	BSPP	Inline Swivel	.60/.27
007275	1" M x M34 M	BSPP/M34	Inline Swivel	.62/.28
007282	3/4" M x 3/4" Hose Barb	BSPP	Roller Bearing Inline Swivel	.42/.19
007467	1" F x 1" M	BSPP	Inline Swivel	.66/.30
008510	1" M x 1" F	BSPP/NPT	Inline Swivel	.66/.30
008822	1" F x 1" M	BSPP	Face Seal Inline Swivel	.66/.30
010936	3/4" M x 3/4" Hose Barb	BSPP	Inline Swivel	.42/.19
012604^	3/4" M x 3/4" F	NPT	Roller Bearing Inline Swivel	.23/.10
012656^	3/4" M x 3/4" F	BSPP	Roller Bearing Inline Swivel	.23/.10

^ NOT LISTED

Accessories

Model No.	Description
007406	3/4" BSPP Seal Kit Assembly
007407	1" BSPP Seal Kit Assembly



^ NOT LISTED




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Diesel Exhaust Fluid Inline Swivels.

Dimensions


Model 007269




Model
007282/010936



Model 007467/008510/008822



Model 007275



Husky Model 6350 Multi-Plane Swivel.

Model 6350



Features

- Multi-Plane, Full 360° spherical rotation for easy movement of nozzle.
- Compatible with unlead, diesel, and all Ethanol blends through E100.
- Compatible with fuels containing alcohol.
- High flow rate due to laminar flow design.
- Compact and light weight for easy handling.
- Double o-ring seals at each swivel provide long life and low temperature (-40° F/C) performance.
- High strength step shoulder bearing diameters and impact absorbing stops.

Construction

Body: Aluminum with Electroless Nickel Plating

Inner O-ring: Fluorosilicone

Outer O-ring: Fluorocarbon


Model No.	Size	Thread	Type	Shipping Wt. Lbs/Kg
6350	3/4" M x 3/4"	NPTF	Multi-Plane Swivel	.44/.19




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Husky Model 6350 Multi-Plane Swivel.

Dimensions



Flow Charts



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





GENERAL FUELING PRODUCTS

Safe-T-Breaks®



All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Models 003360 and 003385

- Retains UL listing after reconnection.
- Features a pre-loaded spring and a single turn wave spring that enables valve to resist sudden pressure build-up in the hose causing nuisance separations.
- Separates using ball bearings and latch ring at less than 200 lbf / 889.6 N which minimizes "backlash" force of separation, reducing damage to equipment.

Model 005230

- Retains UL listing after reconnection.
- Uses the same pre-loaded spring and a single turn wave spring as Model 003360.
- Separates using ball bearings and latch ring at less than 115 lbf / 511.5 N.

Model 002273 & 002774

- Light-weight, inexpensive and disposable.
- Same instant-closing dual poppet check valve design as Model 003360.
- Separates using shear pins at less than 300 lbf / 1334.4 N.

Model 006130

Internal Pressure Compensating Chamber (PCC) that prevents "line shock" nuisance separations.

- Same instant-closing dual poppet check valve as Model 003360.
- Separates using shear pins at less than 225 lbf / 1000.8 N.

Models 015130 & 015349

- Internal Pressure Compensating Chamber (PCC) that prevents "line shock" nuisance separations.

- Same instant-closing dual poppet check valve as Model 002273.
- Features a pre-loaded spring and a single turn wave spring that enables valve to resist fatigue from repeated hose stretching.

- Separates using ball bearings and latch ring at less than 250 lbf / 1,112.1 N.

Reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
003360**	¾" F x ¾" F Reconnectable Safe-T-Break® with scuff guard	0.59 (0.26)
005230**	¾" F x ¾" F Reconnectable Low-Pull Safe-T-Break® with scuff guard	0.59 (0.26)

Non-reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
002273	¾" F x ¾" F Non-Reconnectable Safe-T-Break®	0.78 (0.35)
006130**	¾" F x ¾" F PCC Non-Reconnectable Safe-T-Break® with scuff guard	0.52 (0.23)
015130**	¾" F x ¾" F LH PCC Non-Reconnectable Safe-T-Break® with scuff guard	0.52 (0.23)

Reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
003385**	¾" F x ¾" F Reconnectable Safe-T-Break® with scuff guard	0.57 (0.25)

Non-reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
002774	¾" F x ¾" F Non-Reconnectable Safe-T-Break®	0.73 (0.33)
002774A*	¾" F x ¾" F Non-Reconnectable Safe-T-Break® - Atex	0.73 (0.33)
015349**	¾" F x ¾" F LH PCC Non-Reconnectable Safe-T-Break®	0.52 (0.23)

**See page 2 for guard color options

Construction

RECONNECTABLE SAFE-T-BREAKS®	
Body	Aluminum
Seals	Fluorocarbon
Springs	Stainless Steel
	Stainless steel load and latch spring reverse mechanism
	Hardened stainless steel latch ring and balls
NON-RECONNECTABLE SAFE-T-BREAKS®	
Body	Zinc Alloys and Aluminum


Model 003360



Model 002273



Model 006130



0518
II 1 G
EN 13617-2



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions and System Options

Whip Hoses

MODEL NO.	DESCRIPTION
NPT	
002274	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose
227374	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose connected to Model 002273 ¾" F x ¾" F Non-Reconnectable Safe-T-Break®
336074**	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose connected to Model 003360 ¾" F x ¾" F Reconnectable Safe-T-Break®
002275	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose with Swivel Nut
227375**	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose with Swivel Nut connected to Model 002273 ¾" F x ¾" F Non-Reconnectable Safe-T-Break®
336075**	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose with Swivel Nut connected to Model 003360 ¾" F x ¾" F Reconnectable Safe-T-Break®
BSPP	
002775	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose

Guards

MODEL NO.	DESCRIPTION
003096**	Scuff Guard for Model #003360, 006130 and 005230
006503**	Dispenser Scuff Guard for Model #002273 and 002774
003098	Scuff Guard for Model #015130 & 015349

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007000	Safe-T-Break® Drain Cup
003813	Safe-T-Break® Demonstration Kit

Color Chart


COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

**Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.


Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.


Model 003360



Model 006130



Model 002273




All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

- High impact resistant polymer housing.
- 3/4" or 1" Female NPT inlets.
- Available in 3/4" or 1" Female BSP threads.
- 1" MAGBREAK® has lower back pressure than competing magnetic breakaways. Lower back pressure means higher flow rates.
- 3/4-pound lighter than competing magnetic breakaways.
- Two straight screwdrivers used to separate.
- Easier "separate to inspect" method than competition.
- Assurance of proper reconnection using a simple "twist to lock" feature.
- Absorb line shock in excess of 450 psi at 17 gpm (31 bar at 64.3 Lpm)
- Low scuff housing.
- Line shock absorbing design.
- Stops flow on both sides of break.

New MAGBREAK®


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008330	MAGBREAK® 3/4" F NPT (Separates at less than 200 pounds pull force)	1.21 (.55)
008331	MAGBREAK® 1" F NPT CK (Separates at less than 225 pounds pull force)	1.09 (.50)
010328	MAGBREAK® 3/4" F NPT CK (Separates at less than 225 pounds pull force)	1.21 (.55)

008330 3/4" MagBreak® Reconnectable STB
Back Pressure Performance



▲ Husky® 008330 & 010328
3/4" MAGBREAK®

008331 1" MagBreak® Reconnectable STB
Back Pressure Performance



✕ Husky® 008331
1" MAGBREAK®
with 3/4" Check Valve




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



MAG MAGBREAK®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Models 003360 and 003385

- Retains UL listing after reconnection.
- Features a pre-loaded spring and a single turn wave spring that enables valve to resist sudden pressure build-up in the hose causing nuisance separations.
- Separates at less than 200 lbf / 889.6 N which minimizes "backlash" force of separation, reducing damage to equipment.

Model 005230

- Retains UL listing after reconnection.
- Uses the same pre-loaded spring and a single turn wave spring as Model 003360.

- Separates at less than 115 lbf / 511.5 N.

Model 002273 and 002774

- Light-weight, inexpensive and disposable.
- Same instant-closing dual poppet check valve design as Model 003360.
- Separates at less than 300 lbf / 1334.4 N.

Model 006130

- Internal Pressure Compensating Chamber (PCC) that prevents "line shock" nuisance separations.
- Same instant-closing dual poppet check valve as Model 003360.
- Separates at less than 225 lbf / 1000.8 N.



Model 003600



Model 006130



Model 002273

Reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
003360**	¾" F x ¾" F Reconnectable Safe-T-Break® with scuff guard	0.59 (0.26)
005230**	¾" F x ¾" F Reconnectable Low-Pull Safe-T-Break® with scuff guard	0.59 (0.26)

Non-reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
002273	¾" F x ¾" F Non-Reconnectable Safe-T-Break®	0.78 (0.35)
006130**	¾" F x ¾" F PCC Non-Reconnectable Safe-T-Break® with scuff guard	0.52 (0.23)

Reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
003385**	¾" F x ¾" F Reconnectable Safe-T-Break® with scuff guard	0.57 (0.25)

Non-reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
002774	¾" F x ¾" F Non-Reconnectable Safe-T-Break®	0.73 (0.33)
002774A*	¾" F x ¾" F Non-Reconnectable Safe-T-Break® - Atex	0.73 (0.33)

**See page 2 for guard color options


Construction

RECONNECTABLE SAFE-T-BREAKS®

Body	Aluminum
Seals	Fluorocarbon
Springs	Stainless Steel Stainless steel load and latch spring reverse mechanism Hardened stainless steel latch ring and balls

NON-RECONNECTABLE SAFE-T-BREAKS®

Body	Zinc Alloys and Aluminum
------	--------------------------



0518
II 1 G
EN 13617-2



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions and System Options

Whip Hoses

MODEL NO.	DESCRIPTION
NPT	
002274	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose
227374	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose connected to Model 002273 ¾" F x ¾" F Non-Reconnectable Safe-T-Break®
336074**	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose connected to Model 003360 ¾" F x ¾" F Reconnectable Safe-T-Break®
002275	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose with Swivel Nut
227375**	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose with Swivel Nut connected to Model 002273 ¾" F x ¾" F Non-Reconnectable Safe-T-Break®
336075**	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose with Swivel Nut connected to Model 003360 ¾" F x ¾" F Reconnectable Safe-T-Break®
BSPP	
002775	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose

Guards

MODEL NO.	DESCRIPTION
003096**	Scuff Guard for Model 003360, 006130 and 005230
006503**	Dispenser Scuff Guard for Model 002273 and 002774

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007000	Safe-T-Break® Drain Cup
003813	Safe-T-Break® Demonstration Kit




Color Chart

COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

**Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.

Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

High Volume STB



10-4

SAFE-T-BREAKS®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing

Models 002276, 003076 and 003076A

- Retains UL listing after reconnection.
- Internal pressure balancing chamber prevents "line shock" nuisance separations.
- Separates using ball bearings and latch ring at less than 200 lbf / 889.6 N which minimizes "backlash" force of separation, reducing damage to equipment.

Model 005231

- Retains UL listing after reconnection.
- Uses the same internal pressure balancing chamber as Model 002276.
- Separates using ball bearings and latch ring at less than 115 lbf / 511.5 N.

Model 005812 and 006914

- Light-weight, inexpensive and disposable.
- Same instant-closing dual poppet check valve design as Model 002276.
- Separates using shear pins between 300 lbf / 1334.5 N to 350 lbf / 1556.9 N.

Model 006301

- Internal Pressure Compensating Chamber (PCC) that prevents "line shock" nuisance separations.
- Same instant-closing dual poppet check valve as Model 002276.
- Separates using shear pins at less than 225 lbf / 1000.8 N.

Models 015176 & 015254

- Internal Pressure Compensating Chamber (PCC) that prevents "line shock" nuisance separations.
- Same instant-closing dual poppet check valve as Model 002276.
- Features a pre-loaded spring and a single turn wave spring that enables valve to resist fatigue from repeated hose stretching.
- Separates using ball bearings and latch ring at less than 250 lbf / 1,112.1 N.

Reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
002276**	1" F x 1" F Reconnectable Safe-T-Break®	.75 (.34)
005231**	1" F x 1" F Reconnectable Low-Pull Safe-T-Break®	.75 (.34)

Non-reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
005812**	1" F x 1" F Non-Reconnectable Safe-T-Break®	.61 (.27)
006301**	1" F x 1" F PCC Non-Reconnectable Safe-T-Break®	.69 (.31)
015176**	1" F x 1" F Super STB 1" Non-Reconnectable	.75 (.34)

Reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
003076**	1" F x 1" F Reconnectable Safe-T-Break®	.75 (.34)
003076A*	1" F x 1" F Reconnectable Safe-T-Break® - Atex	.75 (.34)

Non-reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006914**	1" F x 1" F Non-Reconnectable Safe-T-Break®	.61 (.27)
015245**	1" F x 1" F Super STB 1" Non-Reconnectable	.75 (.34)

**See page 2 for guard color options

Construction

Reconnectable Safe-T-Breaks®

Body	Aluminum
Seals	Fluorocarbon
Springs	Stainless Steel

Stainless steel load and latch spring reverse mechanism

Hardened stainless steel latch ring and balls


Non-Reconnectable Safe-T-Breaks®

Body	Zinc Alloys and Aluminum
Seals	Fluorocarbon

Model 002276



Model 005812



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



High Volume STB

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions and System Options

Whip Hoses

MODEL NO.	DESCRIPTION
002277	1" M x 1" M (25 mm M x 25 mm M) Whip Hose
227677**	1" M x 1" M Whip Hose connected to Model 002276 1" F x 1" F Reconnectable Safe-T-Break®
581277**	1" M x 1" M Whip Hose connected to Model 005812 1" F x 1" F Non-Reconnectable Safe-T-Break®
002278	1" M x 1" M (25 mm M x 25 mm M) Whip Hose with Swivel Nut

Guards

MODEL NO.	DESCRIPTION
003098**	Safe-T-Break® Scuff Guard

Accessories, Maintenance, and Testing

Model No.	Description
007000	Safe-T-Break® Drain Cup
003813	Safe-T-Break® Demonstration Kit



Color Chart

COLOR SUFFIX	SUFFIX	COLOR	
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

**Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.

Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Stop the flow of fluid on both sides of the separation.

Model 007219

- Non-reconnectable Safe-T-Break®.
- Low profile design.
- Thread sealant not required with BSPP threads.
- 100% DEF compatible parts.
- Instant-closing, dual poppet check valve design.
- Maximum separation of 300 lbf / 1334.5 N.
- Comes standard with guard.

- Thread sealant not required with BSPP threads.
- Instant-closing, dual poppet check valve design.
- Comes standard with guard.

Model 012070

- Reconnectable Safe-T-Break®.
- Maximum separation of 200 lbf / 889.6 N.
- 100% DEF compatible parts.
- Instant-closing, dual poppet check valve design.
- Comes standard with guard.
- DEF compatible thread sealant required for 3/4" NPT threads.

Model 008216

- Reconnectable Safe-T-Break®.
- Maximum separation of 200 lbf / 889.6 N.
- 100% DEF compatible parts.


Safe-T-Breaks®

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007219	1" M x 1" M Stainless Steel Non-Reconnectable Safe-T-Break®	0.90 (.40)
008216	1" M x 1" M Stainless Steel Reconnectable Safe-T-Break®	0.94 (.43)
012070^	3/4" F x 3/4" F NPT Reconnectable Safe-T-Break®	0.54 (.20)
012659^	3/4" F x 3/4" F BSPP Reconnectable Safe-T-Break®	.54 (.20)

^ NOT LISTED

Construction

Body	Stainless Steel, 012070 - Anodized Aluminum
Seals	Fluorocarbon
Inlet	1" / 25.4 mm BSPP, 012070 - 3/4" / 19.1 mm NPT



Model 008216



Model 012070/012659



Model 007219



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Stop the flow of fluid on both sides of the separation.

Dimensions and System Options


Guards

MODEL NO.	DESCRIPTION
007224	Black Scuff Guard
006534	Dispenser Scuff Guard
003097	Scuff Guard

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007407	1" BSPP Seal Kit Assembly


Model 007219



Model 012070/012659



Model 008216



High Volume STB



10-6

SAFE-T-BREAKS®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Models 002276, 003076 and 003076A

- Retains UL listing after reconnection.
- Internal pressure balancing chamber prevents "line shock" nuisance separations.
- Separates at less than 200 lbf / 889.6 N which minimizes "backlash" force of separation, reducing damage to equipment.

Model 005231

- Retains UL listing after reconnection.

- Uses the same internal pressure balancing chamber as Model 002276.

- Separates at less than 115 lbf / 511.5 N.

Model 005812 and 006914

- Light-weight, inexpensive and disposable.

- Same instant-closing dual poppet check valve design as Model 002276.

- Separates at less than 300 lbf / 1334.4 N.

Model 006301

- Internal Pressure Compensating Chamber (PCC) that prevents "line shock" nuisance separations.

- Same instant-closing dual poppet check valve as Model 002276.

- Separates at less than 225 lbf / 1000.8 N.



Model 002276



Model 005812

Reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
002276**	1" F x 1" F Reconnectable Safe-T-Break®	.75 (.34)
005231**	1" F x 1" F Reconnectable Low-Pull Safe-T-Break®	.75 (.34)

Non-reconnectable with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
005812**	1" F x 1" F Non-Reconnectable Safe-T-Break®	.61 (.27)
006301**	1" F x 1" F PCC Non-Reconnectable Safe-T-Break®	.69 (.31)

Reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
003076**	1" F x 1" F Reconnectable Safe-T-Break®	.75 (.34)
003076A*	1" F x 1" F Reconnectable Safe-T-Break® - Atex	.75 (.34)

Non-reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006914**	1" F x 1" F Non-Reconnectable Safe-T-Break®	.61 (.27)

**See page 2 for guard color options

Construction

Reconnectable Safe-T-Breaks®


Body	Aluminum
Seals	Fluorocarbon
Springs	Stainless Steel

Stainless steel load and latch spring reverse mechanism

Hardened stainless steel latch ring and balls

Non-Reconnectable Safe-T-Breaks®

Body	Zinc Alloys and Aluminum
Seals	Fluorocarbon



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



High Volume **STB**

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions and System Options

Whip Hoses

MODEL NO.	DESCRIPTION
002277	1" M x 1" M (25 mm M x 25 mm M) Whip Hose
227677**	1" M x 1" M Whip Hose connected to Model 002276 1" F x 1" F Reconnectable Safe-T-Break®
581277**	1" M x 1" M Whip Hose connected to Model 005812 1" F x 1" F Non-Reconnectable Safe-T-Break®
002278	1" M x 1" M (25 mm M x 25 mm M) Whip Hose with Swivel Nut

Guards

MODEL NO.	DESCRIPTION
003098**	Safe-T-Break® Scuff Guard

Accessories, Maintenance, and Testing

MODEL NO.	DESCRIPTION
007000	Safe-T-Break® Drain Cup
003813	Safe-T-Break® Demonstration Kit


Color Chart

COLOR SUFFIX	SUFFIX	COLOR	
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

**Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.

Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Balance Vapor STB



10-7

SAFE-T-BREAKS®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Model 3360VR

- Reconnectable Safe-T-Break® for balance vapor recovery systems - coaxial hoses with fuel on the "inside", vapor return on the "outside".
- Unique in-line latching mechanism requires less force to reconnect Safe-T-Break® after a separation.
- Unique vapor valve stops vapors from escaping after a drive away.
- Separates at less than 200 lbf / 889.6 N to minimize backlash damage.
- Patented wave spring design minimizes nuisance breaks.

Model 005900

- Non-reconnectable Safe-T-Break® for balance vapor recovery systems - coaxial hoses with fuel on the "inside", vapor return on the "outside".
- Internal pressure compensating chamber isolates shear pin from line shock preventing nuisance breaks.
- Separates at less than 250 lbf / 1112.1 N to minimize backlash damage.
- Same built-in vapor valve as Model 3360VR.

Reconnectable

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3360VR**	Reconnectable Safe-T-Break®	1.3 (.5)

Non-reconnectable

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
005900**	Non-Reconnectable Safe-T-Break®	1.2 (.5)

**See page 2 for guard color options

Construction


Body	Aluminum
Seals	Fluorocarbon
Springs	Stainless Steel
Threads	1 1/8" x 12
Stainless steel load and latch spring reverse mechanism Hardened stainless steel latch ring and balls	



Model 3360VR



Model 005900



AIR RESOURCES BOARD



Texas Commission on Environmental Quality



Missouri Department of Natural Resources



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions and System Options

Whip Hoses

MODEL NO.	DESCRIPTION
002715	10" / 254 mm Coaxial Whip Hose
3360VR**-333	Reconnectable Safe-T-Break® connected to Model 002715 Coaxial Whip Hose

Guards

MODEL NO.	DESCRIPTION
003990**	Scuff Guard for 3360VR Safe-T-Break®
005895**	Scuff Guard for 005900 Safe-T-Break®

Accessories, Maintenance, and Testing

MODEL NO.	DESCRIPTION
007000	Safe-T-Break® Drain Cup

Color Chart


COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

**Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.


Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.

Model 3360VR



Model 005900



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Model 004034

- Reconnectable Safe-T-Break® for the vapor assist systems: coaxial hoses with fuel "outside" hose, vapor return "inside" hose.
- Meets the reconnect endurance test of the UL Standard 567 Ninth Edition.
- Unique vapor valve stops vapors from escaping after a drive away.
- Separates at less than 200 lbf / 889.6 N to minimize backlash damage.
- Unique pre-loaded shock absorbing wave spring minimizes nuisance breaks.

Model 006560

- Reconnectable Safe-T-Break® designed for the Veeder-Root® 900301 and VST Enviro-Loc® primary hose with ORVR valve.
- Same style and design as Model 004034 including the same fuel / vapor paths and separation force.

Model 005134

- Non-reconnectable Safe-T-Breaks® in the same style and design as Model 004034, including the same fuel / vapor paths and separation force.

Models 004034A/005134A

- Separates between 180-337 lbf / 800-1500 N.

Reconnectable

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
004034**	Reconnectable Safe-T-Break®	1.0 (.45)
004034A*	Reconnectable Safe-T-Break® - Atex	1.0 (.45)
006560**	Reconnectable Safe-T-Break® for ORVR	1.0 (.45)

Non-reconnectable

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
005134**	Non-reconnectable Safe-T-Break®	1.0 (.45)
005134A*	Non-reconnectable Safe-T-Break® - Atex	1.0 (.45)

**See page 2 for guard color options

Construction



Body	Aluminum
Seals	Fluorocarbon
Springs	Fiber Reinforced Teflon®
Threads	004034, 004034A, 005134 and 005134A = M34 x 1.5 006560 = 1 1/4" - 18
	Stainless steel load and latch spring reverse mechanism Hardened stainless steel latch ring and balls



Model 004034



Model 005134



II 1 G
EN13617
Type 2



CALIFORNIA ENVIRONMENTAL PROTECTION AGENCY
AIR RESOURCES BOARD



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Vacuum Assist **STB**

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions and System Options

Guards

Model No.	Description
003098**	Scuff Guard for 004034, 004034A, 005134, 005134A and 006560 Safe-T-Breaks®

Color Chart


COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

**Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.


Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.

Model 004034 & 006560



Model 005134



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



E85 Safe-T-Breaks®



10-9

SAFE-T-BREAKS®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation.

- Compatible with unleaded, diesel and all Ethanol blends through E85.
- Unit is lightweight, inexpensive and disposable.
- Features same instant closing dual poppet check valve design as Model 006360.
- Maximum separation of 300 lbf / 1334.5 N.



Model 006273


E85 Safe-T-Breaks®

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006273	¾" F x ¾" F Standard Non-Reconnectable Safe-T-Break®	.30 (.13)

Construction

Body	Aluminum with Electroless Nickel Plating
Seals	Fluorocarbon
Springs	Stainless Steel
Threads	¾" / 19.1 mm NPT

006273



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



E85 Safe-T-Breaks®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation.

Dimensions and System Options


Whip Hoses

MODEL NO.	DESCRIPTION
002274	¾" / 19.1 mm M x ¾" / 19.1 mm M Standard Whip Hose
002275	¾" / 19.1 mm M x ¾" / 19.1 mm M Standard Whip Hose with Swivel Nut

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007000	Safe-T-Break® Drain Cup
003813	Safe-T-Break® Demonstration Kit

Model 006273



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.



- High impact resistant polymer housing.
- Two straight screwdrivers used to separate.
- Easier "separate to inspect" method than competition.
- Assurance of proper reconnection using a simple "twist of lock" feature.
- Low scuff housing.
- Stops flow on both sides of break.
- Reconnectable Safe-T-Break® for the vapor assist systems: coaxial hoses with fuel "outside" hose, vapor return "inside" hose.
- Unique vapor valve stops vapors from escaping after a drive away.
- Separates at less than 225 lbs / 1000.9 N to minimize backlash damage.

New Vac Assist MAGBREAK®

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008332	MAGBREAK® Coax M34 CK	1.36 (.62)

Construction

Body	Aluminum
Seals	Fluorocarbon
Springs	Fiber Reinforced Teflon®
Threads	8332 = M34 x 1.5




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

E25 Safe-T-Breaks®



10-11

SAFE-T-BREAKS®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation.

- Compatible with unleaded, diesel and all Ethanol blends through E25.
- Retains the UL listing after being reconnected.
- Unusual interface between a pre-loaded spring and a single turn wave spring that enables valve to resist sudden pressure build-up in the hose resulting in nuisance separations.
- Unit separates at less than 200 lbf / 889.6 N which minimizes "backlash" force of separation, reducing damage to equipment.




E25 Safe-T-Breaks®

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006360	¾" F x ¾" F Reconnectable Safe-T-Break®	.58 (.26)

Construction

Body	Aluminum with Electroless Nickel Plating
Seals	Fluorocarbon
Springs	Stainless Steel
Threads	¾" / 19.1 mm NPT
	Stainless steel load and latch spring reverse mechanism
	Hardened stainless steel latch ring and ball



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



E25 Safe-T-Breaks®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation.

Dimensions and System Options

Guards

MODEL NO.	DESCRIPTION
003097	Black Scuff Guard


Whip Hoses

MODEL NO.	DESCRIPTION
002274	¾" / 19.1 mm M x ¾" / 19.1 mm M Standard Whip Hose
002275	¾" / 19.1 mm M x ¾" / 19.1 mm M Standard Whip Hose with Swivel Nut

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007000	Safe-T-Break® Drain Cup
003813	Safe-T-Break® Demonstration Kit

Model 006360



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Inline SAFE-T-BREAK®.


- Threads directly into nozzle inlet.
- Separates at 180-337 lbs (800-1500N).
- Reconnectable.
- Stops flow on hose side of break.
- Separates at angles up to 90 degrees.
- Aluminum internal flow director - stronger than Elaflex plastic design.
- Check valve o-ring to ensure reliable fuel shut-off, not included on Elaflex.

New Inline SAFE-T-BREAK®

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008521A	Inline Safe-T-Break®	.45 (.20)

Construction

Body	Aluminum
Seals	Fluorocarbon
Threads	M34 x 1.5




II 1 G
EN13617
Type 2



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Inline SAFE-T-BREAK®.

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.




All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

- High impact resistant polymer housing.
- Compatible with unleaded, diesel, and all Ethanol blends through E85
- Features same separation mechanism as Model 008330
- ³/₄-pound lighter than competing magnetic breakaways.
- Two straight screwdrivers used to separate.
- Easier "separate to inspect" method than competition.
- Assurance of proper reconnection using a simple "twist to lock" feature.
- Absorb line shock in excess of 450 psi at 17 gpm (31 bar at 64.3 Lpm)
- Low scuff housing.
- Line shock absorbing design.
- Stops flow on both sides of break.

New MAGBREAK®

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
014647	MAGBREAK® 3/4" F x 3/4" F E25/85 NPT (Separates at less than 200 pounds pull force)	1.21 (.55)




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



E25/E85 MAGBREAK®

All Husky® Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Swivel/Safe-T-Break® Combos

Husky Model 006310 Swivel Safe-T-Break® combination for standard fueling applications.


- Multi-plane, full 360° spherical rotation for easy movement of nozzle.
- Swivel Sync® feature to prevent separation failure in the 90° position.
- Safe-T-Break® is reconnectable and retains UL listing after reconnecting.
- Dual check valves stops fuel in both directions.
- Separates at less than 325 lbf / 1,445.6 N which minimizes backlash force of separations, reducing damage to equipment.
- Wave spring helps reduce nuisance breaks due to water hammer.
- Dynamic seals have double o-ring construction for long life and low temperature performance.
- Compatible with Ethanol blends though E10.
- Compact and light weight for easy handling.
- Easier to reconnect when installed at the nozzle.
- Eliminates the need for a whip hose.

Swivel/Safe-T-Break® Combination

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006310	¾" NPT M x ¾" NPT F Multi-Plane Swivel Reconnectable Safe-T-Break®	.90 (.40)
007085	¾" BSP M x ¾" BSP F Multi-Plane Swivel Reconnectable Safe-t-Break®	.90 (.40)
007085A*	¾" BSP M x ¾" BSP F Multi-Plane Swivel Reconnectable Safe-t-Break® - Atex	.90 (.40)
010959	M34 M x ¾" BSP F Multi-Plane Swivel Reconnectable Safe-T-Break®	.90 (.40)

Construction

Body	Aluminum, Zinc Alloy
Seals	Fluorosilicone, Fluorocarbon
Springs	Stainless Steel
Threads	Various



II 2 G
 EN 13617-2 TYPE 1
 EN 13617-4 STYLE 1



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

**Husky**

GENERAL FUELING PRODUCTS


Swivel/STB Standard

Husky Model 006310 Swivel Safe-T-Break® Combination for standard fueling applications.

Dimensions

Guards

MODEL NO.	DESCRIPTION
006534	Scuff Guard for Safe-T-Break®



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Husky® Model 005969 Swivel Safe-T-Break® Combination for truck and high volume fueling.


- Multi-plane, full 360° spherical rotation for easy movement of nozzle.
- Swivel Sync® feature to prevent separation failure in the 90° position.
- High strength step shoulder bearing diameters and impact absorbing stops.
- Dynamic seals have double o-ring construction for long life and low temperature performance.
- Separates at less than 325 lbf / 1,445.6 N which minimizes backlash force of separations, reducing damage to equipment.
- Safe-T-Break® is reconnectable and retains UL listing after reconnecting.
- Dual check valves stop fuel in both directions.
- Internal pressure balancing chamber prevents "line shock" nuisance separations.
- Compatible with Ethanol blends through E10.
- Compact and light weight for easy handling.
- Easier to reconnect when installed at the nozzle.
- Eliminates the need for a whip hose

Swivel/Safe-T-Break® Combination

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
005969	1" NPT M x 1" NPT F Multi-Plane Swivel Reconnectable Safe-T-Break®	1.5 (0.7)
008015	1" BSP M x 1" BSP F Multi-Plane Swivel Reconnectable Safe-T-Break®	1.5 (0.7)
008015A*	1" BSP M x 1" BSP F Multi-Plane Swivel Reconnectable Safe-T-Break® - Atex	1.5 (0.7)
008612	M42 M x 1" BSP F Multi-Plane Swivel Reconnectable Safe-T-Break®	1.5 (0.7)
008614	M34 M x 1" BSP F Multi-Plane Swivel Reconnectable Safe-T-Break®	1.5 (0.7)
008985	1" BSP M x 1" BSP M Multi-Plane Swivel Reconnectable Safe-T-Break®	1.5 (0.7)
008985A*	1" BSP M x 1" BSP M Multi-Plane Swivel Reconnectable Safe-T-Break® - Atex	1.5 (0.7)

Construction

Body	Aluminum, Zinc Alloy
Seals	Fluorocarbon
Springs	Stainless Steel
Threads	Various



II 2 G
EN 13617-2 TYPE 1
EN 13617-4 STYLE 1



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

Swivel/STB High Volume

Husky® Model 005969 Swivel Safe-T-Break® Combination for truck and high volume fueling.


Dimensions and System Options

Guards

MODEL NO.	DESCRIPTION
006534	Scuff Guard for Safe-T-Break®

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007000	Safe-T-Break® Drain Cup



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Swivel/STB Inline Combo



11-3

SWIVEL/SAFE-T-BREAKS®

Inline COMBO.



Features



- Single Plane 360° Rotation
- Unique to Husky® products, the steel ball bearing design provides easier joint movement during high pressure applications.
- Safe-T-Break® is service reconnectable
- Check valve to stop flow of fuel on hose side
- Check valve O-ring to ensure reliable fuel shut-off
- Separates between 180 lbs. and 337 lbs.
- Separates at angles up to 90°
- Compact and easy to handle
- Fuel/Diesel or DEF versions available

Construction

Body: Anodized aluminum
Seals: Fluorocarbon
Nuts: Stainless steel, electroless nickel-plated steel

Inline Combo

MODEL NO.	Scuff Guard	Fuel/ DEF	Swivel	Swivel Thread	STB Thread	ATEX	Shipping Weight
012828	X	DEF	360°	3/4" SP M	3/4" BSP F	—	.90lbs/.40KG
012831	X	DEF	360°	3/4" NPT M	3/4" NPT F	—	.90lbs/.40KG
012887	X	DEF	360°	3/4" BSP M	1" BSP F	—	.90lbs/.40KG
012890	X	DEF	360°	3/4" BSP M	1" BSP M	—	.80lbs/.36KG
013185	X	DEF	360°	M34 M	1" BSP M	—	.80lbs/.36KG
014438	X	DEF	360°	1" BSP M	1" BSP M	—	.90lbs/.40KG
013530A*	X	FUEL	360°	1" BSP M	1" BSP M	X	.90lbs/.40KG
013530	X	FUEL	360°	1" BSP M	1" BSP M	—	.90lbs/.40KG
013827A*	X	FUEL	360°	3/4" BSP M	3/4" BSP M	X	.80lbs/.36KG



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Swivel/STB Inline Combo

Inline COMBO

Dimensions and System Options

Guards

MODEL NO.	DESCRIPTION
0008526	Scuff Guard for Safe-T-Break®



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Guards



HUSKY® Guards



12-1

GUARDS

For nozzles and Safe-T-Breaks®



Nozzle Guards

- Nozzle Guards, Nozzle Reguards, Waffle Splash Guards and Safe-T-Break® Guards are to be ordered with the corresponding color option added to the model number.
- Custom colors are available for all Nozzle Guards, Nozzle Reguards, Waffle Splash Guards and Safe-T-Break® Guards.
- The Safety / Warning logo will be printed on all Nozzle Guards and Nozzle Reguards.
- The E85 logo is available on all Nozzle Guards, Nozzle Reguards and Safe-T-Break® Guards upon request.
- A customized logo can be printed on any Nozzle Guard or Nozzle Reguard upon request

Safe-T-Break® Guards

- Protects dispenser from damage caused by the Safe-T-Break® and whip hose.
- Protects the Safe-T-Break® against corrosion due to environmental exposure.
- Enhanced protection of the Safe-T-Break® during separations.
- Provides a clean / more streamline appearance.
- Available in multiple colors to coordinate with the nozzle guards.
- Available with E85 logo.

Easy-On Guard Package

MODEL NO.	DESCRIPTION
003440	X, XS®, XFS Nozzles (includes 003795 Mate Nozzle Guard and 012117 Fluted Handle Cover)
011597	V34 International Nozzles (includes 014526 Mate Nozzle Guard and 010089 Handle Cover)
014524	X, XS®, XFS International Nozzles (includes 014530 Mate Nozzle Guard and 007361 Handle Cover)

Full Grip Nozzle Guards

MODEL NO.	DESCRIPTION
000554	1A, 1GS, 1HS Nozzles
004145	X, XS®, XFS Nozzles
004740	VIII, VIIS Nozzles
005170	V3 Nozzles
006483	Safe-T-Squeeze® Nozzles
006951	V34 Nozzles

Full Grip Nozzle Reguards (includes zip tie)

MODEL NO.	DESCRIPTION
001804	1A, 1GS, 1HS Nozzles
001806	X, XS®, XFS Nozzles
005516	VIII, VIIS Nozzles
004231	V34 Nozzles
005169	V3 Nozzles

Nozzle Guard Packages

MODEL NO.	DESCRIPTION
000099	1A, 1HS Nozzle Protection Package (includes 000554 Full Grip Nozzle Guard and 001808 Waffle Splash Guard)
001506	X, XS® Nozzle Protection Package (includes 004145 Full Grip Nozzle Guard and 001808 Waffle Splash Guard)
001809	X, XS® Nozzle Reguard Package (includes 001806 Full Grip Reguard, Zip Tie and 001808 Waffle Splash Guard)
001811	1A, 1HS Nozzle Reguard Package (includes 001804 Full Grip Reguard, Zip Tie and 001808 Waffle Splash Guard)

Waffle Splash Guards

MODEL NO.	DESCRIPTION
001807	Waffle Splash Guard (small hole)
001808	X, XS®, 1A, 1HS, VIII, VIIS Nozzles
006955	V3 Nozzles

Safe-T-Break® Guards

MODEL NO.	DESCRIPTION
003096	003360, 006130, and 005230 Safe-T-Breaks®
003098	002276, 004034, 005134, 006210, 006301, and 006560 Safe-T-Breaks®
003990	003360VR Safe-T-Break®
006534	006310 Swivel Safe-T-Break® Combo
006503	2 piece Safe-T-Break® Dispenser Guard

Mate Nozzle Guards

MODEL NO.	DESCRIPTION
000226	1A, 1GS, 1HS, DEF Nozzles
003795	X, XS®, XFS Nozzles
007295	1A, 1GS, 1HS, DEF Handle Cover
007361	X, XS®, XFS, DEF X, PHG Handle Cover
010089	V34, PHG Handle Cover
012117	X, XS®, XFS Fluted Handle Cover
014526	V34 International Nozzles
014530	X, XS®, XFS International Nozzles
015257	1A, 1GS, 1HS, DEF International Nozzles



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



HUSKY® Guards

For nozzles and Safe-T-Breaks®



Color Chart

COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

*Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.

Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



POPD Guards



12-2

GUARDS

Point of purchase display nozzle guards.

- Allows additional advertising at the point of fuel purchases.
- Unique angled design for easy readability both hanging in dispenser and while fueling.
- Guards come standard with clear cover to protect the advertisement.
- Clear cover contains UV stabilizer for durability and to prevent discoloring.
- Built-in to the nozzle guard for easy installation.



Full Grip Nozzle Guards

MODEL NO.	DESCRIPTION
006665	X, XS®, XFS Nozzles
006655	1A, 1HS, 1GS Nozzles
007352	VIII, VIIS Nozzles
006660	V34 Nozzles
007175	11A Nozzles
007180	11B Nozzles
008183	1A, 1GS, 1HS, Nozzles
008184	V34 Nozzle
008185	X, XS®, XFS Nozzles
008186	VIII, VIIS, Nozzles
008187	11A Nozzles
008188	11B Nozzles

Full Grip Nozzle Reguards

MODEL NO.	DESCRIPTION
007205	X, XS®, XFS Nozzles
007210	1A, 1HS, 1GS Nozzles
007220	V34 Nozzles
007225	11A Nozzles
007230	11B Nozzles
008194	VIII, VIIS Nozzles
008190	1A, 1GS, 1HS Nozzles
008191	V34 Nozzle
008192	X, XS®, XFS Nozzles
008193	VIII, VIIS Nozzles
008195	11A Nozzles
008196	11B Nozzles

Clear Cover

MODEL NO.	DESCRIPTION
006628	POPD S Clear Cover
008181	POPD H Clear Cover

EZ Guards

MODEL NO.	DESCRIPTION
008179	1A, 1GS, 1HS Nozzles
008175	X, XS®, XFS Nozzles
008177	VIII, VIIS Nozzles
007990	11A Nozzles
007992	11B Nozzles
008180	1A, 1GS, 1 HS Nozzles
008176	X, XS®, XFS Nozzles
008178	VIII, VIIS Nozzles
007991	11A Nozzles
007993	11B Nozzles



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



POPD Guards

Point of purchase display nozzle guards.

System Options

Mate Nozzle Guards

MODEL NO.	DESCRIPTION
008169	1A, 1GS, 1HS Nozzles
008165	X, XS®, XFS Nozzles
008167	VIII, VIIIS Nozzles
008171	11A Nozzles
008173	11B Nozzles
008170	1A, 1GS, 1HS Nozzles
008166	X, XS®, XFS Nozzles
008168	VIII, VIIIS Nozzles
008172	11A Nozzles
008174	11B Nozzles
015247	X,XS International Polymer Handguard Nozzles
015253	X,XS International Polymer Handguard Nozzles without Clear Cover

Black Handle Cover

MODEL NO.	DESCRIPTION
007361	X,XS,XFS Polymer Handguard Nozzles
007376	1A, 1HS, 1GS and DEF Nozzles
012117	X,XS,XFS Metal Handguard Nozzles

Waffle Splash Guard

MODEL NO.	DESCRIPTION
001808	X, XS®, 1A, 1HS, VIII, VIIIS Nozzles
001807	11A, 11B Nozzles

Color Chart

COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

*Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.

Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Spouts

1GS Spouts



13-3

SPOUT ASSEMBLIES

Spout assemblies.

- Stainless Steel Spout Bushing (optional on LDD).
- *Streamshaper*®.
- Keeps spout tip round.
- Reduces turbulence for straighter fuel flow and less splashback spillage.



Unlead Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
001473	X, XS®, 1A, 1GS Spout Assembly with Streamshaper®	.3 (.14)
003356	XFS Spout Assy with Hanging Hook and Streamshaper®	.5 (.23)
008684	X, XS®, 1A, 1GS MTBE Spout Assembly with Streamshaper®	.3 (.14)
010432	X, XS®, 1A, 1GS Long Spout Assembly with Streamshaper®	.4 (.18)
014376	X, XS®, 1A, 1GS Spout Assembly without Spout Spring, with Streamshaper®	.4 (.18)
014420	X, XS®, 1A, 1GS Spout Assembly with Streamshaper® and Spout Ring	.4 (.18)

Light Duty Diesel Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
001471	X, XS®, 1A, 1GS Spout Assembly with Streamshaper®	.4 (.18)
003358	XFS Spout Assembly with Hanging Hook	.6 (.27)
014378	X, XS®, 1A, 1GS Spout Assembly without Spout Spring, with Streamshaper®	.4 (.18)
014421	X, XS®, 1A, 1GS Spout Assembly with Streamshaper® and Spout Ring	.4 (.18)

High Flow/High Volume Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
005215	1HS, 1GS Spout Assembly	.4 (.18)




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Spout assemblies.

Dimensions

Unlead Spouts



Light Duty Diesel Spout



High Flow/High Volume Spout



Spout assemblies.

- Spout assemblies with the *Streamshaper*® reduces turbulence for straighter DEF flow and less splash back spillage.
- Spout assemblies with the Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Spout assemblies with the Accufuel® safety feature prevents misfilling of DEF in the diesel tank.

Stainless Steel DEF Nozzle Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007360	with Spout Ring and Flo-Stop®	.4 (.18)
007362	with Flo-Stop®	.4 (.18)
007364	with Spout Ring and Magnetic Accufuel® Safety Feature	.4 (.18)

X DEF Nozzle Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
013285	with StreamShaper®	.4 (.18)
013286	with Spout Ring and Magnetic Accufuel® Safety Feature	.4 (.18)

Polymer DEF Nozzle Spout Assemblies




MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
013591	with StreamShaper®	.4 (.18)
013592	with Spout Ring and StreamShaper®	.4 (.18)
013593	with Spout Ring and Magnetic Accufuel® Safety Feature	.4 (.18)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Spout Assemblies.

Dimensions



VIII, VIIS Spouts



Spout assemblies.

- Aluminum Spout Bushing.
- Flow stop device.
- Reduces rounding in of spout.
- Retains spout spring.
- Shuts off flow when spout is raised above horizontal.

High Flow/High Volume Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
002279	VIII, VIIS Spout Assembly with Spout Bushing	.9 (.41)
003589	VIII, VIIS Long Spout Assembly without Spout Bushing	1.0 (.45)
004889	1690 High-Volume Spout Assembly without Shear Groove (USA)	.5 (.23)
005017	VIII, VIIS Spout Assembly without Spout Bushing	.9 (.41)
005042	1691 High-Volume Spout Assembly with Shear Groove (Canada)	.5 (.23)
005215	1HS, 1GS Spout Assembly	.4 (.18)
007218	VIII, VIIS Long Spout Assembly with Spout Bushing	1.0 (.45)





WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Spout assemblies.

Dimensions

High Flow/High Volume Spouts



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



V3 & V34 Spouts



13-6

SPOUT ASSEMBLIES

Spout assemblies.

- Stainless steel spout bushing.
- *Streamshaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Keeps spout tip round.



V3 Spout Kit

Vacuum Assist Vapor Recovery Unlead Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
004000	V34 Vapor Splash Guard (VSG) (Includes 004039 Clamp)	.1 (.05)
004039	VSG Single Use Clamp	.1 (.05)
006289	V3 Spout Assy Kit (Includes 006389 Spout Assembly and 006955 Waffle Splash Guard)	.3 (.14)
006291	V34 Spout Assy Kit (Includes 004000 VSG and 006391 Spout Assembly)	.3 (.14)
006389	V3 Spout Assembly (without Waffle Splash Guard)	.2 (.09)
006391	V34 Spout Assembly with Streamshaper®	.3 (.14)
006656	V34-006536 VSG (Includes 004039 Clamp)	.1 (.05)
006663	V34-006536 Spout Assembly Kit (Includes 006391 Spout Assembly and 006656 VSG)	.3 (.14)
008411	V34i Spout Assembly Kit with Streamshaper® (Includes 003877 O-Ring and 006511 Set Screw)	.2 (.09)
008642	V34-006200 Coaxial Spout Assembly Kit (Includes 009968 Spout Assembly and 004000 VSG)	.3 (.14)
009968	V34-006200 Coaxial Spout Assembly	.2 (.09)

Vacuum Assist Vapor Recovery Light Duty Diesel Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006261	V34C Spout Assembly Kit (Includes 004000 Vsg)	.4 (.18)
006361	V34 Spout Assembly Kit (Includes 004039 Clamp)	.3 (.14)



V34 Spout Kit



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



V3 & V34 Spouts

Spout assemblies.

Dimensions

Vacuum Assist Vapor Recovery



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Spout assemblies.


- Nickel plated aluminum spout.
- *Streamshaper*®
- Stainless Steel Spout Bushing.
- E85 compatible.
- Keeps spout tip round.
- Reduces turbulence for straighter fuel flow and less splashback spillage.

Ethanol Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006207	X, XS® E85 Spout Assembly with Streamshaper®	.4 (.18)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Spout Assemblies.**Dimensions**

2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Pressure/Vacuum Vents



Model 008060 has three (3) separate valves that address pressure/vacuum conditions in underground storage tanks (UST) and above ground storage tanks (AST).

- Husky pressure / vacuum (P/V) vents incorporate three (3) separate valves to control over-pressure and vacuum conditions that arise in storage tanks. The three (3) valve system provides the necessary protection and durability needed in UST and AST vent caps.
- The vacuum valve is diaphragm operated and provides ten (10) times more sealing force than gravity devices. It constantly opens at 6" - 8" of water column (WC) / 2 - 2.5 KPa vacuum.
- The first over-pressure valve is diaphragm operated, giving ten (10) times more sealing force than gravity devices. It opens at 8" - 12" WC / .75 - 1.5 KPa pressure.
- The safety over-pressure valve is designed to handle high pressure / high flow conditions. This valve will vent up to 7900 SCFH at 2 psi / .14 bar.
- Threaded vent cap that is easily installed by using the cast-on hex nut which allows tightening without having to go between vent pipes.
- Not for use in California / EVR applications.
- Constructed from materials 100% compatible with B0-B20 and E0-E85.

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008060	2" / 51 mm Thread-On Pressure / Vacuum Vent Cap	1.2 (.54)

Construction

Body	Aluminum
Screen	40 Mesh Stainless Steel
Set Screws	Stainless Steel
Deflector	Aluminum



This component was tested to and met the following criteria:

PRES. 8-12 IN. W.C.

VAC. 6-8 IN. W.C.

.05 CFH @ +2 IN. W.C.

.21 CFH @ -4 IN. W.C.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

All Pressure/Vacuum Vents have three (3) separate valves that address pressure/vacuum conditions in underground storage tanks (UST) and above ground storage tanks (AST).


Dimensions and System Options

Adapter

MODEL NO.	DESCRIPTION
005041	3 in / 76 mm Thread to 2 in / 51 mm Thread Pipe Adapter

Testing Equipment

MODEL NO.	DESCRIPTION
005426	Pressure / Vacuum Vent Test Adapter



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

All Pressure/Vacuum Vents have three (3) separate valves that address pressure/vacuum conditions in underground storage tanks (UST) and above ground storage tanks (AST).

Model 004620 and 004885

- The three (3) valve system provides the necessary protection and durability needed in UST and AST vent caps.
- The vacuum valve is diaphragm operated and provides ten (10) times more sealing force than gravity devices. It consistently opens at 6" - 10" of water column (WC) / 1.5 - 2.5 KPa vacuum.
- The first over-pressure valve is diaphragm operated, giving ten (10) times more sealing force than gravity devices. It opens at 2.5" - 6" WC / .63 - 1.5 KPa pressure.
- Not for use in California / EVR applications.
- Model 004885 is certified to less than 1/3 of the CARB EVR Standard CP-201 which allows installation of three (3) P/V Vents maximum. This reduces installation time by not having to manifold the vent pipes together.
- Model 004885 is a threaded vent cap that is easily installed by using the caston hex nut which allows tightening without having to go between vent pipes.
- Model 004620 is a slip-on vent cap with a main pliable seal that seals to the vent stack and provides leakproof protection because the seal is at the end of the vent stack, not on the threads.

- Model 004620 uses four (4) stainless steel set screws to grip the vent stack preventing any loosening of the seal.
- Constructed from materials 100% compatible with B0-B20 and E0-E85.

Model 005885*

- Has an internal screen to protect the pressure plate in the event of a bad bulk drop.
- The safety over-pressure valve is designed to handle high pressure / high flow conditions. This valve will vent up to 7900 SCFH at 2 psi / .14 bar.
- Certified to less than 1/3 of the CARB EVR Standard CP-201 which allows installation of three (3) P/V vents maximum. This reduces installation time by not having to manifold the vent pipes together.
- Has a threaded vent cap that is easily installed by using the cast-on hex nut. This also allows tightening without having to go between vent pipes.
- Constructed from materials 100% compatible with B0-B20 and E0-E85.

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
004620	2 in / 51 mm Slip-On Pressure / Vacuum Vent Cap	1.2 (.54)
004885	2 in / 51 mm Thread-On Pressure / Vacuum Vent Cap	1.2 (.54)
005885*	2 in / 51 mm Thread-On Pressure / Vacuum Vent Cap with internal screen	1.2 (.54)

Construction

Body	Aluminum
Screen	40 Mesh Stainless Steel
Internal Screen	40 Mesh Stainless Steel (005885 only)
Set Screws	Stainless Steel
Deflector	Aluminum



This component was tested to and met the following criteria:

PRES. 2.5-6 IN. W.C.

VAC. 6-10 IN. W.C.

.05 CFH @ +2 IN. W.C.

.21 CFH @ -4 IN. W.C.



CALIFORNIA ENVIRONMENTAL PROTECTION AGENCY
AIR RESOURCES BOARD



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

All Pressure/Vacuum Vents have three (3) separate valves that address pressure/vacuum conditions in underground storage tanks and above ground storage tanks (AST).


Dimensions and System Options

Adapter

MODEL NO.	DESCRIPTION
005041	3 in / 76 mm Thread to 2 in / 51 mm Thread Pipe Adapter

Testing Equipment

MODEL NO.	DESCRIPTION
005426	Pressure / Vacuum Vent Test Adapter





Testing & Maintenance



Nozzle Service Kit



15-1

TESTING & MAINTENANCE

For Conventional, Balance or Vacuum Assist Systems.

- Nozzle Service Device (NSD) can be used with all brands / styles of retail nozzles.
- NSD provides easier removal and installation of nozzles - keeps nozzles off the ground.
- Safe-T-Break® Drain Cup can be used with all brands of breakaways - even non-reconnectable versions.
- Safe-T-Break® Drain Cup allows for pressure relief making reconnecting easier.
- Fuel Filter Cup can be used on all brands / styles of automotive and diesel dispenser fuel filters.
- Provides safe collection of fuel when replacing nozzles, Safe-T-Breaks® and fuel filters.
- Allows product maintenance without getting fuel directly on hands / skin.
- NSD, Safe-T-Break® Drain Cup, Fuel Filter Cup, wrench and pliers all fit inside the service pail for easy transportation.

Nozzle Service Kit

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007089	Nozzle Service Kit (includes part 006662 NSD, 007000 Safe-T-Break® Drain Cup, 007004 Fuel Filter Cup, 007086 Service Pail, 007088 NSD Pliers, 007332 Shear Valve Wrench and 007098 Fuel Filter Tool)	9.5 (4.3)

Basic Nozzle Service Kit

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007262	Basic Nozzle Service Kit (includes part 006662 NSD, 007000 Safe-T-Break® Drain Cup, 007004 Fuel Filter Cup and 007086 Service Pail)	9.0 (4.0)

Deluxe Nozzle Service Kit

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007263	Deluxe Nozzle Service Kit (includes part 006662 NSD, 007000 Safe-T-Break® Drain Cup, 007004 Fuel Filter Cup, 007086 Service Pail, 007332 Shear Valve Wrench, 007348 Deluxe Service Pliers and 007349 Deluxe Fuel Filter Pliers)	9.5 (4.3)

Construction

Service Pail	Steel
Nozzle Service Device (NSD)	Polypropylene
Safe-T-Break® Drain Cup	Polypropylene
Fuel Filter Cup	Plastisol



Part No. 007262



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Nozzle Service Kit

For Conventional, Balance, or Vacuum Assist Systems.

System Options

Nozzle Service Kit Parts

MODEL NO.	DESCRIPTION
006662	Nozzle Service Device (NSD)
007000	Safe-T-Break® Drain Cup
007004*	Fuel Filter Cup
007086	Service Pail
007088	NSD 12" Pliers
007098	Fuel Filter Tool (Wrench)
007099	Fuel Filter Service Kit (includes part 007004 Fuel Filter Cup and 007098 Fuel Filter Tool)
007332	Shear Valve Wrench
007348	Deluxe Service Pliers
007349	Deluxe Fuel Filter Pliers
007350	Deluxe Service Tool Kit (includes 007332 Shear Valve Wrench, 007348 Service Pliers, and 007349 Fuel Filter Pliers)
008071	Fuel Filter Cap with 5" Base

Color Chart

COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

*Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.

Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.



Part No. 007086



Part No. 007000



Part No. 007004



Part No. 006662



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Hose Conversion Adaptor

- Easy conversion of vapor recovery dispenser manifold to accept conventional hose configurations.

New Hose Conversion Adaptor

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
006941	Hose Conversion Adaptor M34 x 1.5	.18 (.40)
006959	Hose Conversion Adaptor Balanced	.26 (.57)
009500	Hose Conversion Adaptor 1-1/4" -18	.18 (.40)

Specifications

- 1 piece machined aluminum fittings
- Fluorocarbon o-rings.

Advantages

- Simple installation



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov




Husky

GENERAL FUELING PRODUCTS

HCA Hose Conversion Adaptor

Hose Conversion Adaptor

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





GENERAL FUELING PRODUCTS

Flo-Equalizers™



Husky Flo-Equalizers® limit fuel flow to a maximum 10 gpm / 37.9 Lpm to comply with Comprehensive Environmental Response, Compensation, and Liability Act.

- All Husky Flo-Equalizers® are pressure compensating and allow full advantage of high capacity pumps.
- Low pressure loss at flows less than 10 gpm / 37.9 Lpm.

Model 004490

- For conventional systems.
- Installs in-line within the fuel line.
- Comes standard with pipe nipple for easy installation.



Model 004490

Model 005827

- For balance vapor recovery systems.
- Installs directly into the dispenser outlet casting.

Model 005837

- For vacuum assist vapor recovery systems.
- Installs directly into the dispenser outlet casting.

Model 007490

- For conventional nozzles with 3/4" / 19 mm inlet.
- Installs into nozzle inlet.



Model 007490



Model 005827



Model 005837

Flo-Equalizer®

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
004490	3/4" F x 3/4" F NPT threads	.37 (0.16)
005827	1 1/8" x 12 threads	.43 (0.19)
005837	M34 x 1.5 threads	.37 (0.16)
007490	Internal use only	.02 (0.01)

Construction

Body	004490, 005827 and 005837: Aluminum
	007490: Plastic
Seals	004490 and 700490: N/A
	005827 and 005837: Fluorocarbon




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



FLO-Equalizer®

Husky Flo-Equalizers® limit fuel flow to a maximum 10 gpm / 37.9 Lpm to comply with Comprehensive Environmental Response, Compensation, and Liability Act.

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



DEF Adaptors



Diesel Exhaust Fueling Adaptors.

- 007214, 007285, 007356, 008413, 010579, 010675, 011477 and 012872 adaptors have stainless steel construction.
- 010227, 010549, 010551 and 010553 adaptors have polymer construction.
- 007214, 007285, 007356 and 008413 adaptors are UL recognized components and certified for DEF.



Model 007214



Model 008413

Diesel Exhaust Adaptors

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007214	Hose Barb 3/4" ID Hose x 3/4" BSPP with Seal Kit	.22 (.10)
007285	1" M x 1" M BSPP Straight Adaptor	.29 (.13)
007356	1" M BSPP x M M34 Straight Adaptor	.30 (.13)
008413	Hose Barb 3/4" ID Hose x 1" BSPP with Seal Kit	.29 (.13)
010227	1" F BSPP Adaptor	.20 (.10)
010549	1" F BSPP x 1" NPT Adaptor	.20 (.10)
010551	1" F BSPP x 3/4" NPT Adaptor	.20 (.10)
010553	1" F BSPP x 3/4" BSP Adaptor	.20 (.10)
010579	1" F BSPP x 3/4" Hose Barb Adaptor	.20 (.10)
010675	1" F x 1" F BSPP Straight Adaptor	.20 (.10)
011477	1" M BSPP x 3/4" F NPT Straight Adaptor	.22 (.10)
012872	1" M BSPP x 3/4" F BSPP Straight Adaptor	.22 (.10)

Model 007356



Model 007285














WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Diesel Exhaust Fueling Adaptors.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
007406	3/4" DEF Seal Kit
007407	1" DEF Seal Kit

Model 007214

Model 007285

Model 007356

Model 008413

Model 010579

Model 010675

Model 010227

Model 010549

Model 010551

Model 010553

**Model 011477
& 012872**


2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Hoses



Premium Hardwall Gasoline Pump Hose.

- Recommended anywhere a hardwall hose is required.
- Resists kinking and eliminates meter creep.
- Recommended for all gasoline and gasoline/Ethanol blends at Ethanol levels designated as "gasohol" (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline.
- Improves ozone and abrasion resistance while providing increased life.
- Improves draping and handling characteristics.
- Will not mark or scratch vehicle finishes.
- Hose material is private branded and UL Listed to UL 330 and CAN/ULC-S612-99.
- Designed for durability, flexibility, and easy handling.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.
- Highly resistant to cuts, abrasions, sun and weather.



Hardwall Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
5/8" HOSES		
CP10HW01	5/8" Hardwall 1' Assembly Hose	0.39 (0.58)
CP10HW09	5/8" Hardwall 9' Assembly Hose	3.5 (1.6)
3/4" HOSES		
CP12HWG08	3/4" Green Hardwall 8' Assembly Hose	3.8 (1.7)
CP12HWG09	3/4" Green Hardwall 9' Assembly Hose	4.2 (1.9)
CP12HWG09SV	3/4" Green Hardwall 9' Assembly Hose Swivel	4.2 (1.9)
CP12HWG10	3/4" Green Hardwall 10' Assembly Hose	4.7 (2.1)
CP12HWG12SV	3/4" Green Hardwall 12' Assembly Hose Swivel	5.6 (2.5)
CP12HWR10	3/4" Red Hardwall 10' Assembly Hose	4.7 (2.1)
CP12HW09	3/4" Hardwall 9' Assembly Hose	4.2 (1.9)
CP12HW09.5	3/4" Hardwall 9.5' Assembly Hose	4.5 (2.0)
CP12HW09SV	3/4" Hardwall 9' Assembly Hose Swivel	4.2 (1.9)
CP12HW12	3/4" Hardwall 12' Assembly Hose	5.6 (2.5)
CP12HW14	3/4" Hardwall 14' Assembly Hose	6.6 (3.0)
CP12HW14X	3/4" Hardwall 14' Assembly Hose Bulk	6.6 (3.0)
CP12HW15X	3/4" Hardwall 14' Assembly Hose Bulk	6.6 (3.0)
CP12HW17	3/4" Hardwall 17' Assembly Hose	8.0 (3.6)
CP12HW9.5X	3/4" Hardwall 9.5' Assembly Hose Bulk	4.5 (2.0)
1" HOSES		
CP16HW01	1" Hardwall 1' Assembly Hose	0.64 (0.95)
CP16HW06	1" Hardwall 6' Assembly Hose	3.8 (1.7)
CP16HW10	1" Hardwall 10' Assembly Hose	6.4 (2.9)
CP16HW10X	1" Hardwall 10' Assembly Hose Bulk	6.4 (2.9)
CP16HW15	1" Hardwall 15' Assembly Hose	9.6 (4.4)
CP16HW15X	1" Hardwall 15' Assembly Hose Bulk	9.6 (4.4)
CP16HW17	1" Hardwall 17' Assembly Hose	10.9 (4.9)
CP16HW20X	1" Hardwall 20' Assembly Hose Bulk	12.8 (5.8)

Construction

Tube	Black Nitrile
Cover	Black CPE (chlorinated polyethylene), wrap impression
Reinforcement	Multiple textile braids with dual static wire helix
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Body	3/4" Red or Green Hardwall Available



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



EagleFlex® Hardwall

Premium Hardwall Gasoline Pump Hose.

System Options

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
5/8"	16	1.03	26	150	1.03	0.39	0.58
3/4"	19	1.17	30	150	1.03	0.47	0.70
1"	25	1.45	37	150	1.03	0.64	0.95

Couplings

Permanent internally expanded fixed chrome plated brass or external crimp zinc (L type).

Reattachable fixed and Reattachable swivel 3/4" and 1" male NPT. UL does not recognize field installation of reattachable fittings.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Softwall Gasoline Pump Hose.

- A lightweight, flexible hose for use when a hardwall hose is inappropriate.
- Recommended for all gasoline and gasoline/Ethanol blends at Ethanol levels designated as "gasohol" (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline.
- Excellent strength without sacrificing flexibility.
- Highly resistant to cuts, abrasions, sun and weather.
- Smooth cover will not mark or scratch vehicle finishes.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.



Softwall Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4" HOSES		
CP12SW04X	3/4" Softwall 4' Assembly Hose Bulk	1.4 (0.6)
CP12SW09	3/4" Softwall 9' Assembly Hose	3.1 (1.4)
CP12SW10	3/4" Softwall 10' Assembly Hose	3.4 (1.5)
CP12SW10X	3/4" Softwall 10' Assembly Hose Bulk	3.4 (1.5)
CP12SW12	3/4" Softwall 12' Assembly Hose	4.1 (1.9)
CP12SW14	3/4" Softwall 14' Assembly Hose	4.8 (2.2)
CP12SW14X	3/4" Softwall 14' Assembly Hose Bulk	4.8 (2.2)
CP12SW17	3/4" Softwall 17' Assembly Hose	5.8 (2.6)
CP12SW20	3/4" Softwall 20' Assembly Hose	6.8 (3.1)
CP12SW30	3/4" Softwall 30' Assembly Hose	10.2 (4.6)
CP12SW40	3/4" Softwall 40' Assembly Hose	13.6 (6.2)
CP12SW50	3/4" Softwall 50' Assembly Hose	17.0 (7.7)
CP12SW9.5	3/4" Softwall 9.5' Assembly Hose	3.2 (1.5)
1" HOSES		
CP16SW10	1" Softwall 10' Assembly Hose	4.7 (2.1)
CP16SW11	1" Softwall 11' Assembly Hose	5.2 (2.4)
CP16SW12	1" Softwall 12' Assembly Hose	5.6 (2.5)
CP16SW14	1" Softwall 14' Assembly Hose	6.6 (3.0)
CP16SW14X	1" Softwall 14' Assembly Hose Bulk	6.6 (3.0)
CP16SW17	1" Softwall 17' Assembly Hose	8.0 (3.6)
CP16SW20	1" Softwall 20' Assembly Hose	9.4 (4.3)
CP16SW20X	1" Softwall 20' Assembly Hose Bulk	9.4 (4.3)
CP16SW60	1" Softwall 60' Assembly Hose	28.2 (12.8)

Construction

Tube	Black Nitrile
Cover	Black CPE (chlorinated polyethylene), smooth finish
Reinforcement	Multiple textile braids static wire
Temperature Range	-40°F to +180°F (-40°C to +82°C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Softwall Gasoline Pump Hose.

System Options

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
3/4"	19	1.10	28	150	1.03	0.34	0.51
1"	25	1.39	35	150	1.03	0.47	0.63

Couplings

Permanent internally expanded fixed 3/4" and 1" male NPT chrome plated brass or external crimp zinc (L type).

Swivel couplings are not available with softwall hose.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Wirebraid Gasoline Pump Hose.

- Recommended anywhere a hardwall or softwall hose is inappropriate.
- Recommended for all gasoline and gasoline/Ethanol blends at Ethanol levels designated as "gasohol" (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline.
- Resistant to crushing and stands up to run-over.
- Highly resistant to cuts, abrasions, sun and weather.
- Flexibility of a softwall, durability of a hardwall.
- Assures accurate readings at the pump.
- Will not mark or scratch vehicle finishes.
- Hose material is private branded and UL Listed to UL 330 and CAN/ULC-S612-99.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.



Wirebraid Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
5/8" HOSES		
CP10WB08	5/8" Wirebraid 8' Assembly Hose	2.8 (1.3)
CP10WB09	5/8" Wirebraid 9' Assembly Hose	0.26 (0.12)
CP10WB09.5	5/8" Wirebraid 9.5' Assembly Hose	3.3 (1.5)
CP10WB10	5/8" Wirebraid 10' Assembly Hose	3.5 (1.6)
CP10WB14	5/8" Wirebraid 14' Assembly Hose	4.9 (2.2)
CP10WB9.5X	5/8" Wirebraid 9.5' Assembly Hose Bulk	3.3 (1.5)
3/4" HOSES		
CP12WB04	3/4" Wirebraid 4' Assembly Hose	1.7 (0.8)
CP12WB05	3/4" Wirebraid 5' Assembly Hose	2.1 (1.0)
CP12WB06	3/4" Wirebraid 6' Assembly Hose	2.5 (1.1)
CP12WB08	3/4" Wirebraid 8' Assembly Hose	3.4 (1.5)
CP12WB09	3/4" Wirebraid 9' Assembly Hose	3.8 (1.7)
CP12WB09SV	3/4" Wirebraid 9' Assembly Hose Swivel	3.8 (1.7)
CP12WB10	3/4" Wirebraid 10' Assembly Hose	4.2 (1.9)
CP12WB10X	3/4" Wirebraid 10' Assembly Hose Bulk	4.2 (1.9)
CP12WB12	3/4" Wirebraid 12' Assembly Hose	5.0 (2.3)
CP12WB12SV	3/4" Wirebraid 12' Assembly Hose Swivel	5.0 (2.3)
CP12WB12X	3/4" Wirebraid 12' Assembly Hose Bulk	5.0 (2.3)
CP12WB14	3/4" Wirebraid 14' Assembly Hose	5.9 (2.7)
CP12WB15SV	3/4" Wirebraid 15' Assembly Hose Swivel	6.3 (2.9)
CP12WB16	3/4" Wirebraid 16' Assembly Hose	6.7 (3.0)
CP12WB20	3/4" Wirebraid 20' Assembly Hose	8.4 (3.8)
CP12WB50X	3/4" Wirebraid 50' Assembly Hose Bulk	21.0 (9.5)
1" HOSES		
CP16WB04	1" Wirebraid 4' Assembly Hose	2.0 (0.9)
CP16WB06	1" Wirebraid 6' Assembly Hose	3.0 (1.4)
CP16WB08	1" Wirebraid 8' Assembly Hose	4.0 (1.8)
CP16WB09	1" Wirebraid 9' Assembly Hose	4.5 (2.0)
CP16WB10	1" Wirebraid 10' Assembly Hose Bulk	5.0 (2.3)
CP16WB10X	1" Wirebraid 10' Assembly Hose	5.0 (2.3)
CP16WB100SV	1" Wirebraid 100' Assembly Hose Swivel	50.0 (22.7)
CP16WB100SVSV	1" Wirebraid 100' Assembly Hose w/ Swivel on both ends	50.0 (22.7)
CP16WB12	1" Wirebraid 12' Assembly Hose	6.0 (2.7)
CP16WB12SV	1" Wirebraid 12' Assembly Hose Swivel	6.0 (2.7)
CP16WB13	1" Wirebraid 13' Assembly Hose	6.5 (3.0)
CP16WB14	1" Wirebraid 14' Assembly Hose	7.0 (3.2)
CP16WB14X	1" Wirebraid 14' Assembly Hose Bulk	7.0 (3.2)
CP16WB16	1" Wirebraid 16' Assembly Hose	8.0 (3.6)
CP16WB18	1" Wirebraid 18' Assembly Hose	9.0 (4.1)
CP16WB18X	1" Wirebraid 18' Assembly Hose Bulk	9.0 (4.1)
CP16WB20	1" Wirebraid 20' Assembly Hose	10.0 (4.5)
CP16WB20X	1" Wirebraid 20' Assembly Hose Bulk	10.0 (4.5)
CP16WB30	1" Wirebraid 30' Assembly Hose	15.0 (6.8)
CP16WB50SV	1" Wirebraid 50' Assembly Hose Swivel	25.0 (11.3)

Construction

Tube	Black Nitrile
Cover	Black CPE (chlorinated polyethylene), wrap impression
Reinforcement	Multiple textile braids with full diameter grounding sheath
Temperature Range	-40°F to +180°F (-40°C to +82°C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



EagleFlex® Wirebraid

Wirebraid Gasoline Pump Hose.

System Options

Available in these Sizes

ID	NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT
5/8"	16	0.97	25	150	1.03	0.35
3/4"	19	1.10	28	150	1.03	0.42
1"	25	1.34	34	150	1.03	0.50

Couplings

Permanent internally expanded fixed chrome plated brass or external crimp zinc (L type).

Reattachable fixed and Reattachable swivel 3/4" and 1" male NPT. UL does not recognize field installation of reattachable fittings.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Gasoline Hose Assemblies with Static Wire.

- Designed for durability and flexibility.
- Oil and abrasion resistant.
- Supplied with static wire.
- Recommended for use with electric pumps.
- Static wire hose always recommended with electric motors.
- Designed for use in agricultural, industrial and construction maintenance applications.
- Engineered for dispensing gasoline, diesel, kerosene and oil from farm and barrel-type pumps where UL approval is not required.
- Curb pump hose recommended for:
 - UL Listed hose material requirements.
 - For high aromatics or severe applications.
- All Farm Tank hose assemblies are 100% inspected for electrical continuity.
- Do not use these hoses at a service station or to refuel aircraft.

Farm Fueling Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4" HOSES		
FT012S10	3/4" x 10' Farm Tank Assembly Hose Bulk	2.9 (1.3)
FT012S12	3/4" x 12' Farm Tank Assembly Hose Bulk	3.5 (1.6)
FT012S12B	3/4" x 12' Farm Tank Assembly Hose Boxed	3.5 (1.6)
FT012S14	3/4" x 14' Farm Tank Assembly Hose Bulk	4.1 (1.9)
FT012S14B	3/4" x 14' Farm Tank Assembly Hose Boxed	4.1 (1.9)
FT012S15	3/4" x 15' Farm Tank Assembly Hose Bulk	4.4 (2.0)
FT012S15B	3/4" x 15' Farm Tank Assembly Hose Boxed	4.4 (2.0)
FT012S17	3/4" x 17' Farm Tank Assembly Hose Bulk	4.9 (2.2)
FT012S20	3/4" x 20' Farm Tank Assembly Hose Bulk	5.8 (2.6)
FT012S20B	3/4" x 20' Farm Tank Assembly Hose Boxed	5.8 (2.6)
1" HOSES		
FT016S10	1" x 10' Farm Tank Assembly Hose Bulk	4.5 (2.0)
FT016S12	1" x 12' Farm Tank Assembly Hose Bulk	5.4 (2.4)
FT016S12B	1" x 12' Farm Tank Assembly Hose Boxed	5.4 (2.4)
FT016S14	1" x 14' Farm Tank Assembly Hose Bulk	6.3 (2.9)
FT016S15	1" x 15' Farm Tank Assembly Hose Bulk	6.8 (3.1)
FT016S15B	1" x 15' Farm Tank Assembly Hose Boxed	6.8 (3.1)
FT016S17	1" x 17' Farm Tank Assembly Hose Bulk	7.7 (3.5)
FT016S20	1" x 20' Farm Tank Assembly Hose Bulk	9.0 (4.1)
FT016S20B	1" x 20' Farm Tank Assembly Hose Boxed	9.0 (4.1)
FT016S25	1" x 25' Farm Tank Assembly Hose Bulk	11.3 (5.1)

Construction

Tube	NBR, RMA Class A
Cover	NBR/PVC RMA Class A
Reinforcement	Spiral high tensile strength polyester cord
Temperature Range	-20°F to +160°F (-29°C to +71°C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

EagleFlex® Farm Tank

Gasoline Hose Assemblies with Static Wire.


System Options

Available in these Sizes

ID		NOM OD		WEIGHT	
Size	MM	IN	MM	LB/FT	KG/M
3/4"	19	1.13	29	0.29	0.43
1"	25	1.38	35	0.45	0.67

Couplings

Permanent externally crimped 3/4" and 1" NPT.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



HARDWALL WHIP HOSE:

- Recommended anywhere a hardwall hose is required.
- Highly resistant to cuts, abrasions, sun and weather.
- Improves ozone and abrasion resistance while providing increased life.

WIREBRAID WHIP HOSE:

- Recommended anywhere a hardwall or softwall hose is inappropriate.
- Provides full flow with no internal spring guards and will withstand full suction.
- Highly resistant to cuts, abrasions, sun and weather.
- Flexibility of a softwall, durability of a hardwall.

SOFTWALL WHIP HOSE:

- A lightweight, flexible hose for use when a hardwall hose is inappropriate.
- Highly resistant to cuts, abrasions, sun and weather.

ALL WHIP HOSES:

- Recommended for all gasoline and gasoline/Ethanol blends at Ethanol levels designated as "gasohol" (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline.
- Hose Material is private branded and UL listed.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.

Whip Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
5/8" HOSES		
CP10HW.75	5/8" Hardwall 9" Assembly Hose	0.3 (0.14)
CP10HW.75L	5/8" Hardwall low cost 9" Assembly Hose	0.3 (0.14)
CP10WB.75M	5/8" Wirebraid medium cost 9" Assembly Hose	0.3 (0.14)
CP10WB.75SV	5/8" Wirebraid Swivel 9" Assembly Hose	0.3 (0.14)
CP10WB.75LSV	5/8" Wirebraid low cost Swivel 9" Assembly Hose	0.3 (0.14)
3/4" HOSES		
CP12HW.75	3/4" Hardwall 9" Assembly Hose	0.3 (0.14)
CP12HWG.75	3/4" Green Hardwall 9" Assembly Hose	0.3 (0.14)
CP12HW.75L	3/4" Hardwall low cost 9" Assembly Hose	0.3 (0.14)
CP12HW.75SV	3/4" Hardwall Swivel 9" Assembly Hose	0.3 (0.14)
CP12WB.75L	3/4" Wirebraid low cost 9" Assembly Hose	0.3 (0.14)
CP12WB.75SV	3/4" Wirebraid Swivel 9" Assembly Hose	0.3 (0.14)
1" HOSES		
CP16HW.75	1" Hardwall 9" Assembly Hose	0.5 (0.23)
CP16HW.75L	1" Hardwall low cost 9" Assembly Hose	0.5 (0.23)
CP16HW.75SV	1" Hardwall Swivel 9" Assembly Hose	0.5 (0.23)
CP16WB.75L	1" Wirebraid low cost 9" Assembly Hose	0.5 (0.23)
CP16WB.75SV	1" Wirebraid Swivel 9" Assembly Hose	0.5 (0.23)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Whip Hoses

Dimension



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

DEF hose assemblies without static wire.

- Designed for durability and flexibility.
- Abrasion resistant.
- Supplied without static wire.
- Recommended for use with electric pumps or dispensers.
- Designed for any DEF dispensing applications.
- Engineered for dispensing DEF where UL approval is not required.
- Curb pump hose recommended for:
 - UL Listed hose material requirements.
 - For high aromatics or severe applications.
- All DEF hose assemblies are 100% inspected for pressure to 50 psi.

DEF Fueling Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4" HOSES		
CP12DF10GP	3/4" x 10' DEF Assembly Hose Bulk	2.9 (1.3)
CP12DF12GP	3/4" x 12' DEF Assembly Hose Bulk	3.5 (1.6)
CP12DF12GPX	3/4" x 12' DEF Assembly Hose Boxed	3.5 (1.6)
CP12DF14GP	3/4" x 14' DEF Assembly Hose Bulk	4.1 (1.9)
CP12DF14GPX	3/4" x 14' DEF Assembly Hose Boxed	4.1 (1.9)
CP12DF15GP	3/4" x 15' DEF Assembly Hose Bulk	4.4 (2.0)
CP12DF15GPX	3/4" x 15' DEF Assembly Hose Boxed	4.4 (2.0)
CP12DF17GP	3/4" x 17' DEF Assembly Hose Bulk	4.9 (2.2)
CP12DF20GP	3/4" x 20' DEF Assembly Hose Bulk	5.8 (2.6)
CP12DF20GPX	3/4" x 20' DEF Assembly Hose Boxed	5.8 (2.6)

Construction

Tube	Black customized peroxide-cured EPDM
Cover	Black customized EPDM with smooth finish
Reinforcement	Multiple textile plies
Temperature Range	-40°F to +212°F (-40°C to +100°C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



DEF Dispensing

DEF hose assemblies without static wire.

System Options

Available in these Sizes

ID	NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	LB/FT	KG/M	LB/FT
3/4"	19	1.13	29	150	1.03	0.29
						0.43

Couplings

Permanent externally crimped 3/4" NPT glass filled polypropylene stem with brass ferrule.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Premium Low Permeation Hardwall Gasoline Pump Hose.

- Recommended anywhere a hardwall hose is required.
- Recommended for all gasoline and gasoline/Ethanol blends at Ethanol levels designated as "gasohol" (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline where low permeation ($\leq 10\text{g}/\text{m}^2/\text{day}$) is required.
- Designed for durability, flexibility, and easy handling.
- Highly resistant to cuts, abrasions, sun and weather.
- Resists kinking and eliminates meter creep.
- Improves ozone and abrasion resistance while providing increased life.
- Improves draping and handling characteristics.
- Will not mark or scratch vehicle finishes.
- Hose material is private branded and UL Listed to UL 330 for low permeation.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.

Low Perm Hardwall Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
5/8" LP HOSES		
CP10LP8.5	5/8" Low Perm Hardwall 8.5' Assembly Hose	3.8 (1.7)
CP10LP10	5/8" Low Perm Hardwall 10' Assembly Hose	4.7 (2.1)
3/4" LP HOSES		
CP12LP8.5	3/4" Low Perm Hardwall 8.5' Assembly Hose	3.8 (1.7)
CP12LP8.5SV	3/4" Low Perm Hardwall 8.5' Assembly Hose Swivel	4.2 (1.9)
CP12LP9	3/4" Low Perm Hardwall 9' Assembly Hose	4.2 (1.9)
CP12LP9SV	3/4" Low Perm Hardwall 9' Assembly Hose Swivel	4.7 (2.1)
1" LP HOSES		
CP16LP8	1" Low Perm Hardwall 8' Assembly Hose	6.4 (2.9)
CP16LP14	1" Low Perm Hardwall 14' Assembly Hose	9.6 (4.4)

Construction

Tube	Black Nitrile
Cover	Black CPE (Chlorinated Polyethylene), wrap impression
Reinforcement	Multiple textile braids with dual static wire helix
Temperature Range	-40°F to +180°F (-40°C to +82°C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

EagleFlex® Low Perm Hardwall

Premium Low Permeation Hardwall Gasoline Pump Hose.

System Options

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
5/8"	16	1.03	26	150	1.03	0.37	0.55
3/4"	19	1.17	30	150	1.03	0.44	0.65
1"	25	1.45	37	150	1.03	0.59	0.88

Couplings

Permanent, external crimp, zinc plated steel couplings, fixed and swivel



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Whip Low Perm Hoses



18-8

HUSKY HOSES

- Recommended anywhere a hardwall hose is required.
- Recommended for all gasoline and gasoline/Ethanol blends at Ethanol levels designated as "gasohol" (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline where low permeation ($\leq 10\text{g/m}^2/\text{day}$) is required.
- Designed for durability, flexibility, and easy handling.
- Highly resistant to cuts, abrasions, sun and weather.
- Resists kinking and eliminates meter creep.
- Improves ozone and abrasion resistance while providing increased life.
- Will not mark or scratch dispenser finishes.
- Hose material is private branded and UL Listed to UL 330 for low permeation.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.

Whip Low Perm Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
5/8" LP HOSES		
CP10LP.75	5/8" Low Perm Hardwall 9" Assembly Hose	0.72 (0.3)
CP10LP.75SV	5/8" Low Perm Hardwall 9" Swivel Assembly Hose	0.72 (0.3)
3/4" LP HOSES		
CP12LP.75	3/4" Low Perm Hardwall 9" Assembly Hose	1.00 (0.5)
CP12LP.75SV	3/4" Low Perm Hardwall 9" Swivel Assembly Hose	1.00 (0.5)
1" LP HOSES		
CP16LP.75	1" Low Perm Hardwall 9" Assembly Hose	1.20 (0.5)
CP16LP.75SV	1" Low Perm Hardwall 9" Swivel Assembly Hose	1.20 (0.5)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Husky

GENERAL FUELING PRODUCTS

Whip Low Perm Hoses

System Options

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
5/8"	16	1.03	26	150	1.03	0.37	0.55
3/4"	19	1.17	30	150	1.03	0.44	0.65
1"	25	1.45	37	150	1.03	0.59	0.88

Couplings

Permanent, external crimp, zinc plated steel couplings, fixed and swivel



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Fuel Oil Hose



18-9

FUEL OIL FUELING HOSES

Fuel Oil Permanent Fitting fueling hose recommended for all home fuel oils, leaded and unleaded gasolines, and diesel and tractor fuels.

- Used for all home fuel oils, leaded and unleaded gasolines, and diesel and tractor fueling applications
- All fuel oil hose assemblies are 100% hydrostatic tested
- Resistant to flex fatigue
- Smooth cover gives it minimum ground drag, added freedom of movement and abrasion resistance



Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1" BULK HOSES		
9769	Hose, 1" Red Fuel Oil 100'	47 (21.3)
9769	Hose, 1" Red Fuel Oil 125'	59 (26.8)
9769	Hose, 1" Red Fuel Oil 150'	71 (32.2)
1 1/4" BULK HOSES		
9770	Hose, 1 1/4" Red Fuel Oil 100'	59 (26.8)
9770	Hose, 1 1/4" Red Fuel Oil 125'	74 (33.6)
9770	Hose, 1 1/4" Red Fuel Oil 150'	89 (40.4)
1 1/2" BULK HOSES		
9771	Hose, 1 1/2" Red Fuel Oil 100'	80 (36.3)
9771	Hose, 1 1/2" Red Fuel Oil 125'	100 (45.4)
9771	Hose, 1 1/2" Red Fuel Oil 150'	120 (54.4)
1" HOSES		
CP161200FABA	1" x 100' Red Fuel Oil Assy M x M	49 (22.2)
CP161200FBBA	1" x 100' Red Fuel Oil Assy M x F	49 (22.2)
CP161200FCBA	1" x 100' Red Fuel Oil Assy F x F	49 (22.2)
CP161500FABA	1" x 125' Red Fuel Oil Assy M x M	61 (27.7)
CP161500FBBA	1" x 125' Red Fuel Oil Assy M x F	61 (27.7)
CP161500FCBA	1" x 125' Red Fuel Oil Assy F x F	61 (27.7)
CP161800FABA	1" x 150' Red Fuel Oil Assy M x M	73 (33.1)
CP161800FBBA	1" x 150' Red Fuel Oil Assy M x F	73 (33.1)
CP161800FCBA	1" x 150' Red Fuel Oil Assy F x F	73 (33.1)
1 1/4" HOSES		
CP201200FABA	1 1/4" x 100' Red Fuel Oil Assy M x M	61 (27.7)
CP201200FBBA	1 1/4" x 100' Red Fuel Oil Assy M x F	61 (27.7)
CP201200FCBA	1 1/4" x 100' Red Fuel Oil Assy F x F	61 (27.7)
CP201500FABA	1 1/4" x 125' Red Fuel Oil Assy M x M	76 (34.5)
CP201500FBBA	1 1/4" x 125' Red Fuel Oil Assy M x F	76 (34.5)
CP201500FCBA	1 1/4" x 125' Red Fuel Oil Assy F x F	76 (34.5)
CP201800FABA	1 1/4" x 150' Red Fuel Oil Assy M x M	91 (41.3)
CP201800FBBA	1 1/4" x 150' Red Fuel Oil Assy M x F	91 (41.3)
CP201800FCBA	1 1/4" x 150' Red Fuel Oil Assy F x F	91 (41.3)
1 1/2" HOSES		
CP241200FABA	1 1/2" x 100' Red Fuel Oil Assy M x M	82 (37.2)
CP241200FBBA	1 1/2" x 100' Red Fuel Oil Assy M x F	82 (37.2)
CP241200FCBA	1 1/2" x 100' Red Fuel Oil Assy F x F	82 (37.2)
CP241500FABA	1 1/2" x 125' Red Fuel Oil Assy M x M	102 (46.3)
CP241500FBBA	1 1/2" x 125' Red Fuel Oil Assy M x F	102 (46.3)
CP241500FCBA	1 1/2" x 125' Red Fuel Oil Assy F x F	102 (46.3)
CP241800FABA	1 1/2" x 150' Red Fuel Oil Assy M x M	122 (55.3)
CP241800FBBA	1 1/2" x 150' Red Fuel Oil Assy M x F	122 (55.3)
CP241800FCBA	1 1/2" x 150' Red Fuel Oil Assy F x F	122 (55.3)

Construction

Tube	NBR, RMA Class A
Cover	NBR/PVC, RMA Class A
Reinforcement	4 spiral polyester yarn
Cover Color:	Red
Oil Resistance:	High, Medium-High
Temperature:	-20°F (-29°C) to +180°F (82°C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Fuel Oil Hose


Fuel Oil Permanent Fitting fueling hose recommended for all home fuel oils, leaded and unleaded gasolines, and diesel and tractor fuels.

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
1"	25	1.50	38.0	250	1.72	0.47	0.71
1 ¹ / ₄ "	32	1.78	45.2	250	1.72	0.59	0.87
1 ¹ / ₂ "	38	2.06	52.3	250	1.72	0.80	1.19

Couplings

Permanent Brass	Internally expanded fittings - male NPT and female NPS (swivel nut)
-----------------	---



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

E0-E85 Curb Pump Hose.

- Recommended for use with Ethanol blends from E0 to E85.
- Resistant to crushing and stands up to run-over.
- Highly resistant to cuts, abrasions, sun and weather.
- Flexibility of a softwall, durability of a hardwall.
- Assures accurate readings at the pump.
- Will not mark or scratch vehicle finishes.
- Hose material is private branded and UL Listed to UL 330A and CAN/ULC-S612-99.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.

E0-E85 Wirebraid Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4" HOSES		
CP12ET04	3/4" E0-E85 4' Assembly Hose	1.7 (0.8)
CP12ET05	3/4" E0-E85 5' Assembly Hose	2.1 (1.0)
CP12ET06	3/4" E0-E85 6' Assembly Hose	2.5 (1.1)
CP12ET08	3/4" E0-E85 8' Assembly Hose	3.4 (1.5)
CP12ET09	3/4" E0-E85 9' Assembly Hose	3.8 (1.7)
CP12ET10	3/4" E0-E85 10' Assembly Hose	4.2 (1.9)
CP12ET10X	3/4" E0-E85 10' Assembly Hose Bulk	4.2 (1.9)
CP12ET12	3/4" E0-E85 12' Assembly Hose	5.0 (2.3)
CP12ET12X	3/4" E0-E85 12' Assembly Hose Bulk	5.0 (2.3)
CP12ET14	3/4" E0-E85 14' Assembly Hose	5.9 (2.7)
CP12ET16	3/4" E0-E85 16' Assembly Hose	6.7 (3.0)
CP12ET20	3/4" E0-E85 20' Assembly Hose	8.4 (3.8)
CP12ET50X	3/4" E0-E85 50' Assembly Hose Bulk	21.0 (9.5)

Construction

Tube	Black Nitrile
Cover	Black CPE (chlorinated polyethylene), wrap impression
Reinforcement	Multiple textile braids with full diameter grounding sheath
Temperature Range	-40°F to +180°F (-40°C to +82°C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



EagleFlex® E0-E85

E0-E85 Curb Pump Hose.


System Options

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
3/4"	19	1.10	28	150	1.03	0.42	0.63

Couplings

Permanent externally crimped zinc (L type).



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



EZ-Connect



The only certified, pre-assembled, pressure and continuity-tested hanging hardware.

- Can also be configured for new station installs.
- Fully customizable.
- Available in 5/8", 3/4" and 1" assemblies.
- Pre-fabricated hanging hardware assembly.
- Includes choice of Hose/Dispenser adaptor (Balanced/Vac-Assist/Heavy).
- Robust multi-plane Husky® swivel.
- 3 types of hose material offered: Hardwall, Wirebraid and Softwall.
- Zinc Fittings
- Chrome-plated brass fittings.
- EZ-Connect® hoses assembled with UL/CUL certified components.
- Your choice of nozzle configuration.
- 100% continuity/pressure tested.
- Thread sealant used on all component connections (Gasola®).
- All required hanging hardware for decommissioning in one single package.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



The only certified, pre-assembled, pressure and continuity-tested hanging hardware. Thousands of conventional fuel pump combinations are available with **EZ-Connect's®** six interchangeable components, making it possible to design a pump package to meet specific fuel-dispensing needs.

This sample chart, using 5/8" Hardwall Hoses, demonstrates the many options available:

5/8" Connections/9' Hardwall Hoses Kits			
	w/002273 (Single Use) STB	w/003360 Reconnectable STB	w/008330 MagBreak®
Balance to Conventional Adaptor	006959	006959	006959
5/8" x 9" Hardwall Whip Hose	CP10HW.75	CP10HW.75	CP10HW.75
Safe-T-Break®	002273	003360	008330
5/8" x 9' Hardwall Curb Hose	CP10HW09	CP10HW09	CP10HW09
3/4" Multi-Plane Swivel	000350	000350	000350
New XS® Pressure Activated Automatic Nozzle w/1808 Splash Guard	159559	159559	159559

5/8" Connections/10' Hardwall Hoses Kits

	w/002273 (Single Use) STB	w/003360 Reconnectable STB	w/008330 MagBreak®
Balance to Conventional Adaptor	006959	006959	006959
5/8" x 9" Hardwall Whip Hose	CP10HW.75	CP10HW.75	CP10HW.75
Safe-T-Break®	002273	003360	008330
5/8" x 10' Hardwall Curb Hose	CP10HW10	CP10HW10	CP10HW10
3/4" Multi-Plane Swivel	000350	000350	000350
New XS® Pressure Activated Automatic Nozzle w/1808 Splash Guard	159559	159559	159559

This sample chart, using 3/4" Softwall DEF Hoses, demonstrates the many options available:

New X DEF Nozzle w/ 3/4" NPT Connections/9' Softwall DEF Hose Kits^

	w/012070 Reconnectable STB
3/4" 9" Softwall DEF Whip Hose	CP12DF.75AN
Safe-T-Break®	012070
3/4" 9' Softwall DEF Hose	CP12DF09AN
3/4" Roller Bearing Swivel	012604
New X DEF Automatic Nozzle w/004809 Splash Guard	11676155N

New Polymer DEF Nozzle w/ 3/4" NPT Connections/9' Softwall DEF Hose Kits^

	w/012070 Reconnectable STB
3/4" 9" Softwall DEF Whip Hose	CP12DF.75GP
Safe-T-Break®	012070
3/4" 9' Softwall DEF Hose	CP12DF09PB
New Polymer DEF Automatic Nozzle w/000216 Splash Guard	873504N

New X DEF Nozzle w/ 3/4" BSPP Connections/9' Softwall DEF Hose Kits^

	w/012659 Reconnectable STB
3/4" 9" Softwall DEF Whip Hose	CP12DF.75AB
Safe-T-Break®	012659
3/4" 9' Softwall DEF Hose	CP12DF09AB
3/4" Roller Bearing Swivel	012656
New X DEF Automatic Nozzle w/001808 Splash Guard, w/007361 Handle Guard	11676154N

^Not Listed

Please contact your Husky sales representative or Husky customer service at (800) 325 3558 for questions regarding EZ Connects.



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Oil Baron

Safely cleans petroleum spills, making them non hazardous and nonflammable.

When your job involves working with hydrocarbons (including oil, grease and gasoline), you know how tough it is to safely clean up the spills left behind. Oil Baron safely cleans up the spills, rendering them nonhazardous and requiring no special waste disposal.

From service stations to auto repair bays, Oil Baron makes it easy to clean unsightly, unsafe or hazardous messes and spills. It breaks down hydrocarbons (gasoline and other petroleum products) to water and carbon dioxide. It can be applied using floor scrubbers, pressure washers, foaming sprayers or mops with no special hazardous waste disposal required.



The advantages of Oil Baron:

- Breaks down hydrocarbons (including gasoline) to water and carbon dioxide
- Cuts through the tough oil, grease, carbon and other spills for superior results
- Microbial action digests hydrocarbon mess
- No oil or greasy residue left behind
- Surfaces are clean, dry and oil-free for ideal traction
- Quick drying and available in an easy-to-use spray or concentrate
- Apply with mops, foaming sprayer, auto floor scrubbers and pressure washers
- Less expensive and lasts longer compared to conventional cleaners and degreasers

Works on these surface areas:

- Concrete, tile, and metal
- Urethane, acrylic and latex paint
- VCT and waxed floors
- Plexi-glass, epoxy, plastic and rubber

Nonhazardous:

- Non-corrosive, fragrance-free product
- Significantly reduces the ability of flammable hydrocarbons to ignite



Safely cleans petroleum spills, making them non hazardous and nonflammable.

Usage/Dilution Ratio Chart

Applications & Ratios

	HEAVY DUTY	MEDIUM DUTY	LIGHT DUTY
Floor Scrubber	1:30	1:30	1:40
Mopping	1:05	1:10	1:15
Degreasing	1:2	1:4	1:8
Pressure Washing	1:50	1:75	1:100
Spill Control	Do Not Dilute	1:1	1:1

20 oz. Aerosol

Item No.	013824
Unit Size	20 oz.
Unit Dimensions	9.5" H x 2.25" W x 2.25" D
Case Quantity	12
Case Dimensions	9.5" H x 11" W x 8.5" D
Case Weight	20 lbs.
Case Cubic	0.51
Pallet	18 x 5 = 90 Cases

32 oz. Quart

Item No.	013823
Unit Size	32 oz.
Unit Dimensions	9" H x 4" W x 3" D
Case Quantity	12
Case Dimensions	10.5" H x 11" W x 14.5" D
Case Weight	32 lbs.
Case Cubic	0.97
Pallet	12 x 4 = 48 Cases



20 oz. Aerosol



32 oz. Quart



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Oil Baron Plus removes the toughest hydrocarbon (oil, gas/diesel, tar) stains on most hard, industrial surfaces.

It can seem impossible to remove tough, deep oil, tar and grease stains in concrete or other hard surfaces. With Oil Baron Plus, it's not only possible to regain a clean surface area, this easy-to-use product outperforms all other competitors.

Simply apply Oil Baron Plus onto the effected surface area then scrub. It immediately does the hard work by penetrating deep into the surface to remove tough, embedded stains. Then just rinse for an oil-free surface. There's no waiting to see results. There are no worries about safety concerns you find with dangerous acids. Best of all, Oil Baron Plus removes your frustration of cleaning up the toughest oil stains.



The advantages of Oil Baron Plus:

- Quickly penetrates deep into the material surface to immediately remove oil and tar stains
- Microbial action eliminates stains
- Outperforms dangerous acids, conventional degreasing and poultice products
- Easy and simple to use: Apply, scrub, rinse and you're done
- Economical: Treats up to 10x more surface area than competitive products

Works in these applications:

- Fueling areas
- Loading docks, parking lots, drive-throughs
- Manufacturing facilities
- Vehicle repair facilities
- Concrete parking garages

Ideal for deep cleaning:*

- Concrete
- Bricks
- Masonry
- Pavers

Removes tough stains caused by:

- Motor oil, tar, anti-freeze, grease and diesel fuel
- Brake, hydraulic, power steering and transmission fluid

*Not for use on asphalt.



Oil Baron Plus

Oil Baron Plus removes the toughest hydrocarbon (oil, gas/diesel, tar) stains on most hard, industrial surfaces.

Comparison Chart

Compare

PRODUCT	TIME	CHEMISTRY	COVERAGES
Oil Baron Plus	1 min.	Microbial Cleaner	75 sq. ft./20 oz.
Competitor 1	5-8 hrs.	Poultice	6 sq. ft./32 oz.
Competitor 2	5-8 hrs.	Poultice	18 sq. ft./32 oz.
Competitor 3	5 min.	Acid-Cleaner	50 sq. ft./0.5 gal.
Competitor 4	30 min.	Poultice	30 sq. ft./0.5 gal.

16 oz. Aerosol

Item No.	013826
Unit Size	16 oz.
Unit Dimensions	2.125" L x 2.125" W x 10.25" H
Case Quantity	12
Case Dimensions	11.25" L x 8.5" W x 10.25" H
Case Weight	15 lbs.
Case Cubic	0.56
Pallet	18 x 5 = 90 Cases

32 oz. Quart

Item No.	013825
Unit Size	32 oz.
Unit Dimensions	5.25" L x 2.0" W 7.75" H
Case Quantity	6
Case Dimensions	12.0" L x 6.0" W x 7.75" H
Case Weight	16 lbs.
Case Cubic	0.5
Pallet	12 x 4 = 48 Cases



32 oz. Quart




16 oz. Aerosol



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Oil Filter Crushers



C-4 Crusher



1-1

OIL FILTER CRUSHERS

C-4 Pneumatic Oil Filter Crusher for automobile filters.

- Reduces filters by 75% of original size, and removes 95% of the free-flowing oil so it can be recycled.
- Crushing chamber accepts filters 7 1/2" tall x 5" diameter.
- Only one moving part, a 1 1/2" shaft.
- Safety door - crusher will not operate if door is opened.
- Cycle time: 5 seconds.
- Air requirement: 125 to 175 PSI.
- Air regulator not needed.
- Oiler and lubricator not needed.
- All parts in contact with air are rust proof.
- Optional stand (sold separately).
- Overall size: 26" high, 11" wide, 11" deep.
- Lifetime warranty on housing, one year limited on all other parts.
- 12" Flexible drain hose included.
- Wall mounting brackets included.
- Crusher weight 130 lbs. (Shipping weight 116 lbs. Shipped UPS.)

New Crushers

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
7605	C-4 Pneumatic Automobile Oil Filter Crusher	118 (53.5)
7590	Small Crusher Stand for C-4 and C-6 Oil Filter Crushers	101 (45.8)
8203	C-4 Pneumatic Automobile Oil Filter Crusher with #7590 Crusher Stand	219 (99.3)





C-4 Crusher

C-4 Pneumatic Oil Filter Crusher for automobile filters.

Dimensions and System Options

Repair Parts

MODEL NO.	DESCRIPTION
7589	C4, C6 90 degree Elbow
7599	C4, C6 TT12 Ball Valve
7602	C4 8" Black Cylinder
7611	C4 Cup Plate
7614	C4 Push Plate
7612	C4 Door
7617	C4 Return Spring
7618	C4 Shaft
7619	C4 Top Bearing
7642	C4, C6 TT12 MJV-3 Air Clippard Valve
7708	C4, C6 3/8" Push-on Connector
7719	C4, C6, TT12 Muffler
7749	C4, C6, TT12 S1205 Safety Valve
7847	C4, C6 Handle
7853	C4 Air Tube / Galvanized Pipe
7859	C4 Neoprene Cup
7860	C4 8" Large O-Ring
7901	C4, C6 Reducer Bushing
7902	C4, C6, TT12 1-1/4" 12 Jam Nut
7903	C, C6, TT12 1-1/8" Washer
7904	C4, C6, TT12, TT25 3/8" Ball Bearing Switch
7905	C4, C6, TT12, TT25 Safety Switch Spring
7906	C4, C6, TT12, TT25 1/4" x 2-1/4" Clevis Pin
7907	C4, C6, TT12, TT25 3/8" ID x 1/2" OD Bearing
7908	C4, C6, TT12, TT25 1/4" x 1-1/2" Clevis Pin
7909	C4, C6, TT12, TT25 3/32" x 1/2" Cotter Pin
7914	C4 Drain Hose Adaptor
7917	C4, C6, TT12, TT25 3/8" x 2-1/4" Grade 8 Tap Bolt
7918	C4, C6, TT12, TT25 3/8" x 16 Stover Nut
7938	C4, C6, TT12, TT25 5/16" Flat Washer
7940	C4, C6, TT12 1/4" Air Hose Assembly



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

C-6 Crusher



1-2

OIL FILTER CRUSHERS

C-6 Pneumatic Oil Filter Crusher for light truck diesel and SUV filters.

- Reduces filters by 75% of original size, and removes 95% of the free-flowing oil so it can be recycled.
- Large crushing chamber: accepts filters up to 10" tall x 7" diameter.
- Only one moving part, a 2" shaft.
- Safety door - crusher will not operate if door is opened.
- Cycle time: 27 seconds.
- Air requirement: 125 to 175 PSI.
- Air regulator not needed.
- Oiler and lubricator not needed.
- All parts in contact with air are rust proof.
- Optional stand (sold separately).
- Overall size on stand: 75" high, 36" wide, 26" deep.
- Lifetime warranty on housing, one year limited on all other parts.
- 12" Flexible drain hose included.
- Overall weight on stand 170 lbs. (Shipping weight 182 lbs. Trucked on pallet.)

New Crushers

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008207	C-6 Pneumatic SUV Oil Filter Crusher	221 (100.2)
007590	Smaller Crusher Stand for C-4 and C-6 Oil Filter Crushers	101 (45.9)
007610	C-6 Pneumatic SUV Oil Filter Crusher with #007590 Crusher Stand	281 (127.5)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



C-6 Crusher

C-6 Pneumatic Oil Filter Crusher for light truck diesel and SUV filters.

Dimensions and System Options

Repair Parts

MODEL NO.	DESCRIPTION
007589	C-4, C6 90 degree Elbow
007599	C-4, C6 TT12 Ball Valve
007628	C-6 Cup Plate
007632	C-6 Push Plate
007629	C-6 Door
007858	C-6 Return Spring
007633	C-6 Shaft
007634	C-6 Top Bearing
007642	C-4, C-6 TT-12 MJV-3 Air Clippard Valve
007708	C-4, C-6 3/8" Push-on Connector
007719	C-4, C-6, TT-12 Muffler
007749	C-4, C-6, TT-12 S1205 Safety Valve
007847	C-4, C-6 Handle
007861	C-6 Neoprene Cup
007862	C-6 10" Large O-Ring
007901	C-4, C-6 Reducer Bushing
007902	C-4, C-6, TT-12 1-1/4" 12 Jam Nut
007903	C, C-6, TT-12 1-1/8" Washer
007904	C-4, C-6, TT-12, TT-25 3/8" Ball Bearing Switch
007905	C-4, C-6, TT-12, TT-25 Safety Switch Spring
007906	C-4, C-6, TT-12, TT-25 1/4" x 2-1/4" Clevis Pin
007907	C-4, C-6, TT-12, TT-25 3/8" ID x 1/2" OD Bearing
007908	C-4, C-6, TT-12, TT-25 1/4" x 1-1/2" Clevis Pin
007909	C-4, C-6, TT-12, TT-25 3/32" x 1/2" Cotter Pin
007917	C-4, C-6, TT-12, TT-25 3/8" x 2-1/4" Grade 8 Tap Bolt
007918	C-4, C-6, TT-12, TT-25 3/8" x 16 Stover Nut
007938	C-4, C-6, TT-12, TT-25 5/16" Flat Washer
007940	C-4, C-6, TT-12 1/4" Air Hose Assembly



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

TT-12 Crusher



1-3

OIL FILTER CRUSHERS

Pneumatic Oil Filter Crusher for tractor trailer and truck filters.

- Reduces filters by 75% of original size, and removes 95% of the free-flowing oil so it can be recycled.
- Only one moving part, a 2" shaft.
- Safety door - crusher will not operate if door is opened.
- Cycle time: 23 seconds.
- Air requirement - 125 to 175 PSI.
- Air regulator not needed.
- Oiler and lubricator not needed.
- All parts in contact with air are rust proof.
- Size: 51" high, 18" wide, 17" deep.
- Lifetime warranty on housing, one year limited on all other parts.
- Optional Stand.
- Crusher weight 358 lbs. With stand 470 lbs. (Shipping weight 530 lbs. Trucked on pallet.)
- Large crushing chamber: accepts filters up to 16" tall x 9" diameter.

New Crushers

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007715	TT12 Pneumatic Truck Oil Filter Crusher	418 (189.6)
007550	Large Crusher Stand with Reservoir for C-6, TT12 and TT25 Oil Filter Crushers	172 (78)
008210	TT12 Pneumatic Truck Oil Filter Crusher with #007550 Crusher Stand with Reservoir	530 (240.4)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

Pneumatic Oil Filter Crusher for tractor trailer and truck filters.

Dimensions and System Options

Repair Parts

Model No.	Description
007599	C4, C6 TT12 Ball Valve
007644	TT12 Cylinder
007604	TT12 Bottom Plate
007863	TT12, TT25 Push Plate
007799	TT12 Door
007796	TT12 Return Spring
007800	TT12 Shaft
007642	C4, C6 TT12 MJV-3 Air Clippard Valve
007719	C4, C6, TT12 Muffler
007749	C4, C6, TT12 S1205 Safety Valve
007793	TT12 Handle
007856	TT12 1/2" OD x .062 Tubing
007795	TT12 12" Piston Cup
007794	TT12 12" Large O-Ring
007902	C4, C6, TT12 1-1/4" 12 Jam Nut
007903	C, C6, TT12 1-1/8" Washer
007904	C4, C6, TT12, TT25 3/8" Ball Bearing Switch
007905	C4, C6, TT12, TT25 Safety Switch Spring
007906	C4, C6, TT12, TT25 1/4" x 2-1/4" Clevis Pin
007907	C4, C6, TT12, TT25 3/8" ID x 1/2" OD Bearing
007908	C4, C6, TT12, TT25 1/4" x 1-1/2" Clevis Pin
007909	C4, C6, TT12, TT25 3/32" x 1/2" Cotter Pin
007917	C4, C6, TT12, TT25 3/8" x 2-1/4" Grade 8 Tap Bolt
007918	C4, C6, TT12, TT25 3/8" x 16 Stover Nut
007938	C4, C6, TT12, TT25 5/16" Flat Washer
007940	C4, C6, TT12 1/4" Air Hose Assembly



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

TT-25 CRUSHER



1-4


OIL FILTER CRUSHERS

Electric Hydraulic Oil Filter Crusher for tractor trailer and truck filters.

- Reduces filters by 75% of original size, and removes 95% of the free-flowing oil so it can be recycled.
- Large crushing chamber: accepts filters up to 16" tall x 9" diameter.
- Automatic crushing cycle.
- Cycle time: 1 minute.
- Pump: 1 Phase/ 230V/60Hz or 1 Phase 220V/50Hz.
- Safety door - crusher will not operate if door is opened.
- Overall size on optional stand: 87" high, 23" wide, 31" deep.
- Lifetime warranty on housing, one year limited on all other parts.
- Size: 50" high, 18" wide, 31" deep.
- Optional Stand.
- Crusher weight 404 lbs. With stand 516 lbs. (Shipping weight 576 lbs. Trucked on pallet.)

New Crushers

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008215	TT25 Electric Hydraulic Oil Filter Crusher, 60Hz	464 (210.5)
007550	Large Crusher Stand with Reservoir for C-6, TT12 and TT25 Oil Filter Crushers	172 (78)
007720	TT25 Electric Hydraulic Oil Filter Crusher with #007550 Crusher Stand with Reservoir	576 (261.3)




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Electric Hydraulic Oil Filter Crusher for tractor trailer and truck filters.

Dimensions and System Options

Repair Parts

MODEL NO.	DESCRIPTION
007714	TT25 9/16" MJIC x 9/16" Elbow Adaptor
007863	TT12, TT25 Push Plate
007929	TT25 Ram
007734	TT25 Pump, 60Hz
011943	TT25 Pump, 50Hz
007899	TT25 Handle Spring
007904	C4, C6, TT12, TT25 3/8" Ball Bearing Switch
007905	C4, C6, TT12, TT25 Safety Switch Spring
007906	C4, C6, TT12, TT25 1/4" x 2-1/4" Clevis Pin
007907	C4, C6, TT12, TT25 3/8" ID x 1/2" OD Bearing
007908	C4, C6, TT12, TT25 1/4" x 1-1/2" Clevis Pin
007909	C4, C6, TT12, TT25 3/32" x 1/2" Cotter Pin
007917	C4, C6, TT12, TT25 3/8" x 2-1/4" Grade 8 Tap Bolt
007918	C4, C6, TT12, TT25 3/8" x 16 Stover Nut
007938	C4, C6, TT12, TT25 5/16" Flat Washer



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Filter Crusher Stands



1-5

OIL FILTER CRUSHERS

For all truck and automotive filter crushers.

Model 007550

- Industrial grade steel.
- Drain shelf for storing filters.
- 2" NPT drain for piping to other storage vessels.
- Accomodates a 30-gallon drum.
- Can be used with most filter crushers manufactured by BJ Enterprises.
- Vibration pads and provisions for securing to the floor.

Model 007590

- Designed for use with C-4 and C-6 oil filter crushers.
- Industrial grade steel.
- Vibration pads and provisions for securing to the floor.

New Stands

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007550	Large Crusher Stand with Reservoir for C-6, TT12 and TT25 Oil Filter Crushers	153 (69.4)
007590	Small Crusher Stand for C-4 and C-6 Oil Filter Crushers	101 (45.9)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

For all truck and automotive filter crushers.


Dimensions and System Options

Automotive Crushers

MODEL NO.	DESCRIPTION
007605	C-4 Pneumatic Automobile Oil Filter Crusher
008203	C-4 Pneumatic Automobile Oil Filter Crusher with #007590 Crusher Stand
008207	C-6 Pneumatic SUV Oil Filter Crusher
007610	C-6 Pneumatic SUV Oil Filter Crusher with #007590 Crusher Stand


Truck Crushers

MODEL NO.	DESCRIPTION
007715	TT12 Pneumatic Truck Oil Filter Crusher
008210	TT12 Pneumatic Truck Oil Filter Crusher with #007550 Crusher Stand with Reservoir
008215	TT25 Electronic Over Hydraulic Oil Filter Crusher
007720	TT25 Electronic Over Hydraulic Oil Filter Crusher with #007550 Crusher Stand with Reservoir



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Gauges



**Numbers decrease as fluid level lowers indicating how many inches are left until the tank is empty.
For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.**

- One gauge accommodates tanks up to 99".
- Measures from 99" - 0".
- 2" NPT threads.
- Large number display.
- Molded housing.
- Direct drive.
- Nickel-plated brass chain.
- Oversized aluminum float assembly rotates to prevent chain entanglement.
- For use with oil, waste oil, diesel fuel, antifreeze, and most liquids with a high flash point.
- New swivel allows easy orientation of gauge after installation.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007600	Black Knight® 99" Liquid Level Gauge for New Product	3.5 (1.6)
008164	Black Knight® 99" Liquid Level Gauge for New Product with Vertical Float	3.5 (1.6)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Numbers decrease as fluid level lowers indicating how many inches are left until the tank is empty.
For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.


Dimensions and System Options

Floats

MODEL NO.	DESCRIPTION
007615	1½" Vertical Float
007616	2" Horizontal Float

Other Accessories

MODEL NO.	DESCRIPTION
007551	Chain, #2 Ball
007552	Eyelet, Brass
007639	Clear Acrylic Cover



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



**Numbers decrease as fluid level lowers indicating how many centimeters are left until the tank is empty.
For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.**

- Large number display.
- Measures from 0 cm to 365 cm (approximately 3.65 m).
- Mechanical operation. No batteries required.
- Weather resistant durable molded housing.
- 2" NPT threads and 2" BSPT threads.
- Nickel-plated brass chain.
- Aluminum horizontal float (vertical float optional).
- Easy-to-read digital readout.
- Durable direct drive chain.
- Less expensive than comparable models.
- Faster than sticking the tank for level reading.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008743	Metric Black Knight® Horizontal Float, 2" BSPT	2.5 (1.1)
010176	Metric Black Knight® Horizontal Float, 2" NPT	2.5 (1.1)
010753	Metric Black Knight® Vertical Float, 2" NPT	2.5 (1.1)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Metric Black Knight®

Numbers decrease as fluid level lowers indicating how many centimeters are left until the tank is empty. For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.


Dimensions and System Options

Floats

MODEL NO.	DESCRIPTION
007615	1½" Vertical Float
007616	2" Horizontal Float

Other Accessories

MODEL NO.	DESCRIPTION
007551	Chain, #2 Ball
007552	Eyelet, Brass



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

**Numbers decrease as fluid level rises indicating how many inches are left until the tank is full.
For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.**

- One gauge accommodates tanks up to 99".
- Large number display.
- Molded housing.
- Direct drive.
- 2" NPT threads.
- Nickel-plated brass chain.
- Oversized aluminum float assembly rotates to prevent chain entanglement.
- For use with oil, waste oil, diesel fuel, antifreeze, and most liquids with a high flash point.
- New swivel allows easy orientation of gauge after installation.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007665	Red Fox® 99" Liquid Level Gauge Horizontal Float	3.5 (1.6)
008566	Red Fox® 99" Liquid Level Gauge Vertical Float 2" NPT	3.5 (1.6)

*Specify tank depth (in inches) and riser height (in inches)



WARNING: Cancer and Reproductive
Harm—www.P65Warnings.ca.gov

Numbers decrease as fluid level rises indicating how many inches are left until the tank is full.
 For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.


Dimensions and System Options

Floats

MODEL NO.	DESCRIPTION
007615	1½" Vertical Float
007616	2" Horizontal Float

Other Accessories

MODEL NO.	DESCRIPTION
007551	Chain, #2 Ball
007552	Eyelet, Brass
007639	Clear Acrylic Cover



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Liquid Level Gauges – numbers decrease as fluid level rises indicating how many centimeters are left until the tank is full. For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.

- One gauge accommodates tanks up to 365 cm.
- Large number display.
- Mechanical operation. No batteries required.
- Weather resistant durable molded housing.
- 2" NPT threads and 2" BSPT threads.
- Nickel-plated brass chain.
- Easy-to-read digital readout.
- Durable direct drive chain.
- Less expensive than comparable models.
- Faster than sticking the tank for level reading.
- Aluminum horizontal float (vertical float optional).

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
010751	Metric Red Fox® Tank Gauge, BSPT	2.5 (1.1)
010752	Metric Red Fox® Vertical, BSPT	2.5 (1.1)
010754	Metric Red Fox® Tank Gauge, NPT	2.5 (1.1)
010755	Metric Red Fox® Vertical, NPT	2.5 (1.1)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Metric Red Fox®

Liquid Level Gauges – numbers decrease as fluid level rises indicating how many centimeters are left until the tank is full. For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.


Dimensions and System Options

Floats

MODEL NO.	DESCRIPTION
007615	1½" Vertical Float
007616	2" Horizontal Float

Other Accessories

MODEL NO.	DESCRIPTION
007551	Chain, #2 Ball
007552	Eyelet, Brass



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

Jarhead Tank Gauge



2-5

TANK GAUGES

For use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Large glass 4 window display.
- Highly visible orange indicator with UV inhibitor.
- 2" NPT (1-1/2" optional).
- Stainless steel rods.
- Aluminum linkage.
- Nitrophyl float.
- Easy installation.



New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007620*	Jarhead Sightglass Tank Gauge with Fractional Indicators for 18"-60" Tank Depth with 2" Tank Fitting	2.0 (0.9)
007621*	Jarhead Sightglass Tank Gauge with Fractional Indicators for 18"-60" Tank Depth with 1 1/2" Tank Fitting	2.0 (0.9)
007622*	Jarhead Sightglass Tank Gauge with Fractional Indicators for 61"-72" Tank Depth with 2" Tank Fitting	2.3 (1.0)
007623*	Jarhead Sightglass Tank Gauge with Fractional Indicators for 61"-72" Tank Depth with 1 1/2" Tank Fitting	2.3 (1.0)
007625*	Jarhead 275 Gallon Sightglass Tank Gauge with 2" Tank Fitting	2.0 (0.9)
007626*	Jarhead 275 Gallon Sightglass Tank Gauge with 1 1/2" Tank Fitting	2.0 (0.9)

*Specify tank depth (in inches) and **riser height (in inches)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Jarhead Tank Gauge

For use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions and System Options

007 Tank Monitors

MODEL NO.	DESCRIPTION
007555*	007 Audible and Visual Tank Monitor with Jarhead Tank Gauge (includes indoor mount control panel, Jarhead Tank Gauge, 2" NPT tank fitting and 12 volt transformer)
009919	007 Audible and Visual Tank Monitor with Jarhead Tank Gauge (includes indoor mount control panel, Jarhead Tank Gauge, 1-1/2" NPT tank fitting and 12 volt transformer)


Sentry Wall Mounted Tank Monitors

MODEL NO.	DESCRIPTION
007685*	Sentry High or Low Wall Mounted Battery Operated Tank Monitor with Built-in 103 Decibel Siren and Jarhead Tank Gauge, 2" NPT tank fitting
007686*	Sentry High or Low Wall Mounted Tank Monitor with Built-in 103 Decibel Siren, Jarhead Tank Gauge, 2" NPT tank fitting and 12 Volt Transformer
009969*	Sentry High or Low Wall Mounted Battery Operated Tank Monitor with Built-in 103 Decibel Siren and Jarhead Tank Gauge, 1-1/2" NPT tank fitting
009972*	Sentry High or Low Wall Mounted Tank Monitor with Built-in 103 Decibel Siren, Jarhead Tank Gauge, 1-1/2" NPT tank fitting and 12 Volt Transformer

*Specify tank depth (in inches) and **riser height (in inches)

Accessories

MODEL NO.	DESCRIPTION
011426	2" Jarhead Adaptor
007829	1-1/2" Jarhead Adaptor
007692	Jarhead Jar



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



JAR Adjustable Jarhead



2-6

TANK GAUGES

For use with oil, waste oil, diesel fuel, antifreeze and other fluids with a high flash point. Adjustable Jarhead that covers range of 18"-72" (46 cm - 182 cm).

- Infinitely adjustable within size range.
- Durable glass housing.
- Highly visible orange indicator.
- Available with 2" NPT, 1½" NPT, 2" BSP, and 1½" BSP.
- 4 ranges of tank depth available: 18"-23", 24"-34", 33"-47", 46"-72", 46 cm-58 cm, 61 cm-86 cm, 84 cm-119 cm, 117 cm-182 cm.
- Scale reading - F-¾-½-¼-E.
- Only mechanical tank gauge that is adjustable by the customer.
- No need for custom factory orders. Four models cover range of 18"-72" (46 cm - 182cm).
- No special skills necessary to install.
- Brass linkages.
- Allen wrenches included to adjust and tighten linkages.
- Aluminum float.

New Adjustable Jarhead

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
009909	Adjustable Jarhead, 2" NPT 18"-23"	2.0 (0.9)
009916	Adjustable Jarhead, 2" NPT 24"-34"	2.0 (0.9)
009918	Adjustable Jarhead, 2" NPT 33"-47"	2.3 (1.0)
009930	Adjustable Jarhead, 2" NPT 46"-72"	2.5 (1.1)
010393	Adjustable Jarhead, 2" BSP 46 cm-58 cm	2.0 (0.9)
010472	Adjustable Jarhead, 2" BSP 61 cm-86 cm	2.0 (0.9)
010473	Adjustable Jarhead, 2" BSP 84 cm-119 cm	2.3 (1.0)
010474	Adjustable Jarhead, 2" BSP 117 cm-182 cm	2.5 (1.1)
010996	Adjustable Jarhead, 1-1/2" NPT 18"-23"	2.0 (0.9)
010997	Adjustable Jarhead, 1-1/2" NPT 24"-34"	2.0 (0.9)
010998	Adjustable Jarhead, 1-1/2" NPT 33"-47"	2.3 (1.0)
010999	Adjustable Jarhead, 1-1/2" NPT 46"-72"	2.5 (1.1)
013638	Adjustable Jarhead, 1-1/2" BSP 84 cm-119 cm	2.3 (1.0)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov




JAR Adjustable Jarhead

For use with oil, waste oil, diesel fuel, antifreeze and other fluids with a high flash point. Adjustable Jarhead that covers range of 18"-72" (46 cm - 182 cm).

Dimensions

Accessories

Model No.	Description
007551	#2 Ball Chain
007552	Eyelet, Brass
007692	Jarhead Jar
007829	Adaptor, 1-1/2" NPT
010009	Adaptor, 2" BSP
011189	Adaptor, 1-1/2" BSP
011426	Adaptor, 2" NPT



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Overfill Tank Gauge



2-7

TANK GAUGES

For use with oil, waste oil, diesel fuel, antifreeze and other fluids with a high flash point.



- Large glass 4 window display.
- Highly visible orange indicator with UV inhibitor.
- 2" NPT and BSP
- 1-1/2" NPT and BSP
- Nickel-plated brass chain. Field adjustable to 24" from top of tank. (extended chain available).
- Aluminum float.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007640*	Overfill Guard Sightglass Gauge with 2" NPT Tank Fitting	1.5 (0.7)
007641*	Overfill Guard Sightglass Gauge with 1-1/2" NPT Tank Fitting	1.5 (0.7)
011179*	Overfill Guard Sightglass Gauge with 2" BSP Tank Fitting	1.5 (0.7)
011180*	Overfill Guard Sightglass Gauge with 1-1/2" BSP Tank Fitting	1.5 (0.7)

*Specify tank depth (in inches) and **riser height (in inches)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Overfill Tank Gauge

For use with oil, waste oil, diesel fuel, antifreeze and other fluids with a high flash point.

Dimensions and System Options

007 Tank Monitors

MODEL NO.	DESCRIPTION
007565	007 Audible and Visual Tank Monitor with Overfill Tank Gauge (includes indoor mount control panel, Overfill Tank Gauge and 12 volt transformer)
009965	007 Audible and Visual Tank Monitor with Overfill Tank Gauge, 1-1/2" NPT tank fitting (includes indoor mount control panel, Overfill Tank Gauge and 12 volt transformer)

Sentry Wall Mounted Tank Monitors

MODEL NO.	DESCRIPTION
007680	Sentry High or Low Wall Mounted Battery Operated Tank Monitor with Built-in 103 Decibel Siren and Overfill Tank Gauge
007681	Sentry High or Low Wall Mounted Tank Monitor with Built-in 103 Decibel Siren, Overfill Tank Gauge and 12 Volt Transformer
009973	Sentry High or Low Wall Mounted Battery Operated Tank Monitor with Built in 103 Decibel Siren, and Overfill Tank Gauge, 1-1/2" NPT tank fitting
009975	Sentry High or Low Wall Mounted Tank Monitor with Built-in 103 Decibel Siren, Overfill Tank Gauge and 12 Volt Transformer, 1-1/2" NPT tank fitting

Accessories

MODEL NO.	DESCRIPTION
007829	Adaptor, 1-1/2"
011426	Adaptor, 2"
007551	Chain, #2 Ball
007552	Eyelet, Brass
007866	Jar, Overfill



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Leak Guard Tank Gauge



2-8

TANK GAUGES

For use with oil, waste oil, diesel fuel, antifreeze and other fluids with a high flash point.



- Large glass 4 window display.
- Highly visible orange indicator with UV inhibitor.
- 2" NPT and BSP
- 1-1/2" NPT and BSP
- Nickel-plated brass chain. Field adjustable to 72" from top of tank (extended chain available).
- Aluminum float.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007635	Leak Guard Sightglass Gauge for Double Wall Tanks with 2" Male NPT Tank Fitting	1.5 (0.7)
007636	Leak Guard Sightglass Gauge for Double Wall Tanks with 1 1/2" Male NPT Tank Fitting	1.5 (0.7)
010002	Leak Guard Sightglass Gauge for Double Wall Tanks with 2" Male NPT Tank Fitting and Extended Chain	1.5 (0.7)
011177	Leak Guard Sightglass Gauge for Double Wall Tanks with 2" Male BSP Tank Fitting	1.5 (0.7)
011178	Leak Guard Sightglass Gauge for Double Wall Tanks with 1 1/2" Male BSP Tank Fitting	1.5 (0.7)
014287	Leak Guard Sightglass Gauge for Double Wall Tanks with 1 1/2" Male NPT Tank Fitting and Extended Chain	1.5 (0.7)
014556	Leak Guard Sightglass Gauge for Double Wall Tanks with 2" Female NPT Tank Fitting	1.5 (0.7)





Leak Guard Tank Gauge

For use with oil, waste oil, diesel fuel, antifreeze and other fluids with a high flash point.

Dimensions and System Options

007 Tank Monitors

MODEL NO.	DESCRIPTION
007560	007 Audible and Visual Tank Monitor with Leak Guard Tank Gauge (includes indoor mount control panel, Leak Guard Tank Gauge and 12 volt transformer)

Sentry Wall Mounted Tank Monitors

MODEL NO.	DESCRIPTION
007675	Sentry High or Low Wall Mounted Battery Operated Tank Monitor with Built-in 103 Decibel Siren and Leak Guard Tank Gauge
007676	Sentry High or Low Wall Mounted Tank Monitor with Built-in 103 Decibel Siren, Leak Guard Tank Gauge and 12 Volt Transformer
009967	Sentry High or Low Wall Mounted Battery Operated Tank Monitor with Built-in 103 Decibel Siren and Leak Guard Tank Gauge, 1-1/2" Male NPT tank fitting
009970	Sentry High or Low Wall Mounted Battery Operated Tank Monitor with Built-in 103 Decibel Siren, Leak Guard Tank Gauge and 12 Volt Transformer, 1-1/2" Male NPT tank fitting

Accessories

MODEL NO.	DESCRIPTION
007551	Chain, #2 Ball
007552	Eyelet, Brass
011426	Adaptor, 2"
007865	Jar, Leak



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Seasee Drum Gauge



2-9

TANK GAUGES

55 Gallon Horizontal Drum Gauge for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.



- Zinc-plated aluminum faucet.
- Zinc-plated steel drum gauge with visible fluid level.
- Quick disconnect gauge fitting.
- Gauge can be removed during installation/removal from drum.
- For most fluids except concentrated acids or bases.
- Fits 55 gallon drums with $\frac{3}{4}$ " NPT bung.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
010528	55 Gallon Horizontal Drum Gauge	2.0 (0.9)

Construction

Gauge	Clear polymer
Faucet	Aluminum/polymers
Body	Steel
Quick disconnect	Brass/steel




WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Seasee Drum Gauge

55 Gallon Horizontal Drum Gauge for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

**Numbers decrease as fluid level lowers indicating how many inches are left until the tank is empty.
For use with diesel exhaust fluid (DEF).**

- One gauge accommodates tanks up to 99".
- Measures from 99" - 0".
- 2" NPT Threads.
- Large number display.
- Molded housing.
- Direct drive.
- Stainless steel chain.
- Oversized, DEF compatible anodized aluminum float assembly rotates to prevent chain entanglement.
- For use with diesel exhaust fluid (DEF).
- New swivel allows easy orientation of gauge after installation.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
011809	DEF Black Knight® 99" Liquid Level Gauge for Diesel Exhaust Fluid	3.3 (1.5)





DEF Black Knight® LLG

Numbers decrease as fluid level lowers indicating how many inches are left until the tank is empty.
For use with diesel exhaust fluid (DEF).


Dimensions and System Options

Floats

MODEL NO.	DESCRIPTION
013717	Float, DEF, 2" Horizontal, Anodized Assembly

Other Accessories

MODEL NO.	DESCRIPTION
007639	Clear Polycarbonate Cover



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Clearly Gauge® LLG



2-11


TANK GAUGES

Numbers decrease as fluid level lowers indicating how many inches are left until the tank is empty.
For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.

- One gauge accommodates tanks up to 72" .
- Measures from 72" - 0" .
- 2" NPT threads.
- Molded housing.
- Direct drive.
- Nickel-plated brass chain.
- Oversized aluminum float assembly rotates to prevent chain entanglement.
- For use with oil, waste oil, diesel fuel, antifreeze, and most liquids with a high flash point.
- Greater depths available on request.

New Gauges

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
013962	Clearly Gauge® 72" Liquid Level Gauge	.95 (.43)
015184	Clearly Gauge® 72" Liquid Level Gauge with Vertical Float	.95 (.43)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Clearly Gauge® LLG

Numbers decrease as fluid level lowers indicating how many inches are left until the tank is empty.
For use with oil, waste oil, diesel fuel, antifreeze, and other fluids with a high flash point.




Dimensions and System Options

Floats

MODEL NO.	DESCRIPTION
007615	1½" Vertical Float
007616	1½" Horizontal Float

Other Accessories


MODEL NO.	DESCRIPTION
007551	Chain, #2 Ball
007552	Eyelet, Brass



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Tank Gauges & Alarms



007 Tank Alarm



3-1

TANK GAUGES AND ALARMS

High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Avoid costly overflows or untimely shortages.
- Supervised system.
- Low voltage.
- Strobe and siren.
- Can drive up to 10 solenoid valves.
- Easy installation.
- Maximum milliamp load is 750 mA. Do not exceed.

New Gauges and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007575	007 Audible and Visual Tank Gauge (includes indoor mount control panel, remote tank sensor, 10' lead wire and 12 volt transformer)	4.0 (1.8)
007555*	007 Audible and Visual Tank Gauge with Jarhead Tank Gauge (includes indoor mount control panel, Jarhead Tank Gauge, and 12 volt transformer) with 2" NPT Tank Fitting	5.0 (2.3)
007560 009963	007 Audible and Visual Tank Gauge with Leak Guard Tank Gauge (includes indoor mount control panel, Leak Guard tank gauge and 12 volt transformer) with 2" NPT Tank Fitting with 1-1/2" NPT Tank Fitting	5.0 (2.3)
007565** 009965**	007 Audible and Visual Tank Gauge with Overfill Tank Gauge (includes indoor mount control panel, Overfill tank gauge and 12 volt transformer) with 2" NPT Tank Fitting with 1-1/2" NPT Tank Fitting	5.0 (2.3)
008295	Audible and Visual Tank Monitor with 12 volt transformer (does not include a tank sensor)	5.0 (2.3)
010304	007 Tank Alarm with built-in 103 Decibel Siren and Strobe Light, Remote 55 Gallon Drum High Level Sensor and 12 volt Transformer	2.8 (1.3)
010305	007 Tank Alarm with built-in 103 Decibel Siren and Strobe Light, Remote 55 Gallon Drum Low Level Sensor with Seal and 12 volt Transformer	3.0 (1.4)
010306	007 Tank Alarm with built-in 103 Decibel Siren and Strobe Light, Remote 55 Gallon Drum High Level Sensor with Seal and 12 volt Transformer	2.8 (1.3)
011875	007 Audible and Visual Tank Gauge, 007 SV Solenoid Valve (includes indoor mount control panel, remote tank sensor, 10' lead wire, pneumatic shut off solenoid valve and two 12 volt transformers)	9.0 (4.1)

*Specify tank depth (in inches) and **riser height (in inches).



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
007595	12 volt Transformer
007660	Remote Tank Sensor
007936*	Remote Jarhead Tank Sensor with 2" tank fitting
008206*	Remote Jarhead Tank Sensor with 1-1/2" tank fitting
007655	Remote Leak Guard Tank Sensor with 2" tank fitting
007656	Remote Leak Guard Tank Sensor with 1-1/2" tank fitting
007742*	Remote Overfill Guard Tank Sensor with 2" tank fitting
007743**	Remote Overfill Guard Tank Sensor with 1-1/2" tank fitting
007695	Strobe Light
007690	Siren - 107 Decibels
007645	Heavy Duty Power Relay - 30 amp or 1-1/2" HP at 120 or 240 vac
009503	Remote 55 Gallon Drum High Level Sensor
009980	Remote 55 Gallon Drum Low Level Sealed Sensor
010000	Remote 55 Gallon Drum High Level Sealed Sensor

*Specify tank depth (in inches) and **riser height (in inches).



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Sentry Tank Alarm



3-2

TANK GAUGES AND ALARMS

High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Avoid costly overflows or untimely inventory shortages.
- Engineered for most single and double walled above ground tanks.
- Common 9-volt battery operated or upgradeable to AC power.
- Alarm sounds for up to four days on a fresh battery.
- Ideal for remote areas where AC power is not accessible.
- Simple installation; easy maintenance.
- New swivel allows easy orientation of gauge after installation.

New Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007670	Sentry High or Low Battery Operated Tank Alarm with Built-in 103 Decibel Siren	2.5 (1.1)
007671	Sentry high or Low Tank Alarm with Built-in 103 Decibel Siren and 12 Volt Transformer	3.5 (1.6)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

Sentry Tank Alarm

High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Sentry Wall Mount



3-3

TANK GAUGES AND ALARMS

High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Avoid costly overflows or untimely inventory shortages.
- Engineered for most single and double walled aboveground tanks.
- Common 9-volt battery operated or upgradeable to AC power.
- Alarm sounds for up to four days on a fresh battery.
- Ideal for remote areas where AC power is not accessible.
- Simple installation; easy maintenance.



Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007675	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren and Leak Guard Tank Sensor, with 2" NPT tank fitting	4.8 (2.2)
007676	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren, Leak Guard Tank Sensor and 12 Volt Transformer, with 2" NPT tank fitting	
007680	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren and Overfill Tank Sensor, with 2" NPT tank fitting	4.0 (1.8)
007681	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren, Overfill Tank Sensor, and 12 Volt Transformer, with 2" NPT tank fitting	5.5 (2.5)
007725	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren, with 2" NPT tank fitting	3.0 (1.4)
007726	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren and 12 Volt Transformer, with 2" NPT tank fitting	
007685*	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren and Jarhead Tank Sensor, with 2" NPT tank fitting	5.5 (2.5)
007686* 009972	Sentry High or Low Wall Mount Battery Operated Tank Alarm with Built-in 103 Decibel Siren, Jarhead Tank Sensor, and 12 Volt Transformer, with 2" NPT tank fitting with 1-1/2" NPT tank fitting	6.5 (3.0)
010713	Sentry Wall Mount Tank Alarm with Built-in 103 Decibel Siren, Remote 55 Gallon Drum High Level Sensor and Battery	3.0 (1.4)

*Specify tank depth (in inches) and **riser height (in inches)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.




Dimensions and System Options

Sensors

MODEL NO.	DESCRIPTION
007661	Remote Tank Sensor
007650	Remote Jarhead Tank Sensor - 2" Tank Fitting
008211	Remote Jarhead Tank Sensor - 1 1/2" Tank Fitting
007657	Remote Leak Guard Tank Sensor - 2" Tank Fitting
007658	Remote Leak Guard Tank Sensor - 1 1/2" Tank Fitting
007740	Remote Overfill Guard Tank Sensor - 2" Tank Fitting
007741	Remote Overfill Guard Tank Sensor - 1 1/2" Tank Fitting
010821	Remote 55 Gallon Drum Low Level Sensor
010824	Remote 55 Gallon Drum High Level Sealed Sensor

Accessories

MODEL NO.	DESCRIPTION
007829	Adaptor, 1-1/2" NPT
007689	Adaptor, 2" NPT
007551	Chain, #2 Ball
007552	Eyelet, Brass
007606	Float Sensor
007692	Jar, Jarhead
007865	Jar, Leak
007866	Jar, Overfill



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Diesel Exhaust Fluid Tank Gauge with JARHEAD.

- Indicates level in fractions: empty - $\frac{1}{4}$ - $\frac{1}{2}$ - $\frac{3}{4}$ - full.
- Constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- Available in custom lengths from 12" - 120" (457.2 - 3048 mm).
- Durable silk screen painted scales.
- Visi-Glo® level indicator clearly displayed in the large glass window.
- Available for use with the 007 and Sentry high or low tank gauges.



New Gauges and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008558	Sightglass tank gauge with fractional indicators for 12" - 120" tank depth with 2" NPS connection	2.0 (0.9)
008665	Sightglass tank gauge with fractional indicators for 61" - 120" tank depth with 2" NPS connection	2.3 (1.0)

Construction

Body	Large glass housing
Rods	Stainless steel
Fasteners	Stainless steel
Connectors	Acetal
Linkage	Acetal
Float	DEF Compatible Anodized Aluminum
Seals	Fluorocarbon
Threads	2" / 50.8 mm NPS

Diesel Exhaust Fluid Tank Gauge with JARHEAD.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Diesel Exhaust Fluid OVERFILL Guard Tank Gauge.

- Constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- Stainless steel, field adjustable chain up to 72" (1,828.8 mm).
- Durable silk screen painted graphics.
- Visi-Glo[®] level indicator clearly displayed in the large glass window.
- Available for use with the 007 and Sentry high or low tank alarms.



New Gauges and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008670	Sightglass overfill guard tank gauge with 2" NPS connection	1.5 (.68)

Construction

Body	Large glass housing
Chain	Stainless steel
Fasteners	Stainless steel
Connectors	Acetal
Linkage	Acetal
Float	DEF Compatible Anodized Aluminum
Seals	Fluorocarbon



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



DEF Overfill Guard

Diesel Exhaust Fluid OVERFILL Guard Tank Gauge.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

007 Tank Alarms with DEF JARHEAD Tank Gauges.

- Tank gauge constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- Wall mount tank alarm can be installed up to 350 feet from tank.
- Built-in 103 decibel siren.
- Built-in, highly visible strobe light.
- Tank alarm includes a push button test switch.
- Toggle switch to silence the siren and a flashing LED light warns when siren is muted.
- AC power indicator light.
- DEF Jarhead sightglass tank gauge indicates fluid level in fractions: empty - $\frac{1}{4}$ - $\frac{1}{2}$ - $\frac{3}{4}$ - full.
- Available in custom lengths from 12" - 120" (457.2 - 3048 mm).
- Durable silk screen painted scales.
- Visi-Glo® level indicator clearly displayed in the large glass window.
- Easy to use, adjustable sensor for high or low alarm.

New Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008666	Audible and visual tank alarm with 12-volt transformer and sightglass tank gauge with fractional indicators for 12" - 120" tank depth with 2" NPS connection	10 (4.5)

Construction

Body	Tank Alarm - Weather resistant ABS Tank Gauge - Large glass housing
Rods	Stainless steel
Fasteners	Stainless steel
Connectors	Acetal
Linkage	Acetal
Float	DEF Compatible Anodized Aluminum
Seals	Fluorocarbon
Connections	Tank Alarm - $\frac{1}{2}$ " Romex Connector Tank Gauge - 2" / 50.8 mm NPS threads




WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



DEF 007 Tank Alarm

007 Tank Alarms with DEF JARHEAD Tank Gauges.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

DEF 007 Tank Alarm



3-7

TANK GAUGES AND ALARMS

007 Tank Alarms with DEF OVERFILL Guards.

- Tank gauge constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- Wall mount tank alarm can be installed up to 350 feet from tank.
- Built-in 103 decibel siren.
- Built-in, highly visible strobe light.
- Tank alarm includes a push button test switch.
- Toggle switch to silence the siren and a flashing LED light warns when siren is muted.
- AC power indicator light.
- DEF overfill guard tank gauge has durable silk screen painted graphics.
- Field adjustable length up to 72" (1,828.8 mm).
- Visi-Glo® level indicator clearly displayed in the large glass window.
- Easy to use, adjustable sensor for high or low alarm.

New Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008667	Audible and visual tank alarm with 12-volt transformer and overfill guard tank gauge with 2" NPS connection	7.0 (3.2)

Construction

Body	Tank Alarm - Weather resistant ABS Tank Gauge - Large glass housing
Chain	Stainless steel
Fasteners	Stainless steel
Connectors	Acetal
Linkage	Acetal
Float	DEF Compatible Anodized Aluminum
Seals	Flouorocarbon
Connections	Tank Alarm - ½" Romex Connector Tank Gauge - 2" NPS threads



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

007 Tank Alarms with DEF OVERFILL Guards.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Sentry Wall Mounted Tank Alarms with DEF JARHEAD Tank Gauges.

- Tank gauge constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- Wall mount tank alarm can be installed up to 350 feet from tank.
- Built-in 103 decibel siren.
- Tank alarm includes a push button test switch.
- Toggle switch to silence the siren.
- Available with battery or with optional 12-volt transformer.
- DEF Jarhead sightglass tank gauge indicates fluid level in fractions: empty - $\frac{1}{4}$ - $\frac{1}{2}$ - $\frac{3}{4}$ - full.
- Available in custom lengths from 12" - 120" (457.2 - 3048 mm).
- Durable silk screen painted scales.
- Visi-Glo® level indicator clearly displayed in the large glass window.
- Easy to use, adjustable sensor for high or low alarm.

New Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008677	Audible tank alarm, battery operated, with sightglass tank gauge with fractional indicators for 12" - 120" tank depth with 2" NPS connection	5.5 (2.5)
008664	Audible tank alarm, with 12-volt transformer and sightglass tank gauge with fractional indicators for 12" - 120" tank depth with 2" NPS connection	6.5 (2.9)

Construction

Body	Tank Alarm - Weather resistant ABS Tank Gauge - Large glass housing
Rods	Stainless steel
Fasteners	Stainless steel
Connectors	Acetal
Linkage	Acetal
Float	DEF Compatible Anodized Aluminum
Seals	Fluorocarbon
Connections	Tank Alarm - $\frac{1}{2}$ " Romex Connector Tank Gauge - 2" / 50.8 mm NPS threads




WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

Sentry Wall Mounted Tank Alarms with DEF JARHEAD Tank Gauges.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
008673	DEF Remote Jarhead Sensor



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Sentry Wall Mounted Tank Alarms with DEF OVERFILL Guards.

- Tank gauge constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- DEF overflow guard tank gauge has durable silk screen painted graphics.
- Available with field adjustable chain up to 72" (1,828.8 mm).
- Visi-Glo® level indicator clearly displayed in the large glass window.
- Easy to use, adjustable sensor for high or low alarm.
- Tank gauge constructed from materials 100% compatible with Diesel Exhaust Fluid (DEF).
- Wall mount tank alarm can be installed up to 350 feet from tank.
- Built-in 103 decibel siren.
- Tank alarm includes a push button test switch.
- Toggle switch to silence the siren.
- Available with battery or with optional 12-volt transformer.

New Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
008668	Audible tank alarm, battery operated, with overflow guard tank gauge with 2" NPS connection	5.5 (2.5)
008669	Audible tank alarm, with 12-volt transformer and overflow guard tank gauge with 2" NPS connection	5.5 (2.5)

Construction

Body	Tank Alarm - Weather resistant ABS Tank Gauge - Large glass housing
Rods	Stainless steel
Fasteners	Stainless steel
Connectors	Acetal
Linkage	Acetal
Float	DEF Compatible Anodized Aluminum
Seals	Fluorocarbon
Connections	Tank Alarm - ½" Romex Connector Tank Gauge - 2" / 50.8 mm NPS threads



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

Sentry Wall Mounted Tank Alarms with DEF OVERFILL Guards.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
008674	DEF Remote Overfill Guard Sensor



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

55 Drum Alert



3-10

TANK GAUGES AND ALARMS

Low and High Drum Alert.

- Waterproof self-contained housing to ensure contaminate-free monitoring.
- Vented design.
- 9-volt battery powered, provided.
- 103 decibel alarm siren.
- Yellow LED low battery indicator light.
- Audible low battery indicator chirp.
- On/Off/Test switch.
- PVC and ABS plastics construction.
- Not recommended for liquids with a specific gravity less than .85.
- Fits in 3/4" NPT vent opening.
- UL Buna N sensor.
- Hi level actuation point = 3"
Low level actuation point = 2"
- Simple installation.
- Easy battery replacement.
- Audible alert.
- Housing can be rotated for best viewing orientation.
- Less expensive than comparable monitors.
- 2 plus year battery life.
- Alarm sounds for 12 plus hours.

New 55 Gallon Drum Alert

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
009952	Drum "55" Alert Low	1.0 (0.45)
009953	Drum "55" Alert High	.66 (0.3)
013883	SHM1 Outdoor Tank Monitor with Remote Sensor	1.35 (0.6)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

55 Drum Alert

Low and High Drum Alert.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



55 Drum Alarm



3-11

TANK GAUGES AND ALARMS

Low, 007 and SENTRY 55 gallon drum alarm.

- Compact low profile sensor housing.
- Vented or sealed design.
- Waterproof cord grip and housing to prevent external contamination of barrel contents.
- 10 foot sensor leads for convenient installation to SENTRY or 007 control panels.
- Not recommended for liquids with a specific gravity less than .85.
- Fits in 3/4" NPT vent opening.
- UL Buna N sensor.
- Hi level actuation point = 3"
Low level actuation point = 32"
- Interfaces with existing SENTRY or 007 tank monitors.
- Combined with a SENTRY or 007 tank monitors, multiple barrels can be monitored at the same time (additional remote barrel sensors required).
- Less expensive than comparable monitor.

New 007 55 Gallon Drum Alarm

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
009503	Remote 55 Gallon Drum High Level Alarm	.25 (0.1)
009980	Remote 55 Gallon Drum Low Level Sealed Alarm	.45 (0.2)
010000	Remote 55 Gallon Drum High Level Sealed Alarm	.25 (0.1)

New SENTRY 55 Gallon Drum Alarm

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
010821	Remote 55 Gallon Drum Low Level Alarm	.45 (0.2)
010824	Remote 55 Gallon Drum High Level Sealed Alarm	.25 (0.1)



**High
Alarm**

Low Alarm




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

55 Drum Alarm

Low, 007 and SENTRY 55 gallon drum alarm.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

FNTM Drum Gauge



3-12

TANK GAUGES AND ALARMS

FNTM 55 Gallon Drum Gauge

- Waterproof self-contained housing to ensure contaminate-free monitoring.
- AA battery powered, provided.
- Touch gauge sides to activate LEDs
- Displays drum levels from 90% to 5%.
- Alerts when the drum level is below 5%
- Low battery alert
- Audible low battery indicator chirp.
- PVC and ABS Plastics Construction.
- FNTM is designed to be used in standard metal 55 gallon drums.
- Fits in 3/4" NPT vent opening.
- Simple installation.
- Easy battery replacement.
- Audible alert.
- Less expensive than comparable monitors
- 2 plus year battery life

New 55 Gallon Drum Alert

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
010807	FNTM 55 Gallon Drum Gauge	1.0 (0.45)




WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



FNTM Drum Gauge

FNTM 55 Gallon Drum Gauge

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Kalkey Commander Tank Controller



3-13

TANK GAUGES AND ALARMS

Tank Controller for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Self-regulating fluid transfer system.
- Provides automatic re-filling of monitored tank.
- Prevents costly tank overfills.
- Built in overflow monitoring-103 decibel alarm siren and flashing LED.
- Push to fill button provides instant topping off of monitored tank.
- Engineered for most single or double wall tanks with 2" NPT bung opening.
- Designed for tank depths between 24"-78" (610 mm-1981 mm).
- Requires one air powered diaphragm pump not included.
- System shuts off air to diaphragm pump and oil flow to day tank when high level sensor is tripped.
- System includes: Tank mounted controller, air solenoid valve, fluid control valve, 115 volt ac adaptor, 25 ft of cabling.
- Tank depth and riser height information required at time of order.
- New swivel allows easy orientation of gauge after installation.

Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
010613	Kalkey Commander Tank Controller	14 (6.4)





WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Kalkey Commander Tank Controller

Tank Controller for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Kaltey Commander Tank Controller Wall Mount



3-14

TANK GAUGES AND ALARMS

Tank Controller for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Self-regulating fluid transfer system.
- Provides automatic re-filling of monitored tank.
- Prevents costly tank overfills.
- Built in overflow monitoring-103 decibel alarm siren and flashing LED.
- Push to fill button provides instant topping off of monitored tank.
- Engineered for most single or double wall tanks with 2" NPT bung opening.
- Designed for tank depths between 24"-78" (610 mm-1981 mm).
- Requires one air powered diaphragm pump not included.
- System shuts off air to diaphragm pump and oil flow to day tank when high level sensor is tripped.
- System includes: wall mounted controller, air solenoid valve, fluid control valve, 115 volt ac adaptor, 25 ft of cabling.
- Tank depth and riser height information required at time of order.

Monitors and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
010614	Kaltey Commander Wall Mount Tank Controller	14 (6.4)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov





Kaltey Commander Tank Controller Wall Mount

Tank Controller for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
013752	Kaltey Commander Wall Mount Tank Controller Remote Sensor



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



MK6 Tank Alarm



3-15

TANK GAUGES AND ALARMS

High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Monitor up to 6 tanks independently.
- Tank probes sold separately
- Avoid costly overflows or untimely shortages.
- Supervised system.
- Low voltage.
- Strobe and siren.
- 6 independent LED displays
- to indicate which circuit is in alarm.
- Easy installation.
- Maximum milliamp load is 750 mA.
- Capable of driving a solenoid valve for each tank monitored.

New Gauges and Alarms

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
014509	MK6 Audible and Visual Tank Gauge (includes indoor mount control panel, and 12 volt transformer)	4.0 (1.8)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



MK6 Tank Alarm


High/Low Tank Alarm for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions and System Options

Accessories


MODEL NO.	DESCRIPTION
007595	12 volt Transformer
007660	Remote Tank Sensor
007936*	Remote Jarhead Tank Sensor with 2" tank fitting
008206*	Remote Jarhead Tank Sensor with 1-1/2" tank fitting
007655	Remote Leak Guard Tank Sensor with 2" tank fitting
007656	Remote Leak Guard Tank Sensor with 1-1/2" tank fitting
007742	Remote Overfill Guard Tank Sensor with 2" tank fitting
007743	Remote Overfill Guard Tank Sensor with 1-1/2" tank fitting
007695	Strobe Light
007690	Siren - 107 Decibels
007645	Heavy Duty Power Relay - 30 amp or 1-1/2" HP at 120 or 240 vac
009503	Remote 55 Gallon Drum High Level Sensor
009980	Remote 55 Gallon Drum Low Level Sealed Sensor
010000	Remote 55 Gallon Drum High Level Sealed Sensor

*Specify tank depth (in inches) and riser height (in inches).



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Gauge Accessories



AD 110 Drain Valve



4-1

GAUGE ACCESSORIES

Automatic Drain Valve.

- Automatically drains moisture from air compressor tanks, dryers, after coolers, etc.
- Delivers drier air extending life of tools and pneumatic equipment.
- Eliminates manual draining - fully automatic - no maintenance.
- 230 PSI maximum pressure.
- ¼" NPT ports.
- 6 ft. power cord.
- 115 VAC power.
- Adjustable cycle time from 1 - 45 minutes.
- Adjustable discharge time from .25 - 25 seconds.
- Manual test switch.

New Valves

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007585	AD110 Electronic Drain Valve	1.0 (0.4)

Optional ¼" Y Strainer

Recommended for optimal performance, i.e. scaling, where air compressor rust can occur. Brass, includes screen.

007730	AD Y Strainer	1.0 (0.4)
--------	---------------	-----------



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



AD 110 Drain Valve

Automatic Drain Valve.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

Solenoid Valve System



4-2

GAUGE ACCESSORIES

Keyed Remote Solenoid Valve System controls air supply to equipment with the turn of a key up to 2000 feet away. Helps assure air compressors or oil pumps are idled when unattended.

- Stop unauthorized use of pneumatic equipment.
- Prevent pilferage of bulk oil/ product inventory.
- Low voltage.
- Red LED indicates valve is on/open.
- 12 volt DC, 1/2" NPT ports, 200 PSI max.
- Easy installation.

New Valves

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007630	Keyed Remote Air Solenoid Valve System Control	4.0 (1.8)




WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov



Solenoid Valve System

Keyed Remote Solenoid Valve System controls air supply to equipment with the turn of a key up to 2000 feet away. Helps assure air compressors or oil pumps are idled when unattended.

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

Solenoid Valves



4-3

GAUGE ACCESSORIES

For use with the 007 tank monitor.

007 SV Solenoid Valve

- Low voltage solenoid valve.
- Shuts off air to pump when 007 is in alarm condition.
- Can be located up to 350' away from 007.
- Wall mount transformer included.
- 12V DC.
- 1/2" NPT Ports.
- 10-200 PSI.

007 SVT Solenoid Valve with Timer

- Same as 007 SV with added timer.
- SAVE TIME AND MONEY!
- Shuts off pump, saving labor time and equipment failure due to unattended pump station.
- Simply turn knob to desired time (3-15 min.) and get back to the job.

Heavy Duty 007 Power Relay

- SPDT [N/O or N/C] dry contacts for a variety of applications, i.e. drive electric pumps, turn lights on/off, etc.
- 30 amp or 1-1/2 hp at 120 or 240 VAC

Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007645	Heavy Duty Power Relay for 007 Tank Gauge - 30 AMP or 1 1/2 HP at 120 or 240 VAC	1.0 (0.4)
007570	007 SVT Solenoid Valve with Timer - 12 Volt Electric (includes wall mount transformer)	5.0 (2.3)
007580	007 SV Solenoid Valve - 12 Volt Electric (includes wall mount transformer)	5.0 (2.3)




WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

For use with the 007 tank monitor.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
007595	12 Volt Transformer



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

For all tank gauges.

107-Decibel Siren

- Ideal for remote locations.
- Low voltage.
- Can be located up to 350' away from 007 tank gauge with 18-gauge wire.

Remote Tank Sensor

- Designed for use with Sentry or 007 tank gauge.
- Ideal for 2nd sensor or interstitial space.
- 1/2" x 6" PVC tube can be replaced for monitoring low tank. Please specify 007 or Sentry.
- 2" and 1-1/2" NPT tank fittings available.

Strobe Light

- Low voltage.
- Ideal for remote locations.
- Can be located up to 350' away from 007 tank gauge with 18-gauge wire.

UL Transformer

- Self-resetting.



007 Gauges Accessories

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007695	Strobe Light for 007 Tank Gauge	0.4 (0.2)
007690	Siren for 007 Tank Gauge - 107 Decibels	0.1 (0.04)
007660	Remote Tank Sensor for 007 Tank Gauge	1.5 (0.7)
007936*	Remote Jarhead Tank Sensor for 007 Tank Gauge with 2" Tank Fitting	1.5 (0.7)
008206*	Remote Jarhead Tank Sensor for 007 Tank Gauge with 1 1/2" Tank Fitting	1.5 (0.7)
007655*	Remote Leak Guard Tank Sensor for 007 Tank Gauge with 2" Tank Fitting	2.0 (0.9)
007656*	Remote Leak Guard Tank Sensor for 007 Tank Gauge with 1 1/2" Tank Fitting	2.0 (0.9)
007742*	Remote Overfill Guard Tank Sensor for 007 Tank Gauge with 2" Tank Fitting	2.0 (0.9)
007743*	Remote Overfill Guard Tank Sensor for 007 Tank Gauge with 1 1/2" Tank Fitting	2.0 (0.9)
007595	12 Volt Transformer for 007 and Sentry Tank Gauges	1.5 (0.7)

Sentry Gauge Accessories

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007661	Remote Tank Sensor for Sentry Tank Gauge	1.5 (0.7)
007650*	Remote Jarhead Tank Sensor for Sentry Tank Gauge with 2" Tank Fitting	3.0 (1.4)
008211*	Remote Jarhead Tank Sensor for Sentry Tank Gauge with 1 1/2" Tank Fitting	3.0 (1.4)
007657*	Remote Leak Guard Tank Sensor for Sentry Tank Gauge with 2" Tank Fitting	2.0 (0.9)
007658*	Remote Leak Guard Tank Sensor for Sentry Tank Gauge with 1 1/2" Tank Fitting	2.0 (0.9)
007740*	Remote Overfill Guard Tank Sensor for Sentry Tank Gauge with 2" Tank Fitting	2.0 (0.9)
007741*	Remote Overfill Guard Tank Sensor for Sentry Tank Gauge with 1 1/2" Tank Fitting	2.0 (0.9)
007595	12 Volt Transformer for 007 and Sentry Tank Gauges	1.5 (0.7)

*Specify tank depth (in inches) and **riser height (in inches)





Siren/Sensor/Strobe

For all tank gauges.

Dimensions and System Options

007 Tank Gauges

MODEL NO.	DESCRIPTION
007575	007 Audible and Visual Tank Gauge (includes indoor mount control panel, remote tank sensor, 10' lead wire and 12 volt transformer)
007555*	007 Audible and Visual Tank Gauge with Jarhead Tank Gauge (includes indoor mount control panel, Jarhead Tank Gauge, and 12 volt transformer)
007560	007 Audible and Visual Tank Gauge with Leak Guard Tank Gauge (includes indoor mount control panel, Leak Guard Tank gauge, remote strobe, remote siren, and 12 volt transformer)
007565	007 Audible and Visual Tank Gauge with Overfill Tank Gauge (includes indoor mount control panel, Overfill tank gauge, remote strobe, remote siren, and 12 volt transformer)



Sentry Tank Gauges

MODEL NO.	DESCRIPTION
007670	Sentry High or Low Battery Operated Tank Gauge with Built-in 103 Decibel Siren
007671	Sentry high or Low Tank Gauge with Built-in 103 Decibel Siren and 12 Volt Transformer
007675	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren and Leak Guard Tank Gauge
007676	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren, Leak Guard Tank Gauge and 12 Volt Transformer
007680	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren and Overfill Tank Gauge
007681	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren, Overfill Tank Gauge, and 12 Volt Transformer
007725	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren
007726	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren and 12 Volt Transformer
007685*	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren and Jarhead Tank Gauge
007686*	Sentry High or Low Wall Mounted Battery Operated Tank Gauge with Built-in 103 Decibel Siren, Jarhead Tank Gauge, and 12 Volt Transformer

*Specify tank depth (in inches) and **riser height (in inches)

Accessories

MODEL NO.	DESCRIPTION
007829	Adaptor, 1-1/2" Jarhead
007865	Jar, Leak



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

TM3 Valve



4-5

GAUGE ACCESSORIES

TM3 Air Shut-off Valve for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

- Fully pneumatic - no electronic parts.
- Avoid costly overflows or untimely inventory shortages.
- Ideal for tanks with baffles.
- Engineered for most single or double walled above ground storage tanks.
- Aluminum float is not affected by oils or most other chemicals.
- Shuts off air supply to pumps preventing tank overflows.
- Easy installation.
- Operating range 30-200 PSI.

New Valves

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007700	TM3 Pneumatic Shut Off Valve	4.7 (2.1)



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov

TM3 Air Shut-off Valve for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

Dimensions and System Options


Replacement Parts

MODEL NO.	DESCRIPTION
007553	TM3 Replacement Chain
011425	TM3 Replacement Float
007774	TM3 Weight



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Oil Baron

Safely cleans petroleum spills, making them non hazardous and nonflammable.

When your job involves working with hydrocarbons (including oil, grease and gasoline), you know how tough it is to safely clean up the spills left behind. Oil Baron safely cleans up the spills, rendering them nonhazardous and requiring no special waste disposal.

From service stations to auto repair bays, Oil Baron makes it easy to clean unsightly, unsafe or hazardous messes and spills. It breaks down hydro carbons (gasoline and other petroleum products) to water and carbon dioxide. It can be applied using floor scrubbers, pressure washers or mops with no special hazardous waste disposal required.



The advantages of Oil Baron:

- Breaks down hydrocarbons (including gasoline) to water and carbon dioxide
- Cuts through the tough oil, grease, carbon and other spills for superior results
- Microbial action digests hydrocarbon mess
- No oil or greasy residue left behind
- Surfaces are clean, dry and oil-free for ideal traction
- Quick drying and available in an easy-to-use spray or concentrate
- Apply with mops, garden sprayer, auto floor scrubbers and pressure washers
- Less expensive and lasts longer compared to conventional cleaners and degreasers

Works on these surface areas:

- Concrete, tile, and metal
- Urethane, acrylic and latex paint
- VCT and waxed floors
- Plexi-glass, epoxy, plastic and rubber

Nonhazardous:

- Non-corrosive, fragrance-free product
- Significantly reduces the ability of flammable hydrocarbons to ignite



Oil Baron

Safely cleans petroleum spills, making them non hazardous and nonflammable.

Usage/Dilution Ratio Chart

Applications & Ratios

	HEAVY DUTY	MEDIUM DUTY	LIGHT DUTY
Floor Scrubber	1:30	1:30	1:40
Mopping	1:05	1:10	1:15
Degreasing	1:2	1:4	1:8
Pressure Washing	1:50	1:75	1:100
Spill Control	1:1	1:5	1:10

20 oz. Aerosol

Item No.	013824
Unit Size	20 oz.
Unit Dimensions	9.5" H x 2.25" W x 2.25" D
Case Quantity	12
Case Dimensions	9.5" H x 11" W x 8.5" D
Case Weight	20 lbs.
Case Cubic	0.51
Pallet	18 x 5 = 90 Cases

32 oz. Quart

Item No.	013823
Unit Size	32 oz.
Unit Dimensions	9" H x 4" W x 3" D
Case Quantity	12
Case Dimensions	10.5" H x 11" W x 14.5" D
Case Weight	32 lbs.
Case Cubic	0.97
Pallet	12 x 4 = 48 Cases



20 oz. Aerosol



32 oz. Quart



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

Oil Baron PLUS removes the toughest hydrocarbon (oil, gas/diesel, tar) stains on most hard, industrial surfaces.

It can seem impossible to remove tough, deep oil, tar and grease stains in concrete or other hard surfaces. With Oil Baron PLUS, it's not only possible to regain a clean surface area, this easy-to-use product outperforms all other competitors.

Simply apply Oil Baron PLUS onto the effected surface area then scrub. It immediately does the hard work by penetrating deep into the surface to remove tough, embedded stains. Then just rinse for an oil-free surface. There's no waiting to see results. There are no worries about safety concerns you find with dangerous acids. Best of all, Oil Baron PLUS removes your frustration of cleaning up the toughest oil stains.



The advantages of Oil Baron Plus:

- Quickly penetrates deep into the material surface to immediately remove oil and tar stains
- Microbial action eliminates stains
- Outperforms dangerous acids, conventional degreasing and poultice products
- Easy and simple to use: Apply, scrub, rinse and you're done
- Economical: Treats up to 10x more surface area than competitive products

Works in these applications:

- Fueling areas
- Loading docks, parking lots, drive-throughs
- Manufacturing facilities
- Vehicle repair facilities
- Concrete parking garages

Ideal for deep cleaning:*

- Concrete
- Bricks
- Masonry
- Pavers

Removes tough stains caused by:

- Motor oil, tar, anti-freeze, grease and diesel fuel
- Brake, hydraulic, power steering and transmission fluid



Oil Baron Plus

Oil Baron PLUS removes the toughest hydrocarbon (oil, gas/diesel, tar) stains on most hard, industrial surfaces.

Comparison Chart

Compare

PRODUCT	TIME	CHEMISTRY	COVERAGES
Oil Baron PLUS	1 min.	Microbial Cleaner	75 sq. ft./20 oz.
Competitor 1	5-8 hrs.	Poultice	6 sq. ft./32 oz.
Competitor 2	5-8 hrs.	Poultice	18 sq. ft./32 oz.
Competitor 3	5 min.	Acid-Cleaner	50 sq. ft./0.5 gal.
Competitor 4	30 min.	Poultice	30 sq. ft./0.5 gal.

16 oz. Aerosol

Item No.	013826
Unit Size	16 oz.
Unit Dimensions	2.125" L x 2.125" W x 10.25" H
Case Quantity	12
Case Dimensions	11.25" L x 8.5" W x 10.25" H
Case Weight	15 lbs.
Case Cubic	0.56
Pallet	18 x 5 = 90 Cases

32 oz. Quart

Item No.	013825
Unit Size	32 oz.
Unit Dimensions	5.25" L x 2.0" W 7.75" H
Case Quantity	6
Case Dimensions	12.0" L x 6.0" W x 7.75" H
Case Weight	16 lbs.
Case Cubic	0.5
Pallet	12 x 4 = 48 Cases



32 oz. Quart



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Aviation Fueling Hoses



4113 Permanent



1-1

4113 Permanent Fitting aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.

- Used for commercial and private aircraft
- Resistant to jet fuel and higher aromatic aviation gasolines
- Compatible with use on hydrant service
- Meets EI 1529, 7th Edition, 2014 and European Standard EN ISO 1825 (2011), Type C, Grade 2, and NPFA 407
- Operating temperature -22 °F to +149 °F (-30 °C to +65 °C)
- Recommended for all types of riser deck, reel, and hydrant hose applications
- All aviation hose assemblies are 100% hydrostatic tested to 600 PSI and inspected for electrical continuity
- Every hose receives a unique serial number and test certificate



AVIATION FUELING HOSES

Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1" HOSES		
CP160024HABA	1" x 2' HEW 4113 MXM NPT BR NR	1.24 (0.6)
CP160180HABA	1" x 15' HEW 4113 MXM NPT BR NR	10.0 (4.5)
CP160360HABA	1" x 30' HEW 4113 MXM NPT BR NR	20.0 (9.1)
CP160420HABA	1" x 35' HEW 4113 MXM NPT BR NR	23.0 (10.5)
CP160472HABA	1" x 39' 4" HEW 4113 MXM NPT BR NR	25.0 (11.3)
CP160480HABA	1" x 40' HEW 4113 MXM NPT BR NR	26.0 (11.8)
CP160588HABA	1" x 49' HEW 4113 MXM NPT BR NR	30.4 (13.8)
CP160600HABA	1" x 50' HEW 4113 MXM NPT BR NR	32.0 (14.5)
CP160720HABA	1" x 60' HEW 4113 MXM NPT BR NR	38.0 (17.3)
CP160792HABA	1" x 66' HEW 4113 MXM NPT BR NR	42.0 (19.1)
CP160900HABA	1" x 75' HEW 4113 MXM NPT BR NR	48.0 (21.8)
CP160960HABA	1" x 80' HEW 4113 MXM NPT BR NR	51.0 (23.1)
CP161080HABA	1" x 90' HEW 4113 MXM NPT BR NR	57.0 (25.9)
CP161200HABA	1" x 100' HEW 4113 MXM NPT BR NR	63.0 (28.6)
CP161380HABA	1" x 115' HEW 4113 MXM NPT BR NR	71.3 (32.4)
CP161560HABA	1" x 130' HEW 4113 MXM NPT BR NR	80.6 (36.6)
1 1/4" HOSES		
CP200600HABA	1 1/4" x 50' HEW 4113 MXM NPT BR NR	42.0 (19.1)
CP200660HABA	1 1/4" x 55' HEW 4113 MXM NPT BR NR	45.0 (20.1)
CP200792HABA	1 1/4" x 66' HEW 4113 MXM NPT BR NR	54.0 (24.5)
CP200840HBBA	1 1/4" x 70' HEW 4113 MXF NPT BR NR	57.0 (25.9)
CP200900HABA	1 1/4" x 75' HEW 4113 MXM NPT BR NR	61.0 (27.8)
CP201176HABA	1 1/4" x 98' HEW 4113 MXM NPT BR NR	77.4 (35.2)
CP201200HBBA	1 1/4" x 100' HEW 4113 MXF NPT BR NR	81.0 (36.8)
CP201200HABA	1 1/4" x 100' HEW 4113 MXM NPT BR NR	81.0 (36.8)
1 1/2" HOSES		
CP240024HABA	1 1/2" x 2' HEW 4113 MXM NPT BR NR	1.7 (0.8)
CP240108HABA	1 1/2" x 9' HEW 4113 MXM NPT BR NR	11.0 (5.0)
CP240120HABA	1 1/2" x 10' HEW 4113 MXM NPT BR NR	12.0 (5.5)
CP240600HABA	1 1/2" x 50' HEW 4113 MXM NPT BR NR	51.0 (23.2)
CP240720HABA	1 1/2" x 60' HEW 4113 MXM NPT BR NR	61.0 (27.8)
CP240780HBBA	1 1/2" x 65' HEW 4113 MXF NPT BR NR	66.0 (30.0)
CP240792HABA	1 1/2" x 66' HEW 4113 MXM NPT BR NR	67.0 (30.5)
CP240840HABA	1 1/2" x 70' HEW 4113 MXM NPT BR NR	71.0 (32.3)
CP240900HABA	1 1/2" x 75' HEW 4113 MXM NPT BR NR	76.0 (34.5)
CP241020HABA	1 1/2" x 85' HEW 4113 MXM NPT BR NR	85.0 (38.6)
CP241200HABA	1 1/2" x 100' HEW 4113 MXM NPT BR NR	100.0 (45.5)
CP241200HBBA	1 1/2" x 100' HEW 4113 MXF NPT BR NR	100.0 (45.5)

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
CP240420HABA	1 1/2" x 35' HEW 4113 MXM NPT BR NR	36.0 (16.4)
CP240684HABA	1 1/2" x 57' HEW 4113 MXM NPT BR NR	49.0 (22.3)
CP240780HABA	1 1/2" x 65' HEW 4113 MXM NPT BR NR	66.0 (30.0)
CP241368HABA	1 1/2" x 114' HEW 4113 MXM NPT BR NR	98.0 (44.5)
CP241800HABA	1 1/2" x 150' HEW 4113 MXM NPT BR NR	129.0 (58.6)
2" HOSES		
CP320120HABA	2" x 10' HEW 4113 MXM NPT BR NR	16.0 (7.3)
CP320134HABA	2" x 11.17' HEW 4113 MXM NPT BR NR	13.4 (6.1)
CP320144HABA	2" x 12' HEW 4113 MXM NPT BR NR	19.0 (8.6)
CP320180HABA	2" x 15' HEW 4113 MXM NPT BR NR	23.0 (10.5)
CP320197HABA	2" x 16' 5" HEW 4113 MXM NPT BR NR	24.0 (10.9)
CP320216HABA	2" x 18' HEW 4113 MXM NPT BR NR	26.0 (11.8)
CP320240HABA	2" x 20' HEW 4113 MXM NPT BR NR	29.0 (13.2)
CP320420HABA	2" x 35' HEW 4113 MXM NPT BR NR	49.0 (22.3)
CP320480HABA	2" x 40' HEW 4113 MXM NPT BR NR	55.0 (25.0)
CP320564HABA	2" x 47' HEW 4113 MXM NPT BR NR	56.4 (25.6)
CP320600HABA	2" x 50' HEW 4113 MXM NPT BR NR	68.0 (30.9)
CP320600HBBA	2" x 50' HEW 4113 MXF NPT BR NR	68.0 (30.9)
CP320684HABA	2" x 57' HEW 4113 MXM NPT BR NR	68.4 (31.1)
CP320720HABA	2" x 60' HEW 4113 MXM NPT BR NR	81.0 (36.8)
CP320792HABA	2" x 66' HEW 4113 MXM NPT BR NR	89.0 (40.5)
CP320900HABA	2" x 75' HEW 4113 MXM NPT BR NR	101.0 (45.9)
2 1/2" HOSES		
CP400096HABA	2 1/2" x 8' HEW 4113 MXM NPT BR NR	19.0 (8.6)
CP400108HABA	2 1/2" x 9' HEW 4113 MXM NPT BR NR	20.0 (9.1)
CP400120HBBA	2 1/2" x 10' HEW 4113 MXF NPT BR NR	22.0 (10.0)
CP400120HABA	2 1/2" x 10' HEW 4113 MXM NPT BR NR	22.0 (10.0)
CP400144HABA	2 1/2" x 12' HEW 4113 MXM NPT BR NR	25.0 (11.4)
CP400156HABA	2 1/2" x 13' HEW 4113 MXM NPT BR NR	27.0 (12.3)
CP400192HABA	2 1/2" x 16' HEW 4113 MXM NPT BR NR	32.0 (14.5)
CP400197HABA	2 1/2" x 16' 5" HEW 4113 MXM NPT BR NR	33.0 (15.0)
CP400420HABA	2 1/2" x 35' HEW 4113 MXM NPT BR NR	64.0 (29.1)
CP400480HABA	2 1/2" x 40' HEW 4113 MXM NPT BR NR	73.0 (33.2)
CP400600HBBA	2 1/2" x 50' HEW 4113 MXF NPT BR NR	90.0 (40.9)
CP400600HABA	2 1/2" x 50' HEW 4113 MXM NPT BR NR	90.0 (40.9)
CP400660HABA	2 1/2" x 55' HEW 4113 MXM NPT BR NR	98.0 (44.5)
CP400720HABA	2 1/2" x 60' HEW 4113 MXM NPT BR NR	106.0 (48.2)
CP400084HABA	2 1/2" x 7' HEW 4113 MXM NPT BR NR	17.0 (7.7)
CP400118HABA	2 1/2" x 9' 3" HEW 4113 MXM NPT BR NR	20.0 (9.1)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

4113 Permanent Fitting aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
CP400132HABA	2 ¹ / ₂ " x 11' HEW 4113 MXM NPT BR NR	34.0 (15.5)
CP400180HABA	2 ¹ / ₂ " x 15' HEW 4113 MXM NPT BR NR	30.0 (13.6)
CP400240HABA	2 ¹ / ₂ " x 20' HEW 4113 MXM NPT BR NR	39.0 (17.7)
CP400684HABA	2 ¹ / ₂ " x 57' HEW 4113 MXM NPT BR NR	100.0 (45.5)
CP401200HBBA	2 ¹ / ₂ " x 100' HEW 4113 MXF NPT BR NR	174.0 (79.1)

3" HOSES

CP480096HABA	3" x 8' HEW 4113 MXM NPT BR NR	28.0 (12.7)
CP480108HABA	3" x 9' HEW 4113 MXM NPT BR NR	31.0 (14.1)
CP480120HABA	3" x 10' HEW 4113 MXM NPT BR NR	34.0 (15.5)
CP480132HABA	3" x 11' HEW 4113 MXM NPT BR NR	36.0 (16.4)
CP480144HABA	3" x 12' HEW 4113 MXM NPT BR NR	39.0 (17.7)
CP480168HABA	3" x 14' HEW 4113 MXM NPT BR NR	44.0 (20.0)
CP480180HABA	3" x 15' HEW 4113 MXM NPT BR NR	46.0 (20.9)
CP480240HABA	3" x 20' HEW 4113 MXM NPT BR NR	59.0 (26.8)
CP480360HBBA	3" x 30' HEW 4113 MXF NPT BR NR	85.0 (38.6)
CP480600HBBA	3" x 50 FT HEW 4113 MXF NPT BR NR	136.0 (61.8)
CP480600HABA	3" x 50' HEW 4113 MXM NPT BR NR	136.0 (61.8)
CP480720HABA	3" x 60' HEW 4113 MXM NPT BR NR	162.0 (73.6)

Construction

Tube	Black nitrile synthetic rubber
Cover	Black neoprene static dissipating/static conductive synthetic rubber (wrapped finish)
Reinforcement	Spiral-plied (4) synthetic fabric and one nylon breaker
Couplings	Permanent brass internally expanded fittings - male and female NPT (swivel nut) Reusable 4-bolt aluminum clamp fittings - male and female, NPT and BSP threads - all females have swivel nuts - available with brass, tin plated brass, and stainless inserts

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
3/4"	19	1.25	31.8	300	2.07	0.50	0.75
1"	25	1.50	38.0	300	2.07	0.62	0.93
1 1/4"	32	1.78	45.2	300	2.07	0.79	1.18
1 1/2"	38	2.06	52.3	300	2.07	0.86	1.28
2"	50	2.57	65.3	300	2.07	1.20	1.79
2 1/2"	63	3.20	81.2	300	2.07	1.69	2.52
3"	75	3.70	94.0	300	2.07	2.33	3.47
4"	102	4.94	125.0	300	2.07	3.30	4.92

Couplings

Permanent Brass	Internally expanded fittings (standard for 3/4" and 3" ID) - male NPT and female NPS (swivel nut)
Crimped on Stainless	Male NPT (zinc-plated ferrules) standard for 4" ID hose assemblies. Internally expanded brass male NPT and NPS are also available.
Reusable 4-Bolt	Aluminum clamp fittings - male and female, NPT and BSP threads - all females have swivel nuts - available with brass, tin-plated brass and stainless inserts.

Protective Coils

9746	2" Banding Coil, White
9744	3" Banding Coil, White
9774	4" Banding Coil, White

Order Guide (Ex. CP320600HABA)

AVIATION HOSE SIZE - CPSS

3/4" = CP12	2" = CP32
1" = CP16	2 1/2" = CP40
1 1/4" = CP20	3" = CP48
1 1/2" = CP24	4" = CP64

HOSE LENGTH (IN INCHES) - LLLL

0600 = 50 feet 0 inches
0606 = 50 feet 6 inches

AVIATION HOSE - H, C OR J

H = 4113 Aviation Hose
C = 4113CT Cold Temp
J = 5500 JacRiser Hose

FITTING STYLE - S

A = Male x Male NPT Not Reusable
B = Male x Female NPT not Reusable
C = Female x Female NPT Not Reusable
D = Male x Male NPT Reusable
E = Male x Female NPT Reusable
F = Female x Female NPT Reusable
J = Male x Male BSP Reusable
K = Male x Female BSP Reusable
L = Female x Female BSP Reusable
S = Special (See Note 1)

FITTING BRAND - F

A = Internal Expansion Permanent (stainless steel only)
B = Dixon/UMI Internal Expansion (Permanent (Brass Insert))
D = Dixon Swaged
E = Dixon Reusable
F = Elaflex Resuable
G = Roman Seliger Reusable

INSERT MATERIAL - M

A = Brass
B = Stainless Steel
D = Tin-Plated Brass
F = Carbon Steel

OVERALL LENGTH - O

For all sizes except CP64, if "0" is present, LLLL = OAL
For CP64 only, if blank, LLLL = OAL
For CP64 only, if "C" present, LLLL = Cut Length

NOTE:

If special, the next two digits will be used sequentially first using numbers (0-9) then using Alpha (A-Z). Special fittings or special materials will be described in the fab/shipping instructions section of the factory order. See separate assembly drawing for each special assembly number.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

4113 Reuseable



1-2

AVIATION FUELING HOSES

4113 with Reusable couplings aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.

- Used for commercial and private aircraft
- Resistant to jet fuel and higher aromatic aviation gasolines
- Compatible with use on hydrant service
- Meets EI 1529, 6th edition, 2005 and European Standard EN ISO 1825 (2011) and NPFA 407
- Recommended for all types of riser deck, reel, and hydrant hose applications
- All aviation hose assemblies are 100% hydrostatic tested to 600 PSI and inspected for electrical continuity
- Every hose receives a unique serial number and test certificate
- Standard hose assemblies are supplied with Roman Seliger brand 4-bolt aluminum clamp reusable couplings. Elaflex Spannloc are available on request.
- All 4" ID hoses utilize Roman Seliger 4-bolt aluminum clamped reusable fittings.

Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1 1/2" HOSES		
CP240720HKGB	1 1/2" X 60' 4113 MXF BSP SS RU	51.6 (23.5)
CP240792HEGA	1 1/2" X 66' 4113 MXF NPT BR RU	56.8 (25.8)
2" HOSES		
CP320720HKGB	2" x 60' 4113 MXF BSP SS RU	72.0 (32.7)
CP320720HKGA	2" x 60' 4113 MXF BSP BR RU	72.0 (32.7)
CP320792HEGA	2" x 66' 4113 MXF NPT BR RU	79.2 (36.0)
2 1/2" HOSES		
CP400120HEGD	2 1/2" x 10' 4113 MXF BSP TP RU	16.9 (7.7)
CP400144HEGD	2 1/2" x 12' 4113 MXF BSP TP RU	20.3 (9.2)
CP400156HDGB	2 1/2" x 13' 4113 MXM NPT SS RU	22.0 (10.0)
3" HOSES		
CP480144HEGD	3" x 12' 4113 MXF BSP TP RU	28.0 (12.7)
CP480168HABA	3" x 14' 4113 MXM NPT BR RU	32.6 (14.8)
CP480240HEGD	3" x 20' 4113 MXF BSP TP RU	46.6 (21.2)
CP480300HEGD	3" x 25' 4113 MXF BSP TP RU	58.3 (26.5)
CP480396HDGB	3" x 33' 4113 MXM NPT SS RU	76.9 (36.3)
CP480480HEGD	3" x 40' 4113 MXF BSP TP RU	93.2 (42.4)
4" HOSES		
CP640144HEGD	4" x 12' 4113 MXF BSP TP RU	39.6 (18.0)
CP640394HEGD	4" x 32.8' 4113 MXF BSP TP RU	108.2 (49.2)
CP640432HKGD	4" x 46' 4113 MXF BSP TP RU	151.8 (69.0)

Construction

Tube	Black nitrile synthetic rubber
Cover	Black neoprene static dissipating/static conductive synthetic rubber (wrapped finish)
Reinforcement	Spiral-plied (4) synthetic fabric and one nylon breaker





4113 Reusable

4113 with Reusable couplings aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.

Available in these Sizes

ID	NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT
3/4"	19	1.25	31.8	300	2.07	0.50
1"	25	1.50	38.0	300	2.07	0.62
1 1/4"	32	1.78	45.2	300	2.07	0.79
1 1/2"	38	2.06	52.3	300	2.07	0.86
2"	50	2.57	65.3	300	2.07	1.20
2 1/2"	63	3.20	81.2	300	2.07	1.69
3"	75	3.70	94.0	300	2.07	2.33
4"	102	4.94	125.0	300	2.07	3.30

Couplings

Permanent	Brass male and female NPT (swivel nut)
Reusable 4-bolt	Aluminum clamp fittings - male and female, NPT and BSP threads - all females have swivel nuts - available with brass, tin plated brass, and stainless inserts
	Aluminum male available for 2, 2 1/2 and 3-inch ID

Protective Coils

9746	2" Banding Coil, White
9744	3" Banding Coil, White
9774	4" Banding Coil, White
9793	3" Banding Coil, Orange

Order Guide (Ex. CP320600HABA)

AVIATION HOSE SIZE - CPSS

3/4" = CP12	2" = CP32
1" = CP16	2 1/2" = CP40
1 1/4" = CP20	3" = CP48
1 1/2" = CP24	4" = CP64

HOSE LENGTH (IN INCHES) - LLLL

0600 = 50 feet 0 inches
0606 = 50 feet 6 inches

AVIATION HOSE - H or J

H = 4113 Aviation Hose
J = 5500 JacRiser Hose

FITTING STYLE - S

A = Male x Male NPT Not Reusable
B = Male x Female NPT not Reusable
C = Female x Female NPT Not Reusable
D = Male x Male NPT Reusable
E = Male x Female NPT Reusable
F = Female x Female NPT Reusable
J = Male x Male BSP Reusable
K = Male x Female BSP Reusable
L = Female x Female BSP Reusable
S = Special (See Note 1)

FITTING BRAND - F

A = Internal Expansion Permanent (stainless steel only)
B = Dixon/UMI Internal Expansion (Permanent (Brass Insert))
D = Dixon Swaged
E = Dixon Reusable
F = Elaflex Resuable
G = Roman Seliger Reusable

INSERT MATERIAL - M

A = Brass
B = Stainless Steel
D = Tin-Plated Brass
F = Carbon Steel

OVERALL LENGTH - O

For all sizes except CP64, if "0" is present, LLLL = OAL
For CP64 only, if blank, LLLL = OAL
For CP64 only, if "C" present, LLLL = Cut Length



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

4113CT Permanent



1-3

4113CT Cold Temperature Hose Permanent Fitting aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.

- Used for commercial and private aircraft
- Resistant to jet fuel and higher aromatic aviation gasolines
- Compatible with use on hydrant service
- Meets EI 1529, 7th Edition, 2014 and European Standard EN ISO 1825 (2011), Type CT, Grade 2, NPFA 407 and MIL-DTL-6615G
- Operating temperature -67°F to +158°F (-55°C to +70°C)
- Recommended for all types of riser deck, reel, and hydrant hose applications
- All aviation hose assemblies are 100% hydrostatic tested to 600 PSI and inspected for electrical continuity
- Every hose receives a unique serial number and test certificate



AVIATION FUELING HOSES

Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
1" HOSES		
CP160024CABA	1" x 2' HEW 4113CT MM NPT BR NR	1.24 (0.6)
CP160180CABA	1" x 15' HEW 4113CT MM NPT BR NR	10.0 (4.5)
CP160360CABA	1" x 30' HEW 4113CT MM NPT BR NR	20.0 (9.1)
CP160420CABA	1" x 35' HEW 4113CT MM NPT BR NR	23.0 (10.5)
CP160472CABA	1" x 39' 4" HEW 4113CT MM NPT BR NR	25.0 (11.3)
CP160480CABA	1" x 40' HEW 4113CT MM NPT BR NR	26.0 (11.8)
CP160588CABA	1" x 49' HEW 4113CT MM NPT BR NR	30.4 (13.8)
CP160600CABA	1" x 50' HEW 4113CT MM NPT BR NR	32.0 (14.5)
CP160720CABA	1" x 60' HEW 4113CT MM NPT BR NR	38.0 (17.3)
CP160792CABA	1" x 66' HEW 4113CT MM NPT BR NR	42.0 (19.1)
CP160900CABA	1" x 75' HEW 4113CT MM NPT BR NR	48.0 (21.8)
CP160960CABA	1" x 80' HEW 4113CT MM NPT BR NR	51.0 (23.1)
CP161080CABA	1" x 90' HEW 4113CT MM NPT BR NR	57.0 (25.9)
CP161200CABA	1" x 100' HEW 4113CT MM NPT BR NR	63.0 (28.6)
CP161380CABA	1" x 115' HEW 4113CT MM NPT BR NR	71.3 (32.4)
CP161560CABA	1" x 130' HEW 4113CT MM NPT BR NR	80.6 (36.6)
1 1/4" HOSES		
CP200600CABA	1 1/4" x 50' HEW 4113CT MM NPT BR NR	42.0 (19.1)
CP200660CABA	1 1/4" x 55' HEW 4113CT MM NPT BR NR	45.0 (20.1)
CP200792CABA	1 1/4" x 66' HEW 4113CT MM NPT BR NR	54.0 (24.5)
CP200840CBBA	1 1/4" x 70' HEW 4113CT MF NPT BR NR	57.0 (25.9)
CP200900CABA	1 1/4" x 75' HEW 4113CT MM NPT BR NR	61.0 (27.8)
CP201176CABA	1 1/4" x 98' HEW 4113CT MM NPT BR NR	77.4 (35.2)
CP201200CBBA	1 1/4" x 100' HEW 4113CT MF NPT BR NR	81.0 (36.8)
CP201200CABA	1 1/4" x 100' HEW 4113CT MM NPT BR NR	81.0 (36.8)
1 1/2" HOSES		
CP240024CABA	1 1/2" x 2' HEW 4113CT MM NPT BR NR	1.7 (0.8)
CP240108CABA	1 1/2" x 9' HEW 4113CT MM NPT BR NR	11.0 (5.0)
CP240120CABA	1 1/2" x 10' HEW 4113CT MM NPT BR NR	12.0 (5.5)
CP240600CABA	1 1/2" x 50' HEW 4113CT MM NPT BR NR	51.0 (23.2)
CP240720CABA	1 1/2" x 60' HEW 4113CT MM NPT BR NR	61.0 (27.8)
CP240780CBBA	1 1/2" x 65' HEW 4113CT MF NPT BR NR	66.0 (30.0)
CP240792CABA	1 1/2" x 66' HEW 4113CT MM NPT BR NR	67.0 (30.5)
CP240840CABA	1 1/2" x 70' HEW 4113CT MM NPT BR NR	71.0 (32.3)
CP240900CABA	1 1/2" x 75' HEW 4113CT MM NPT BR NR	76.0 (34.5)
CP241020CABA	1 1/2" x 85' HEW 4113CT MM NPT BR NR	85.0 (38.6)
CP241200CABA	1 1/2" x 100' HEW 4113CT MM NPT BR NR	100.0 (45.5)
CP241200CBBA	1 1/2" x 100' HEW 4113CT MF NPT BR NR	100.0 (45.5)

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
CP240420CABA	1 1/2" x 35' HEW 4113CT MM NPT BR NR	36.0 (16.4)
CP240684CABA	1 1/2" x 57' HEW 4113CT MM NPT BR NR	49.0 (22.3)
CP240780CABA	1 1/2" x 65' HEW 4113CT MM NPT BR NR	66.0 (30.0)
CP241368CABA	1 1/2" x 114' HEW 4113CT MM NPT BR NR	98.0 (44.5)
CP241800CABA	1 1/2" x 150' HEW 4113CT MM NPT BR NR	129.0 (58.6)
2" HOSES		
CP320120CABA	2" x 10' HEW 4113CT MM NPT BR NR	16.0 (7.3)
CP320134CABA	2" x 11.17' HEW 4113CT MM NPT BR NR	13.4 (6.1)
CP320144CABA	2" x 12' HEW 4113CT MM NPT BR NR	19.0 (8.6)
CP320180CABA	2" x 15' HEW 4113CT MM NPT BR NR	23.0 (10.5)
CP320197CABA	2" x 16' 5" HEW 4113CT MM NPT BR NR	24.0 (10.9)
CP320216CABA	2" x 18' HEW 4113CT MM NPT BR NR	26.0 (11.8)
CP320240CABA	2" x 20' HEW 4113CT MM NPT BR NR	29.0 (13.2)
CP320420CABA	2" x 35' HEW 4113CT MM NPT BR NR	49.0 (22.3)
CP320480CABA	2" x 40' HEW 4113CT MM NPT BR NR	55.0 (25.0)
CP320564CABA	2" x 47' HEW 4113CT MM NPT BR NR	56.4 (25.6)
CP320600CABA	2" x 50' HEW 4113CT MM NPT BR NR	68.0 (30.9)
CP320600CBBA	2" x 50' HEW 4113CT MF NPT BR NR	68.0 (30.9)
CP320684CABA	2" x 57' HEW 4113CT MM NPT BR NR	68.4 (31.1)
CP320720CABA	2" x 60' HEW 4113CT MM NPT BR NR	81.0 (36.8)
CP320792CABA	2" x 66' HEW 4113CT MM NPT BR NR	89.0 (40.5)
CP320900CABA	2" x 75' HEW 4113CT MM NPT BR NR	101.0 (45.9)
2 1/2" HOSES		
CP400096CABA	2 1/2" x 8' HEW 4113CT MM NPT BR NR	19.0 (8.6)
CP400108CABA	2 1/2" x 9' HEW 4113CT MM NPT BR NR	20.0 (9.1)
CP400120CBBA	2 1/2" x 10' HEW 4113CT MF NPT BR NR	22.0 (10.0)
CP400120CABA	2 1/2" x 10' HEW 4113CT MM NPT BR NR	22.0 (10.0)
CP400144CABA	2 1/2" x 12' HEW 4113CT MM NPT BR NR	25.0 (11.4)
CP400156CABA	2 1/2" x 13' HEW 4113CT MM NPT BR NR	27.0 (12.3)
CP400192CABA	2 1/2" x 16' HEW 4113CT MM NPT BR NR	32.0 (14.5)
CP400197CABA	2 1/2" x 16' 5" HEW 4113CT MM NPT BR NR	33.0 (15.0)
CP400420CABA	2 1/2" x 35' HEW 4113CT MM NPT BR NR	64.0 (29.1)
CP400480CABA	2 1/2" x 40' HEW 4113CT MM NPT BR NR	73.0 (33.2)
CP400600CBBA	2 1/2" x 50' HEW 4113CT MF NPT BR NR	90.0 (40.9)
CP400600CABA	2 1/2" x 50' HEW 4113CT MM NPT BR NR	90.0 (40.9)
CP400660CABA	2 1/2" x 55' HEW 4113CT MM NPT BR NR	98.0 (44.5)
CP400720CABA	2 1/2" x 60' HEW 4113CT MM NPT BR NR	106.0 (48.2)
CP400084CABA	2 1/2" x 7' HEW 4113CT MM NPT BR NR	17.0 (7.7)
CP400118CABA	2 1/2" x 9' 3" HEW 4113CT MM NPT BR NR	20.0 (9.1)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



4113CT Permanent

4113CT Cold Temperature Hose Permanent Fitting aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
CP400132CABA	2 1/2" x 11' HEW 4113CT MM NPT BR NR	34.0 (15.5)
CP400180CABA	2 1/2" x 15' HEW 4113CT MM NPT BR NR	30.0 (13.6)
CP400240CABA	2 1/2" x 20' HEW 4113CT MM NPT BR NR	39.0 (17.7)
CP400684CABA	2 1/2" x 57' HEW 4113CT MM NPT BR NR	100.0 (45.5)
CP401200CBBA	2 1/2" x 100' HEW 4113CT MF NPT BR NR	174.0 (79.1)
3" HOSES		
CP480096CABA	3" x 8' HEW 4113CT MM NPT BR NR	28.0 (12.7)
CP480108CABA	3" x 9' HEW 4113CT MM NPT BR NR	31.0 (14.1)
CP480120CABA	3" x 10' HEW 4113CT MM NPT BR NR	34.0 (15.5)
CP480132CABA	3" x 11' HEW 4113CT MM NPT BR NR	36.0 (16.4)
CP480144CABA	3" x 12' HEW 4113CT MM NPT BR NR	39.0 (17.7)
CP480168CABA	3" x 14' HEW 4113CT MM NPT BR NR	44.0 (20.0)
CP480180CABA	3" x 15' HEW 4113CT MM NPT BR NR	46.0 (20.9)
CP480240CABA	3" x 20' HEW 4113CT MM NPT BR NR	59.0 (26.8)
CP480360CBBA	3" x 30' HEW 4113CT MF NPT BR NR	85.0 (38.6)
CP480600CBBA	3" x 50 FT HEW 4113CT MF NPT BR NR	136.0 (61.8)
CP480600CABA	3" x 50' HEW 4113CT MM NPT BR NR	136.0 (61.8)
CP480720CABA	3" x 60' HEW 4113CT MM NPT BR NR	162.0 (73.6)

Construction

Tube	Black nitrile synthetic rubber
Cover	Black neoprene static dissipating/static conductive synthetic rubber (wrapped finish)
Reinforcement	Spiral-plied (4) synthetic fabric and one nylon breaker
Couplings	Permanent brass internally expanded fittings - male and female NPT (swivel nut) Reusable 4-bolt aluminum clamp fittings - male and female, NPT and BSP threads - all females have swivel nuts - available with brass, tin plated brass, and stainless inserts

Technical Data for 4113CT Cold Temperature Fueling Hose

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
1"	25	1.457	37	300	2.07	0.54	0.80
1 ¹ / ₄ "	32	1.732	44	300	2.07	0.67	1.00
1 ¹ / ₂ "	38	2.008	51	300	2.07	0.81	1.20
2"	50	2.598	66	300	2.07	1.28	1.90
2 1/2"	63	3.110	79	300	2.07	1.61	2.40
3"	75	3.583	91	300	2.07	1.88	2.80

Couplings

Permanent Brass	Internally expanded fittings (standard for 1" and 3" ID) - male NPT and female NPS (swivel nut)
Crimped on Stainless	Male NPT (zinc-plated ferrules) standard for 4" ID hose assemblies. Internally expanded brass male NPT and NPS are also available.
Reusable 4-Bolt	Aluminum clamp fittings - male and female, NPT and BSP threads - all females have swivel nuts - available with brass, tin-plated brass and stainless inserts.

Protective Coils

9746	2" Banding Coil, White
9744	3" Banding Coil, White
9774	4" Banding Coil, White

Order Guide (Ex. CP320600CABA)

AVIATION HOSE SIZE - CPSS

3/4" = CP12	2" = CP32
1" = CP16	2 1/2" = CP40
1 1/4" = CP20	3" = CP48
1 1/2" = CP24	4" = CP64

HOSE LENGTH (IN INCHES) - LLLL

0600 = 50 feet 0 inches
0606 = 50 feet 6 inches

AVIATION HOSE - H, C OR J

H = 4113 Aviation Hose
C = 4113CT Cold Temp
J = 5500 JacRiser Hose

FITTING STYLE - S

A = Male x Male NPT Not Reusable
B = Male x Female NPT not Reusable
C = Female x Female NPT Not Reusable
D = Male x Male NPT Reusable
E = Male x Female NPT Reusable
F = Female x Female NPT Reusable
J = Male x Male BSP Reusable
K = Male x Female BSP Reusable
L = Female x Female BSP Reusable
S = Special (See Note 1)

FITTING BRAND - F

A = Internal Expansion Permanent (stainless steel only)
B = Dixon/UMI Internal Expansion (Permanent (Brass Insert))
D = Dixon Swaged
E = Dixon Reusable
F = Elaflex Resuable
G = Roman Seliger Reusable

INSERT MATERIAL - M

A = Brass
B = Stainless Steel
D = Tin-Plated Brass
F = Carbon Steel

OVERALL LENGTH - O

For all sizes except CP64, if "0" is present, LLLL = OAL
For CP64 only, if blank, LLLL = OAL
For CP64 only, if "C" present, LLLL = Cut Length

NOTE:

If special, the next two digits will be used sequentially first using numbers (0-9) then using Alpha (A-Z). Special fittings or special materials will be described in the fab/shipping instructions section of the factory order. See separate assembly drawing for each special assembly number.



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



JacRiser Fueling Hoses



Used in riser connection of aviation refuelers, hydrant cart servicers and tank farm connections.

- Used for commercial and private aircraft.
- Resistant to jet fuel and higher aromatic aviation gasolines.
- Premium fueling and defueling hose designed to achieve more than twice the cycle flexing capabilities (124000 plus cycles).
- Meets EI 1529, 7th Edition, 2014 and European Standard EN ISO 1825 (2011), Type E, Grade 2, NPFA 407
- Suitable for full vacuum service and high flex applications.
- Designed for flexible connection between hydrant cart or refueler chassis and adjustable riser platform.
- Functional in temperatures -40°F to 180°F (-40°C to 82°C).
- All aviation hose assemblies are 100% hydrostatic tested to 600 PSI and inspected for electrical continuity.
- Every hose receives a unique serial number and test certificate.

Swaged on Stainless Male NPT – 4 Inch ID Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
CP640092JADB	4" x 92" OAL JAC 5500 MXM NPT SS NR	51 (23.2)
CP640102JADB	4" x 102" OAL JAC 5500 MXM NPT SS NR	55 (25.0)
CP640132JADB	4" x 11' OAL JAC 5500 MXM NPT SS NR	66 (30.0)
CP640108JADB	4" x 9' OAL JAC 5500 MXM NPT SS NR	57 (25.9)
CP640420JADB	4" x 35' OAL JAC 5500 MXM NPT SS NR	171 (77.7)
CP640087JADB	4" x 87" OAL JAC 5500 MXM NPT SS NR	50 (22.7)
CP640128JADB	4" x 128" OAL JAC 5500 MXM NPT SS NR	65 (29.5)
CP640126JADB	4" x 10'6" OAL JAC 5500 MXM NPT SS NR	64 (29.1)
CP640110JADB	4" x 110" OAL JAC 5500 MXM NPT SS NR	54 (24.5)

Internally Expanded Brass Male NPT – 1-1/2, 2, 2-1/2 and 3 Inch ID Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
CP240480JABA	1-1/2" X 40' 5500 MXM NPT BR NR	54 (24.5)
CP240400JABA	1-1/2" X 70' 5500 MXM NPT BR NR	94 (42.6)
CP320480JABA	2" x 40' JAC 5500 MXM NPT BR NR	67 (30.4)
CP320900JABA	2" x 75' JAC 5500 MXM NPT BR NR	123 (55.8)
CP400120JABA	2-1/2" X 10' 5500 MXM NPT BR NR	25 (11.3)
CP400360JABA	2-1/2" X 30' 5500 MXM NPT BR NR	69 (31.3)
CP480180JABA	3" x 15' JAC 5500 MXM NPT BR NR	53 (24.0)
CP480300JABA	3" x 25' JAC 5500 MXM NPT BR NR	83 (37.6)
CP480144JABA	3" x 12' JAC 5500 MXM NPT BR NR	44 (20.0)
CP480096JABA	3" x 8' JAC 5500 MXM NPT BR NR	32 (14.5)

Construction

Tube	Black nitrile synthetic rubber
Cover	Black neoprene static dissipating/static conductive synthetic rubber (wrapped finish)
Reinforcement	Spiral-plied (4) synthetic fabric and one nylon breaker with dual wire helix construction



Above are examples of existing part numbers. Husky can build any hose to any length with a variety of fittings. Contact Husky for additional information if you do not see an assembly that matches your needs.

Used in riser connection of aviation refuelers, hydrant cart servicers and tank farm connections.

Dimensions and System Options

Available in these Sizes


ID		NOM OD		MAX WP		BEND RADIUS		WEIGHT	
Size	MM	IN	MM	PSI	MPA	IN	MM	LB/FT	KG/M
1-1/2"	38	2.18	55.4	300	2.07	6.0	152	1.27	1.89
2"	50	2.756	69.8	300	2.07	8.0	203	1.74	2.59
2-1/2"	63.5	3.22	81.9	300	2.07	10.0	254	2.13	3.17
3"	75	3.82	98.6	300	2.07	12.0	305	2.93	4.36
4"	102	4.97	126.2	300	2.07	16.0	406	4.40	6.55

Couplings

Permanent Brass	Internally expanded fittings (standard for 2" and 3" ID) - male NPT and female NPS (swivel nut)
Swaged on Stainless	Male NPT (zinc-plated ferrules) standard for 4" ID hose assemblies. Internally expanded brass male NPT and NPS are also available.
Reusable 4-Bolt	Aluminum clamp fittings - male and female, NPT and BSP threads - all females have swivel nuts - available with brass, tin-plated brass and stainless inserts.

Protective Coils

9746	2" Banding Coil, White
9744	3" Banding Coil, White
9774	4" Banding Coil, White
9793	3" Banding Coil, Orange



Order Guide (Ex. CP320600JABA)

AVIATION HOSE SIZE - CPSS

3/4" = CP12	2" = CP32
1" = CP16	2 1/2" = CP40
1 1/4" = CP20	3" = CP48
1 1/2" = CP24	4" = CP64

HOSE LENGTH (IN INCHES) - LLLL

0600 = 50 feet 0 inches
0606 = 50 feet 6 inches

AVIATION HOSE - H or J

H = 4113 Aviation Hose
J = 5500 JacRiser Hose

FITTING STYLE - S

A = Male x Male NPT Not Reusable
B = Male x Female NPT not Reusable
C = Female x Female NPT Not Reusable
D = Male x Male NPT Reusable
E = Male x Female NPT Reusable
F = Female x Female NPT Reusable
J = Male x Male BSP Reusable
K = Male x Female BSP Reusable
L = Female x Female BSP Reusable
S = Special (See Note 1)

FITTING BRAND - F

A = Internal Expansion Permanent (stainless steel only)
B = Dixon/UMI Internal Expansion (Permanent (Brass Insert)
D = Dixon Swaged
E = Dixon Reusable
F = Elaflex Resuable
G = Roman Seliger Reusable

INSERT MATERIAL - M

A = Brass
B = Stainless Steel
D = Tin-Plated Brass
F = Carbon Steel

OVERALL LENGTH - O

For all sizes except CP64, if "0" is present, LLLL = OAL
For CP64 only, if blank, LLLL = OAL
For CP64 only, if "C" present, LLLL = Cut Length

NOTE:

If special, the next two digits will be used sequentially first using numbers (0-9) then using Alpha (A-Z). Special fittings or special materials will be described in the fab/shipping instructions section of the factory order. See separate assembly drawing for each special assembly number.



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Couplings



In order to meet and comply with EI 1529 and EN ISO 1825 specifications, all Hewitt® aviation hoses are supplied with either permanent or reusable couplings.

Permanent Couplings

- Internally expanded brass and stainless fittings. Stainless available upon request.
- NPT male and NPSH female threads (swivel nuts on female fittings)
- Swaged stainless male NPT insert with zinc-plated ferrule (Standard on 4" only).
- 4" internally expanded brass male NPT and NPSH female inserts are available as options.

Reusable Couplings

- 4-bolt aluminum clamps with brass, tin-plated brass or stainless inserts
- NPT male, NPSH female, BSP male and BSP female threads (swivel nuts on female fittings)
- Reusable fittings are available as separate items on request.

Adaptors

- Any of the above fittings can be supplied with adaptors such as Cam & Groove and threaded flanges.
- Dixon "Boss" Cam & Groove fittings are USA made. Imported versions are available.
- Stainless, brass, and aluminum step-up bushings.
- Stainless, carbon steel and aluminum threaded flanges.





Aviation Couplings



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Protective Coils



Spiral Hose Protectors



Hewitt

AVIATION FUELING PRODUCTS

4-1

PROTECTIVE COILS

Used to extend hose life, prevent kinking and reduce abrasion.

- Excellent for extending hose life, preventing kinking on deck and reel hoses, and reducing abrasion to hose cover.
- Installing coils at hose reel outlet riser will prevent hose collapse and maintain high fuel flow.
- Covers from 2 to 4 feet.
- Available to fit 1" to 4" ID aviation hose.
- Easily installed by factory or in the field.
- Standard white hose coils available from stock.
- Special colors and extra tough urethane hose protector coil available upon request.

Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT FT/LBS.
9746	2" Banding Coil, White	0.6385
9744	3" Banding Coil, White	1.2260
9774	4" Banding Coil, White	1.5710
9793	3" Banding Coil, Orange	1.2260

Construction

Material	PVC
----------	-----





Spiral Hose Protectors



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Deadman Hoses



Twin 1/4-Inch



5-1

DEADMAN HOSES

Used in connection of deadman control during aircraft servicing.

- Integral assembly for use with the deadman control valve.
- Vertically braided textile.
- Twinned 1/4" diameter red and green hose is vulcanized.
- Highly resistant to oil.
- Available in bulk or with crimped-on male or female swivel fittings.

Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
9742	Hose, A, 1/4" Deadman Twinline	0.20 (0.09)

Spring Guards

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS.
9878	1/4" x 50' Dead MXF with spring guard	11.25

Construction

Tube	Nitrile synthetic rubber, RMA Class A
Color	One red hose, one green hose



Used in connection of deadman control during aircraft servicing.

Dimensions and System Options

Available in these Sizes


ID (IN)	ID (MM)	SPIRALS	OD (IN)	OD (MM)	LB/FT	KG/M
1/4	6.4	2	34/64	13.5	0.19	0.28

Fittings

Crimped on male or female swivels.

Options

Available in cut lengths assembled or in bulk (approx. 700 ft. per reel).



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





Sensing Hoses



Twin $\frac{3}{8}$ -Inch



6-1

Used in connection of aircraft servicers and airport hydrants and sensing control systems.

- Integral assembly to connect aircraft servicers to airport hydrant reference and sensing control systems.
- Vertically braided textile.
- Twinned $\frac{3}{8}$ " diameter yellow and green hose is vulcanized.
- Highly resistant to oil.
- Available in bulk or with crimped-on male or female swivel fittings.

Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
9743	Hose, A, $\frac{3}{8}$ " Sensing Hose Twinline	0.29 (0.13)

Construction

Tube	Nitrile synthetic rubber, RMA Class A
Color	One yellow, one green hose



SENSING HOSES

Used in connection of aircraft servicers and airport hydrants and sensing control systems.

Dimensions and System Options

Available in these Sizes


ID (IN)	ID (MM)	SPIRALS	OD (IN)	OD (MM)	LB/FT	KG/M
³ / ₈	9.5	2	21/32	16.6	0.29	0.43

Fittings

Crimped on male or female swivels.

Options

Available in cut lengths assembled or in bulk (approx. 700 ft. per reel).



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Aviation Fueling Nozzles

Osprey Nozzle



7-1

OSPREY AVIATION NOZZLE

Automatic shut-off nozzle for over-the-wing fueling of aircraft.

- Specifically designed for business and private over-the-wing aviation fueling.
- Automatic shut-off when wing tanks are full.
- Easy to remove and clean fuel 100 mesh SS fuel filter assembly.
- Nozzle comes with red full grip guard to identify use only with aviation fuel or black full grip guard for jet fuel application if desired.
- Complies with EI1540 and NFPA 407.

Osprey Nozzle with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
1149812N [^]	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard and mesh filter	4.6 (2.0)
		[^] NOT LISTED

Osprey Nozzle with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
1149840N [^]	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard and mesh filter	4.6 (2.0)
		[^] NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon [®]
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Automatic shut-off nozzle for over-the-wing fueling of aircraft.


Dimensions and System Options

Swivels

MODEL NO.	DESCRIPTION
008517	1" M x 1" F NPT Single Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Accessories

MODEL NO.	DESCRIPTION
011817	Electrical Grounding Plug
012141	Osprey Spout Assembly Kit
011946	Spout Cap Assembly
012148	Strainer BSP Kit
012143	Strainer NPT Kit



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Osprey S Nozzle



7-2

OSPREY S AVIATION NOZZLE

Automatic shut-off nozzle for over-the-wing fueling of aircraft.

- Specifically designed for business and private over-the-wing aviation fueling.
- Osprey S nozzle prevents draining of fuel from fueling hose. The nozzle shuts off when
 - the pump shuts off.
 - the fuel tank is full.
 - the lever is opened before the pump is turned on.
- Easy to remove and clean 100 mesh SS fuel filter assembly.
- Nozzle comes with red full grip guard to identify use only with AvGas or black full grip guard for jet fuel application if desired.
- Complies with EI1540 and NFPA 407.

Osprey S Nozzle with NPT


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
1212312N [^]	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard and mesh filter	4.6 (2.0)
		[^] NOT LISTED

Osprey S Nozzle with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
1212340N [^]	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard and mesh filter	4.6 (2.0)
		[^] NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon [®]
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT and BSPP



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Osprey S Nozzle

Automatic shut-off nozzle for over-the-wing fueling of aircraft.


Dimensions and System Options

Swivels

MODEL NO.	DESCRIPTION
008517	1" M x 1" F NPT Single Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
003306	1" M x 1" F BSPP Multi-Plane Swivel
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel

Accessories

MODEL NO.	DESCRIPTION
011817	Electrical Grounding Plug
012139	Osprey S Spout Assembly Kit
011946	Spout Cap Assembly
012148	Strainer BSP Kit
012143	Strainer NPT Kit



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Falcon Manual Nozzle



9-2

FALCON AVIATION NOZZLE

Manual shut-off nozzle for over-the-wing fueling of aircraft.

- Specifically designed for business and private over-the-wing aviation fueling.
- Spout can be removed by loosening nut.
- 100 mesh stainless steel fuel filter to prevent dust and debris from entering the fuel tank; located in the spout for easy removal and cleaning.
- Complies with IE 1540 and NPA 407.
- Black jet fuel nozzle with optional duck bill spout or round spout.
- Red aviation gas nozzle with round spout.
- Available with the following inlets:
1-1/2" (38mm) Female NPT
1-1/2" (38mm) Female BSPP
1-1/4" (32mm) Female NPT
1-1/4" (32mm) Female BSPP



Falcon Nozzle with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
12090218N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1½ FNPT (38mm) Inlet Inline Swivel	5.0 (2.3)
12090219N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1¼ FNPT (32mm) Inlet Inline Swivel	5.0 (2.3)
13734218N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1½ FNPT (38mm) Inlet Inline Swivel	5.0 (2.3)
13734219N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1¼ FNPT (32mm) Inlet Inline Swivel	5.0 (2.3)
13739218N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1½ FNPT (38mm) Inlet Inline Swivel	5.0 (2.3)
13739219N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1¼ FNPT (32mm) Inlet Inline Swivel	5.0 (2.3)

[^] NOT LISTED


Falcon Nozzle with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
12090216N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1½ FBSP (38mm) Inlet Inline Swivel	5.0 (2.3)
12090217N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1¼ FBSP (32mm) Inlet Inline Swivel	5.0 (2.3)
13734216N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1½ FBSP (38mm) Inlet Inline Swivel	5.0 (2.3)
13734217N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1¼ FBSP (32mm) Inlet Inline Swivel	5.0 (2.3)
13739216N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1½ FBSP (38mm) Inlet Inline Swivel	5.0 (2.3)
13739217N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1¼ FBSP (32mm) Inlet Inline Swivel	5.0 (2.3)

[^] NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Manual shut-off nozzle for over-the-wing fueling of aircraft.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
012086	Falcon Strainer Kit
012946	Jet Oval Manual Spout Kit
012948	Aviation Round Manual Spout Kit
013476	Interlock Hook Assembly
014204	Black Jet Fuel Oval Spout Cap Assembly
014205	Black Jet Fuel Round Spout Cap Assembly
014206	Red Aviation Fuel Round Spout Cap Assembly
015829	Falcon Poppet Valve Seal Service Kit



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Falcon Manual Quick Disconnect Nozzle



9-3

FALCON AVIATION NOZZLE

Manual shut-off nozzle for over-the-wing fueling of aircraft.

- Specifically designed for business and private over-the-wing aviation fueling.
- Quick disconnect spout feature for easy removal.
- 100 mesh stainless steel fuel filter to prevent dust and debris from entering the fuel tank; located in the spout for easy removal and cleaning.
- Complies with IE 1540 and NPA 407.
- Black jet fuel nozzle with optional duck bill spout or round spout.
- Red aviation gas nozzle with round spout.
- Available with the following inlets:
1-1/2" (38mm) Female NPT
1-1/2" (38mm) Female BSPP
1-1/4" (32mm) Female NPT
1-1/4" (32mm) Female BSPP



Falcon Nozzle with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
13731218N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1½ FNPT (38mm) Inlet Inline Swivel	5.0 (2.3)
13731219N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1¼ FNPT (32mm) Inlet Inline Swivel	5.0 (2.3)
13736218N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1½ FNPT (38mm) Inlet Inline Swivel	5.0 (2.3)
13736219N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1¼ FNPT (32 mm) Inlet Inline Swivel	5.0 (2.3)
13742218N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1½ FNPT (38mm) Inlet Inline Swivel	5.0 (2.3)
13742219N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1¼ FNPT (32mm) Inlet Inline Swivel	5.0 (2.3)

[^] NOT LISTED


Falcon Nozzle with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
13731216N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1½ FBSP (38mm) Inlet Inline Swivel	5.0 (2.3)
13731217N [^]	without Hold Open Clip, with Jet Black, Duck Bill Spout, and 1¼ FBSP (32mm) Inlet Inline Swivel	5.0 (2.3)
13736216N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1½ FBSP (38mm) Inlet Inline Swivel	5.0 (2.3)
13736217N [^]	without Hold Open Clip, with Jet Black, Round Spout, and 1¼ FBSP (32mm) Inlet Inline Swivel	5.0 (2.3)
13742216N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1½ FBSP (38mm) Inlet Inline Swivel	5.0 (2.3)
13742217N [^]	without Hold Open Clip, with Aviation Red, Round Spout, and 1¼ FBSP (32mm) Inlet Inline Swivel	5.0 (2.3)

[^] NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Manual shut-off nozzle for over-the-wing fueling of aircraft.

Dimensions and System Options

Accessories

MODEL NO.	DESCRIPTION
012086	Falcon Strainer Kit
012947	Jet Oval Quick Disconnect Manual Spout Kit
012949	Aviation Quick Disconnect Round Manual Spout Kit
013476	Interlock Hook Assembly
014204	Black Jet Fuel Oval Spout Cap Assembly
014205	Black Jet Fuel Round Spout Cap Assembly
014206	Red Aviation Fuel Round Spout Cap Assembly
015829	Falcon Poppet Valve Seal Service Kit



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Aviation Swivels

High volume swivels for over-the-wing fueling of aircraft.

- Prevents kinking and twisting of hose.
- Unique stainless steel ball bearing design provides easier joint movement during high pressure applications.
- Easier to angle the nozzle into fill openings.

NPT x BSPP


MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
012799	1½" x 1½" BSPP Long Thread Single Plane Swivel	1.4 (.65)
012800	1¼" x 1½" BSPP Long Thread Single Plane Swivel	1.4 (.65)

BSPP x BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
013517	1¼" F x 1½" M Long Thread Single Plane Swivel	1.4 (.65)
013518	1½" F x 1½" M Long Thread Single Plane Swivel	1.4 (.65)

Construction

Body	Aluminum
Seals	Fluorocarbon



High volume swivels for over-the-wing fueling of aircraft.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Aviation Spouts

Falcon Spouts



11-1

AVIATION SPOUTS

Spout assemblies.

- Replacement spout assemblies for nozzles that attach to the nozzle with a nut.
- Replacement spout assemblies for nozzles that attach to a nozzle with a quick disconnect.
- Duck bill spout assemblies for use with jet fuel only.
- Round spout assemblies for use with both aviation and jet fuel.

Falcon Nut Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
012946	Duck Bill Spout Assembly for Jet Fuel	.6 (.27)
012948	Round Spout Assembly for Aviation and Jet Fuel	.5 (.23)

Falcon Quick Disconnect Spout Assemblies

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
012947	Duck Bill Spout Assembly for Jet Fuel	.5 (.23)
012949	Round Spout Assembly for Aviation and Jet Fuel	.5 (.23)



012946



012947



012948



012949

Falcon Nut Spout Assembly

Falcon Quick Disconnect Spout Assembly




Spout assemblies.

Dimensions



012946
012947



012948
012949



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Aviation Strainers

Aviation NPT Strainer



12-1

AVIATION NPT STRAINER

Strainer for over-the-wing fueling of aircraft.

- Easy to remove and clean fuel 100 mesh SS fuel filter assembly.
- Complies with IE1540 and NPA 407.
- Simple Male NPT x Female NPT strainer adaptor for multipurpose uses in fluid transfer.
- Suitable for aviation fueling and other compatible fluids.

Strainer

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
014024	3/4" NPT F x 3/4" NPT	1.5 (.8)

Construction

Body	Aluminum
Strainer	Stainless Steel
Inlet	3/4" (19mm) NPT threads



Strainer for over-the-wing fueling of aircraft.

Dimensions



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Loading Arms

SGA Loading Arm



The new Roman Seliger SGA Loading Arm is a safe and easy arrangement for transfer of liquid and gas products to tanker cars, tanker trucks, and vessels. This simple loading arm supports a loading transfer hose and allows for easy and safe movement of the transfer hose to and from the loading vehicle or car from a stowed position. Operator is not required to lift the hose. The loading arm supports all the weight. Any type of hose can be used with the SGA loading arm along with dry breaks, breakaways, or special attachment couplings.

- Special flexible joint mechanism makes it impossible for the loading arm radius to go below the minimum safe bending radius of the hose assembly and extends the life of hose.
- Eliminates wear and tear on hose cover and reduces operator injuries.
- Special spring or gas operated mechanisms can be added to allow operator to rise and lower arm with minimal effort.
- Lower maintenance time and cost.
- Lower risk of damage.
- Suitable for heavy or heated hoses and fittings.
- Maximum transfer rate.
- RS system meets highest safety requirements.
- Each SGA hose loading arm is made to measure for a particular application and conditions of use.



Components

Mounting brackets (wall, foot or other types)
Hose loading arm
Heading section (for top loading, bottom loading, etc.)

Couplings

Breakaway coupling
Dry disconnect coupling
Specialty hose to tanker, truck, or vessel connectors

Construction



Material	Stainless steel 1.4301/1.4401, steel 1.0037 RAL 5002, steel 1.0037 galvanized
Nominal length	6 to 20 feet (2 to 6 meters)
Nominal width	1 to 4 inch (25 to 100 mm)
Bending radius	6 to 17.75 inches (150 to 450 mm)
Types	Top loading, bottom loading, and floor loading



Husky/Hewitt is the Authorized US Rep for RS loading arms and couplings.



SGA Loading Arm



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.





enevo

LOGISTICS OPTIMIZATION

Sensors

WE-008L Sensor



1-1

LIQUID LEVEL SENSORS

The WE-008L sensor is a wireless tank fill level monitoring device. This innovation features state-of-the-art measurement and communication technologies to enable logistical efficiency.

- Instant value through ease-of-use
- Military-grade lithium battery technology provides an extremely long battery life
- Global coverage — partnerships with more than a hundred telecom operators globally to ensure growth
- Analytics offer at-a-glance graphs, alerts and reports
- Monitors non-combustible liquids including:
 - New or waste oil
 - Diesel or biodiesel fuel
 - Waste water
- Sensor and server software continuously improved; reliable, world-class technology

Specifications

DIMENSIONS	WEIGHT LBS
6.5" (H) x 4.7" (W)	1.3

Environmental

IP Rating: IP 69

Operational temperature: -40° F/+175° F — -40° C/80° C

Communication

2G/3G penta-band 850/900/1800/1900/2100 Mhz

Power

3.6V Lithium battery

Materials

Glass fiber reinforced polypropylene, proprietary polyurethane

Measurement

Up to 16 ft

Accuracy +/- 0.4"

Installation

1.5" and 2" NPT threads



The WE-008L sensor is a wireless tank fill level monitoring device. This innovation features state-of-the-art measurement and communication technologies to enable logistical efficiency.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

distributed by:
Acterra Group, Inc. | 800.289.7371 | www.acterragroup.com